



**THE DATASHEET OF  
FCCR16801ABTP**



Spec. No.: FCCR-K-HTS-0001 /5

Date: 2017. 1. 10

# Specification

Title: CHIP FUSE; RECTANGULAR TYPE

Style: FCCR10,16

RoHS COMPLIANCE ITEM

Halogen and Antimony Free

Product specification contained in this specification  
are subject to change at any time without notice  
If you have any questions or a Purchasing Specification for any quality  
Agreement is necessary, please contact our sales staff.



**釜屋電機株式會社**  
**KAMAYA ELECTRIC CO., LTD.**

Hokkaido Research Center  
Approval by: T. Sannomiya  
Drawing by: M. Shibuya

Note: Stock conditions

Temperature: +5°C ~ +35°C

Relative humidity: 25% ~ 75%

The period of guarantee: Within 2 year from shipment by the company.

Solderability shall be satisfied.

## 1. Scope

1.1 This specification covers the detail requirements for chip fuses; rectangular type, style of FCCR10,16.

### 1.2 Applicable documents

UL248-1-2000 Low-Voltage Fuses-Part1: General Requirements

UL248-14-2000 Low-Voltage Fuses-Part14: Supplemental Fuses

CSA C22.2 No.248.1-2000 Low-Voltage Fuses-Part1: General Requirements

CSA C22.2 No.248.14-2000 Low-Voltage Fuses-Part14: Supplemental Fuses

IEC60127-1 Miniature fuses-part 1: Definitions for miniature fuses and general requirements for miniature fuse-links

IEC60127-4 Miniature fuses-Part4: Universal modular fuse-links (UMF)

## 2. Classification

Type designation shall be the following form.

(Example) 

|      |    |     |    |    |
|------|----|-----|----|----|
| FCCR | 10 | 201 | AB | PA |
| 1    | 2  | 3   | 4  | 5  |

Style

1 Chip fuses; rectangular type  Style

2 Size

3 Rated current

|     |             |
|-----|-------------|
| 201 | 201--> 0.2A |
|-----|-------------|

4 Optional code

| Symbol | Content  |
|--------|----------|
| AB     | Standard |

5 Packaging form

|    |                      |
|----|----------------------|
| B  | Bulk (loose package) |
| PA | Press pocket taping  |
| TP | Paper taping         |

## 3. Safety standard approval

- UL248-1 and UL248-14
- CSA C22.2, No. 248.1-00 and CSA C22.2, No. 248.14-00

The file number to be designated by UL and C-UL shall be as follows: E176847

## 4. Rating

4.1 The ratings shall be in accordance with Table-1.

Table-1

| Style  | Rated current |       |                | Internal resistance value (mΩ max.) | Rated voltage (V) | Breaking capacity (A) | Time / current characteristic |                 |
|--------|---------------|-------|----------------|-------------------------------------|-------------------|-----------------------|-------------------------------|-----------------|
|        | Symbol        | (A)   | Marking symbol |                                     |                   |                       | Current                       | Pre-arcing time |
| FCCR10 | 151           | 0.15  | ∩              | 1850                                | DC24              | 35                    | 200%                          | 5 s max.        |
|        | 201           | 0.2   | Z              | 1250                                |                   |                       |                               |                 |
|        | 251           | 0.25  | C              | 880                                 |                   |                       |                               |                 |
|        | 321           | 0.315 | D              | 600                                 |                   |                       |                               |                 |
|        | 401           | 0.4   | E              | 400                                 |                   |                       |                               |                 |
|        | 501           | 0.5   | F              | 300                                 |                   |                       |                               |                 |
| FCCR16 | 151           | 0.15  | OB             | 2300                                | DC50              | 50                    | 200%                          | 5 s max.        |
|        | 201           | 0.2   | ZB             | 1350                                |                   |                       |                               |                 |
|        | 251           | 0.25  | CB             | 1000                                |                   |                       |                               |                 |
|        | 321           | 0.315 | DB             | 600                                 |                   |                       |                               |                 |
|        | 401           | 0.4   | EB             | 450                                 |                   |                       |                               |                 |
|        | 501           | 0.5   | FB             | 300                                 |                   |                       |                               |                 |
|        | 631           | 0.63  | IB             | 220                                 |                   |                       |                               |                 |
|        | 751           | 0.75  | AB             | 190                                 |                   |                       |                               |                 |
|        | 801           | 0.8   | KB             | 165                                 |                   |                       |                               |                 |
|        | 102           | 1.0   | LB             | 130                                 |                   |                       |                               |                 |
|        | 132           | 1.25  | MB             | 110                                 |                   |                       |                               |                 |
|        | 152           | 1.5   | HB             | 90                                  |                   |                       |                               |                 |
|        | 162           | 1.6   | NB             | 75                                  |                   |                       |                               |                 |
|        | 202           | 2.0   | SB             | 65                                  |                   |                       |                               |                 |
| 252    | 2.5           | TB    | 40             |                                     |                   |                       |                               |                 |

4.2 Working temperature range: -55 to +125(°C)

## 5. Packaging form

The standard packaging form shall be in accordance with Table-2.

Table-2

| Symbol | Packaging form                     |                        | Standard packaging quantity / units | Application |
|--------|------------------------------------|------------------------|-------------------------------------|-------------|
| B      | Bulk (loose package)               |                        | 1,000 pcs.                          | FCCR10,16   |
| PA     | Press pocket taping (paper taping) | 8mm width, 2mm pitches | 10,000 pcs.                         | FCCR10      |
| TP     | Paper taping                       | 8mm width, 4mm pitches | 5,000 pcs.                          | FCCR16      |

## 6. Dimensions

6.1 The resistor shall be of the design and physical dimensions in accordance with Figure-1 and Table-3.




Figure-1

Table-3

Unit:mm

| Style  | L        | W                                     | H         | c        | d         |
|--------|----------|---------------------------------------|-----------|----------|-----------|
| FCCR10 | 1.0±0.05 | 0.5±0.05                              | 0.4±0.05  | 0.2±0.1  | 0.25±0.10 |
| FCCR16 | 1.6±0.1  | 0.8 <sup>+0.15</sup> <sub>-0.05</sub> | 0.45±0.10 | 0.3±0.15 | 0.3±0.1   |

## 6.2 Net weight (Reference)

| Style  | Net weight(mg) |
|--------|----------------|
| FCCR10 | 0.8            |
| FCCR16 | 2              |

## 7. Marking

The Marking symbol of Sub-clause 4.1 shall be marked on over coat side.

(Example)

| Style  | Optional code | Marking symbol | Content       |
|--------|---------------|----------------|---------------|
| FCCR10 | AB            | Z              | FCCR10 201 AB |
| FCCR16 | AB            | EB             | FCCR16 401 AB |

## 8. Performance

8.1 Unless otherwise specified, the standard range of atmospheric conditions for tests is as follows;

Ambient temperature: 5 °C to 35 °C, Relative humidity: 45 % to 85 %, Air presser: 86 kPa to 106 kPa

If there is any doubt the results, measurements shall be made within the following:

Ambient temperature: 20 °C ± 2 °C, Relative humidity: 60 % to 70 %, Air presser: 86 kPa to 106 kPa

8.2 The performance shall be satisfied in Table-4.

Table-4(1)

| No. | Test items                                 | Condition of test   | Performance requirements   |         |                 |
|-----|--|---|--|---------|-----------------|
| 1   | Temperature rise                           | The fuse shall be mounted on the test substrate as shown in Figure-2.<br>Measurement temp.: 10 °C to 30 °C<br>Test current: Rated current<br>The temperature at the hottest point on the surface of the fuse shall be measured after temperature equilibrium has been attained.         | 75 °C max.   |         |                 |
| 2   | Current carrying capacity                  | The fuse shall be mounted on the test substrate as shown in Figure-2.<br>Test current: 110 % of Rated current<br>Test temp.: 70 °C ± 2 °C<br>Test period: 1h  | Without opening  |         |                 |
| 3   | Time / current characteristic              | The fuse shall be mounted on the test substrate as shown in Figure-2.<br>Test current shall be applied for continuously.  | Optional code  | Current | Pre-arcing time |
|     |  |   | AB   | 200%    | 5 s max.        |
| 4   | Terminal bond strength of the face plating | JIS C 60068-2-21 Ue1<br>The fuse shall be mounted on the test substrate as shown in Figure-2.<br>Bending value: 3 mm (Among the fulcrums: 90 mm)<br>Duration: 10 s ± 1 s  | Change of internal resistance: ±10%<br>No evidence of mechanical damage.                     |         |                 |
| 5   | Resistance to soldering heat               | Test by a piece.<br>Temp. of solder bath: 260 °C ± 5 °C<br>Immersion time: 10 s ± 1 s<br>After immersion into solder, leaving the room temp. for 1h or more, and then measure the internal resistance.  | Change of internal resistance: ±10%<br>No evidence of appearance damage                      |         |                 |
|     |  | <ul style="list-style-type: none"> <li>Reflow soldering</li> </ul> Pre-heating: 150 °C ~ 180 °C, 120 s max.<br>Peak: 260 °C ± 5 °C, 10 s max.<br>Reflow cycle: 2 times<br>After immersion into solder, leaving the room temp. for 1h or more, and then measure the internal resistance. |  |         |                 |
| 6   | Solderability                              | JIS C 60068-2-58<br>Test by a piece<br>Flux: Rosin-Methanol<br>Temp. of solder: bath: 235 °C ± 5 °C<br>Immersion time: 2 s ± 0.5 s  | The surface of terminal immersed shall be min. of 95 % covered with a new coating of solder. |         |                 |

Table-4(2)

| No. | Test items               | Condition of test  | Performance requirements  |
|-----|--------------------------|--|---|
| 7   | Rapid change temperature | JIS C 60068-2-14 Na<br>The fuse shall be mounted on the test substrate as shown in Figure-2.<br>Upper temperature: +125 °C<br>Lower temperature: -55 °C<br>Duration of exposure at each temperature: 30 min.<br>Number of cycles: 5 cycles   | Change of internal resistance: ±10%<br>No evidence of appearance damage   |
| 8   | Endurance test           | The fuse shall be mounted on the test substrate as shown in Figure-2.<br>Test condition: Nominal ambient temp. and Relative humidity.<br>Test potential:<br>1. Cycle of 1 h "ON" and 15 min. "OFF" at 1.05 times rated current for 100 cycles.<br>2. After above the test , 1.25 times rated current for 1h. | The voltage drop across the fuse after the test shall not have increased by more than 10 % of the value measured before test. |

9. Test substrate




Figure-2 FCCR TEST SUBSTRATE

Remark 1). Material: Epoxide woven glass  
Thickness: 1.6mm Thickness of copper clad: 0.035mm

10. Taping

10.1 Applicable documents JIS C 0806-3: 2014, EIAJ ET-7200C: 2010

10.2 Taping dimensions

10.2.1 Press pocket taping(8mm width, 2mm pitches)

Taping dimensions shall be in accordance with Figure-3 and Table-5.




Figure-3

Table-5

| Style  | A        | B        | t <sub>1</sub> | t <sub>2</sub> | t <sub>3</sub> |
|--------|----------|----------|----------------|----------------|----------------|
| FCCR10 | 0.65±0.1 | 1.15±0.1 | 0.6±0.05       | 0.7max.        | 0.5±0.05       |

10.2.2 Paper taping (8mm width, 4mm pitches)

Taping dimensions shall be in accordance with Figure-4 and Table-6.




Figure-4

Table-6

| Style  | A         | B       | t <sub>1</sub> | t <sub>2</sub> |
|--------|-----------|---------|----------------|----------------|
| FCCR16 | 1.15±0.15 | 1.9±0.2 | 0.6±0.1        | 0.8 max.       |

- 1). The cover tapes shall not cover the sprocket holes.
- 2). Tapes in adjacent layers shall not stick together in the packing.
- 3). Components shall not stick to the carrier tape or to the cover tape.
- 4). Pitch tolerance over any 10 pitches  $\pm 0.2\text{mm}$ .
- 5). The peel strength of the top cover tape shall be within 0.1N to 0.5N on the test method as shown in the following  
FCCR10:Figure-5,FCCR16: Figure-6.
- 6). When the tape is bent with the minimum radius for 25 mm, the tape shall not be damaged and the components shall maintain their position and orientation in the tape.
- 7). In no case shall there be two or more consecutive components missing.  
The maximum number of missing components shall be one or 0.1%, whichever is greater.
- 8). The fuses shall be faced to upward at the over coating side in the carrier cavity.




Figure-5




Figure-6

10.3 Reel dimension

Reel dimensions shall be in accordance with the following Figure-5 and Table-6.  
Plastic reel (Based on EIAJ ET-7200C)




Figure-5

Table-6

| Style     | Unit: mm                         |          | Note              |
|-----------|----------------------------------|----------|-------------------|
|           | A                                | B        |                   |
| FCCR10,16 | 9 <sup>+1.0</sup> / <sub>0</sub> | 11.4±1.0 | Injection molding |
|           |                                  | 13±1.0   | Vacuum forming    |

Note: Marking label shall be marked on a place of Marking A or two place of marking A and B.

10.4 Leader and trailer tape.

(Example)




Figure-8

11. Marking on package

The label of a minimum package shall be legibly marked with follows.

11.1 Marking A

- (1) Classification (Style, Rated current, Optional code, Packaging form)
- (2) Quantity
- (3) Lot number
- (5) Manufacturer's name or trade mark
- (6) UL and /or C-UL recognized component mark
- (7) Others

11.2 Marking B (KAMAYA Control label)


## 12. Recommended Derating for Rated Current

- Nominal Derating

Option Code AB: Nominal Derating  $\leq$  75% of Rated Current

- Temperature Derating

Please refer to the following graph regarding the current derating value for ambient temperature.





Ex.) • If Optional code: AB (Rated Current:0.5A) is used under ambient temperature 70°C

Kamaya recommends, less than the current value derated as below,

Rated Current:  $0.5A \times (\text{Nominal Derating} : 75\% \times \text{Temperature Derating} : 100\%) = 0.375A$

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

-  [View FCCR16801ABTP](#) on WIN SOURCE
-  [Kamaya Inc.](#) Information

## Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management