




**THE DATASHEET OF  
10N40S350**





**SS** Stainless Steel

**Specification**

1 5

- Lever body  
Plastic **KT**  
Nylon thermoplastic  
- Glass fiber reinforced  
- With molded-in stainless steel inlay  
- Temperature resistant up to 230 °F (110 °C)
- Color  
Black, RAL 9005, textured finish **● SW**  
Orange, RAL 2004, textured finish **● OS**  
Gray, RAL 7035, textured finish **● GS**
- Threaded stud / retaining screw  
Stainless steel AISI 303
- [Plastic Characteristics](#) → page 2135
- [Stainless Steel Characteristics](#) → page 2143
- [RoHS compliant](#)

**Information**

Made in the USA, WN 300.1 adjustable levers are the result of modern industrial design: glass fiber reinforced thermoplastic with molded-in stainless steel inlay.

All such levers have proven to be ideal wherever parts have to be clamped in a confined space or in a particular lever position. The insert is connected to the lever via serrations that can easily be disengaged.

Pulling the lever upwards disengages the serrations, allowing it to be swiveled to the ideal clamping position. When releasing the lever, the serrations automatically re-engage.

see also...

- [Adjustable Levers WN 300.1 \(Nylon Plastic, Tapped or Plain Bore Type\)](#) → page 418
- [Adjustable Levers GN 300.1 \(Zinc Die-Cast, Threaded Stud Type\)](#) → page 412
- [Adjustable Levers GN 300.5 \(Stainless Steel, Matte Shot-Blasted Finish\)](#) → page 432
- [Adjustable Levers WN 303.1 \(Nylon Plastic, with Push Button, Threaded Stud Type\)](#) → page 450
- [Adjustable Levers GN 303.1 \(Zinc Die-Cast, with Push Button, Threaded Stud Type\)](#) → page 442

**On request**

- Special colors, stud lengths, and threads

How to order (Inch)	1 Material
	2 Lever length $l_1$
	3 Thread $d_1$
	4 Thread length $l_2$
	5 Color
 <b>WN 300.1-KT-63-3/8X16-50-GS</b>	

How to order (Metric)	1 Material
	2 Lever length $l_1$
	3 Thread $d_1$
	4 Thread length $l_2$
	5 Color
 <b>WN 300.1-KT-30-M5-16-OS</b>	

**Inch table**

Dimensions in: inches - millimeters

l <sub>1</sub>	d <sub>1</sub> Thread	l <sub>2</sub>								d <sub>3</sub>	d <sub>4</sub>	h <sub>1</sub>	h <sub>2</sub>	h <sub>3</sub>	h <sub>4</sub> Stroke
		0.47	0.63	0.79	0.98	1.26	-	-	-						
1.18 30	10 x 32	0.47 12	0.63 16	0.79 20	0.98 25	1.26 32	-	-	-	0.39 10	0.57 14.5	0.96 24.5	0.16 4	1.20 30.5	0.14 3.5
1.18 30	10 x 24	0.63 16	0.79 20	0.98 25	1.26 32	-	-	-	-	0.39 10	0.57 14.5	0.96 24.5	0.16 4	1.20 30.5	0.14 3.5
1.18 30	1/4 x 20	0.47 12	0.63 16	0.79 20	0.98 25	1.26 32	1.57 40	1.77 45	-	0.39 10	0.57 14.5	0.96 24.5	0.16 4	1.20 30.5	0.14 3.5
1.77 45	10 x 32	0.47 12	0.63 16	0.79 20	0.98 25	1.26 32	-	-	-	0.39 10	0.57 14.5	0.96 24.5	0.16 4	1.38 35	0.14 3.5
1.77 45	10 x 24	0.63 16	0.79 20	0.98 25	1.26 32	-	-	-	-	0.39 10	0.57 14.5	0.96 24.5	0.16 4	1.38 35	0.14 3.5
1.77 45	1/4 x 20	0.47 12	0.63 16	0.79 20	0.98 25	1.26 32	1.57 40	1.77 45	-	0.39 10	0.57 14.5	0.96 24.5	0.16 4	1.38 35	0.14 3.5
2.48 63	5/16 x 18	0.63 16	0.79 20	0.98 25	1.26 32	1.57 40	1.77 45	1.97 50	2.48 63	0.53 13.5	0.76 19.4	1.22 31	0.26 6.5	1.77 45	0.16 4
2.48 63	3/8 x 16	0.79 20	0.98 25	1.26 32	1.57 40	1.97 50	-	-	-	0.53 13.5	0.76 19.4	1.22 31	0.26 6.5	1.77 45	0.16 4
3.07 78	3/8 x 16	0.79 20	0.98 25	1.26 32	1.57 40	1.77 45	1.97 50	2.48 63	-	0.63 16	0.87 22.2	1.42 36	0.31 8	2.17 55	0.16 4
3.07 78	1/2 x 13	0.79 20	0.98 25	1.26 32	1.57 40	1.97 50	-	-	-	0.63 16	0.87 22.2	1.42 36	0.31 8	2.17 55	0.16 4
3.62 92	1/2 x 13	0.98 25	1.26 32	1.57 40	1.77 45	1.97 50	2.48 63	-	-	0.75 19	0.99 25.2	1.69 43	0.43 11	2.56 65	0.16 4

**Metric table**

Dimensions in: millimeters - inches

l <sub>1</sub>	d <sub>1</sub> Thread	l <sub>2</sub>								d <sub>3</sub>	d <sub>4</sub>	h <sub>1</sub>	h <sub>2</sub>	h <sub>3</sub>	h <sub>4</sub> Stroke
		6	8	10	12	16	-	-	-						
30 1.18	M 3	6 0.24	8 0.31	10 0.39	12 0.47	16 0.63	-	-	-	10 0.39	14.5 0.57	24.5 0.96	4 0.16	30.5 1.20	3.5 0.14
30 1.18	M 5	12 0.47	16 0.63	20 0.79	25 0.98	32 1.26	40 1.57	50 1.97	-	10 0.39	14.5 0.57	24.5 0.96	4 0.16	30.5 1.20	3.5 0.14
30 1.18	M 6	12 0.47	16 0.63	20 0.79	25 0.98	32 1.26	40 1.57	45 1.77	50 1.97	10 0.39	14.5 0.57	24.5 0.96	4 0.16	30.5 1.20	3.5 0.14
45 1.77	M 5	12 0.47	16 0.63	20 0.79	25 0.98	32 1.26	40 1.57	50 1.97	-	10 0.39	14.5 0.57	24.5 0.96	4 0.16	35 1.38	3.5 0.14
45 1.77	M 6	12 0.47	16 0.63	20 0.79	25 0.98	32 1.26	40 1.57	45 1.77	50 1.97	10 0.39	14.5 0.57	24.5 0.96	4 0.16	35 1.38	3.5 0.14
63 2.48	M 6	16 0.63	20 0.79	25 0.98	32 1.26	40 1.57	50 1.97	63 2.48	-	13.5 0.53	19.4 0.76	31 1.22	6.5 0.26	45 1.77	4 0.16
63 2.48	M 8	16 0.63	20 0.79	25 0.98	32 1.26	40 1.57	45 1.77	50 1.97	63 2.48	13.5 0.53	19.4 0.76	31 1.22	6.5 0.26	45 1.77	4 0.16
78 3.07	M 10	20 0.79	25 0.98	32 1.26	40 1.57	45 1.77	50 1.97	63 2.48	80 3.15	16 0.63	22.2 0.87	36 1.42	8 0.31	55 2.17	4 0.16
92 3.62	M 10	20 0.79	25 0.98	32 1.26	40 1.57	50 1.97	63 2.48	80 3.15	-	19 0.75	25.2 0.99	43 1.69	11 0.43	65 2.56	4 0.16
92 3.62	M 12	20 0.79	25 0.98	32 1.26	40 1.57	45 1.77	50 1.97	63 2.48	80 3.15	19 0.75	25.2 0.99	43 1.69	11 0.43	65 2.56	4 0.16

1.1  
1.2  
1.3  
1.4  
2.1  
2.2  
2.3  
2.4



## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

- [View 10N40S350 on WIN SOURCE](#)
- [J.W. Winco Information](#)

## Optimize Your Supply Chain with WIN SOURCE Solutions

- ✓ Global Sourcing Solution
- ✓ Obsolete Management
- ✓ Cost Control Management
- ✓ Shortage Management
- ✓ Alternative Solution
- ✓ Excess Inventory Management