



**THE DATASHEET OF  
HLCD-10-24.00-TR-TR-1**



# HIGH-SPEED HERMAPHRODITIC CABLE

(0.50 mm) .0197" PITCH • HLCD SERIES



**HLCD**  
**Mates:**  
 LSHM

## SPECIFICATIONS

**Cable:**  
 38 AWG 50 Ω coax or  
 36 AWG 50 Ω high-temp coax  
**Signal Routing:**  
 50 Ω Single-Ended  
**Plating:**  
 10 μ" (0.25 μm) Gold on  
 contact, Matte Tin on tail  
**Operating Temp Range:**  
 -25 °C to +105 °C  
 -40 °C to +125 °C (-T option)  
**Current Rating:**  
 0.9 A per pin  
 (2 pins powered)

HLCD	POSITIONS PER ROW	WIRE LENGTH	END NO. 1	END 1 OPTION	END NO. 2	END 2 OPTION	WIRING OPTION	CABLE OPTION
------	-------------------	-------------	-----------	--------------	-----------	--------------	---------------	--------------

**-05, -10,  
 -20, -30,  
 -40, -50**  
 (Standard sizes)

**-"XX.XX"**  
 = Wire Length  
 in Inches  
 (43.7 mm)  
 01.72"  
 minimum

**-TR**  
 = Vertical,  
 Top Right

**-TL**  
 = Vertical,  
 Top Left

**-BR**  
 = Vertical,  
 Bottom  
 Right

**-BL**  
 = Vertical,  
 Bottom  
 Left

**-TD**  
 = Right-angle,  
 Top

**-TH**  
 = Reversed  
 Right-angle,  
 Top

**-BD**  
 = Right-angle,  
 Bottom

**-BH**  
 = Reversed  
 Right-angle,  
 Bottom

Leave blank for no screw down. Screw down not available for -TD, -TH, -BD & -BH options.

**S**  
 = Screw down in PCB

**-TR**  
 = Vertical,  
 Top Right

**-TL**  
 = Vertical,  
 Top Left

**-BR**  
 = Vertical,  
 Bottom  
 Right

**-BL**  
 = Vertical,  
 Bottom  
 Left

**-TD**  
 = Right-angle,  
 Top

**-TH**  
 = Reversed  
 Right-angle,  
 Top

**-BD**  
 = Right-angle,  
 Bottom

**-BH**  
 = Reversed  
 Right-angle,  
 Bottom

Leave blank for no screw down. Screw down not available for -TD, -TH, -BD & -BH options.

**S**  
 = Screw down in PCB

**-1**  
 = Pin 1 to  
 Pin 1

**-2**  
 = Pin 1 to  
 Pin 2

**-3**  
 = Pin 1 to  
 Pin N-1

**-4**  
 = Pin 1 to  
 Pin N

Leave blank for 38 AWG coax



**-T**  
 = 36 AWG,  
 high-temp  
 coax

END TO END	A
Vertical to Vertical	(21.84) .860
Vertical to Right-angle	(25.35) .998
Vertical to Reversed Right-angle	
Right-angle to Right-angle	(28.85) 1.136
Right-angle to Reversed Right-angle	
Reversed Right-angle to Reversed Right-angle	

POSITIONS PER ROW	B	
	XR, XL	XH, XD
-05	(9.65) .380	(10.92) .430
-10	(12.14) .478	(13.41) .528
-20	(17.15) .675	(18.42) .725
-30	(24.77) .975	(26.04) 1.025
-40	(32.39) 1.275	(33.66) 1.325
-50	(40.01) 1.575	(41.28) 1.625

END OPTION	C	D
XL, XR	(16.51) .650	(6.02) .237
XD	(20.02) .788	(6.71) .264
XH		

**EYE  
 SPEED**  
 CABLE



END NO. 1 (-TR SHOWN)

END NO. 2 (-TD SHOWN)



**Notes:**  
 Cable lengths longer than 40.00" (1 meter) are not supported with S.I. test data.

Design your full cable assembly with Samtec's High-Speed Cable Solutionator® at [www.samtec.com/cablebuilder](http://www.samtec.com/cablebuilder)

Some lengths, styles and options are non-standard, non-returnable.

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

-  [View HLCD-10-24.00-TR-TR-1 on WIN SOURCE](#)
-  [Samtec Inc. Information](#)

## Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management