



**THE DATASHEET OF
CN113-230-0001(01)VE**




SPECIFICATIONS:

Insulation Resistance: 250MΩ min. at 500V DC
 Withstanding Voltage: 500Vrms for 1min
 Voltage Rating: 50V AC
 Current Rating: 0.5A MAX
 Contact Resistance: 200mΩ max. at 20mV max.
 Operating Temp.: - 40°C ~ +85°C
 Mating Cycle: 35 times

PART NUMBER:

CN113-230-0001(01)VE




MATERIALS AND FINISH:

- Contacts: Pb
- Insulator: LCP
- GND Metal Pads: Bs
- Screw-Down Nut: Bs


AUTOMOTIVE COMPLIANT

FEATURES:


- Automotive Grade Performance
- Mechanically compliant with Qseven and MXM2,1 Module Interface design
- Screw-Down feature to secure module and connector connection



OUTLINE DIMENSIONS:



RECOMMENDED PCB LAYOUT:



Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View CN113-230-0001\(01\)VE on WIN SOURCE](#)

 [Yamaichi Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management