



**THE DATASHEET OF  
S1PBHE3/84A**



## High Current Density Surface Mount Glass-Passivated Rectifiers

eSMP™ Series



DO-220AA (SMP)

### FEATURES

- Very low profile - typical height of 1.0 mm
- Ideal for automated placement
- Glass passivated chip junction
- Low forward voltage drop
- Low thermal resistance
- Meets MSL level 1, per J-STD-020, LF maximum peak of 260 °C
- Component in accordance to RoHS 2002/95/EC and WEEE 2002/96/EC



**RoHS**  
COMPLIANT

### TYPICAL APPLICATIONS

General purpose, polarity protection, and rail-to-rail protection in both consumer and automotive applications.

### MECHANICAL DATA

**Case:** DO-220AA (SMP)

Epoxy meets UL 94V-0 flammability rating

**Terminals:** Matte tin plated leads, solderable per J-STD-002 and JESD22-B102

E3 suffix for consumer grade, meets JESD 201 class 1A whisker test, HE3 suffix for high reliability grade (AEC Q101 qualified), meets JESD 201 class 2 whisker test

**Polarity:** Color band denotes the cathode end

| PRIMARY CHARACTERISTICS |                 |
|-------------------------|-----------------|
| $I_{F(AV)}$             | 1 A             |
| $V_{RRM}$               | 100 V to 1000 V |
| $I_R$                   | 1 $\mu$ A       |
| $V_F$                   | 0.95 V          |
| $T_J$ max.              | 150 °C          |

| MAXIMUM RATINGS ( $T_A = 25$ °C unless otherwise noted)                           |                |               |      |      |      |      |      |      |
|---|----------------|---------------|------|------|------|------|------|------|
| PARAMETER   | SYMBOL         | S1PB          | S1PD | S1PG | S1PJ | S1PK | S1PM | UNIT |
| Device marking code   |                | SB            | SD   | SG   | SJ   | SK   | SM   |      |
| Maximum repetitive peak reverse voltage   | $V_{RRM}$      | 100           | 200  | 400  | 600  | 800  | 1000 | V    |
| Maximum RMS voltage   | $V_{RMS}$      | 70            | 140  | 280  | 420  | 560  | 700  | V    |
| Maximum DC blocking voltage   | $V_{DC}$       | 100           | 200  | 400  | 600  | 800  | 1000 | V    |
| Average forward current   | $I_{F(AV)}$    | 1.0           |      |      |      |      |      | A    |
| Peak forward surge current 10 ms single half sine-wave superimposed on rated load | $I_{FSM}$      | 30            |      |      |      |      |      | A    |
| Operating junction and storage temperature range                                  | $T_J, T_{STG}$ | - 55 to + 150 |      |      |      |      |      | °C   |



| ELECTRICAL CHARACTERISTICS (T <sub>A</sub> = 25 °C unless otherwise noted) |   |   |                 |             |      |      |            |      |      |      |
|--|---|---|-----------------|-------------|------|------|------------|------|------|------|
| PARAMETER  | TEST CONDITIONS   |   | SYMBOL          | S1PB        | S1PD | S1PG | S1PJ       | S1PK | S1PM | UNIT |
| Maximum instantaneous forward voltage <sup>(1)</sup>                       | I <sub>F</sub> = 1.0 A<br>I <sub>F</sub> = 1.0 A                            | T <sub>J</sub> = 25 °C<br>T <sub>J</sub> = 125 °C | V <sub>F</sub>  | 1.1<br>0.95 |      |      |            |      |      | V    |
| Maximum reverse current <sup>(1)</sup>                                     | rated V <sub>R</sub>  | T <sub>J</sub> = 25 °C<br>T <sub>J</sub> = 125 °C | I <sub>R</sub>  | 1.0<br>50   |      |      | 1.0<br>100 |      |      | μA   |
| Typical reverse recovery time  | I <sub>F</sub> = 0.5 A, I <sub>R</sub> = 1.0 A,<br>I <sub>rr</sub> = 0.25 A |   | t <sub>rr</sub> | 1.8         |      |      |            |      |      | μs   |
| Typical junction capacitance time  | 4.0 V, 1 MHz  |   | C <sub>J</sub>  | 6.0         |      |      |            |      |      | pF   |

**Note:**

(1) Pulse test: 300 μs pulse width, 1 % duty cycle

| THERMAL CHARACTERISTICS (T <sub>A</sub> = 25 °C unless otherwise noted) |  |                 |      |      |      |      |      |      |      |
|---|--|-----------------|------|------|------|------|------|------|------|
| PARAMETER   | SYMBOL   | S1PB            | S1PD | S1PG | S1PJ | S1PK | S1PM | UNIT |      |
| Typical thermal resistance <sup>(1)</sup>                               | R <sub>θJA</sub><br>R <sub>θJL</sub><br>R <sub>θJC</sub> | 105<br>15<br>20 |      |      |      |      |      |      | °C/W |

**Note:**

(1) Thermal resistance from junction to ambient and junction to lead mounted on P.C.B. with 5.0 x 5.0 mm copper pad areas. R<sub>θJC</sub> is measured at the terminal of cathode band. R<sub>θJC</sub> is measured at the top centre of the body

| ORDERING INFORMATION (Example) |                 |                        |               |                                    |
|--------------------------------|-----------------|------------------------|---------------|------------------------------------|
| PREFERRED P/N                  | UNIT WEIGHT (g) | PREFERRED PACKAGE CODE | BASE QUANTITY | DELIVERY MODE                      |
| S1PJ-E3/84A                    | 0.024           | 84A                    | 3000          | 7" diameter plastic tape and reel  |
| S1PJ-E3/85A                    | 0.024           | 85A                    | 10000         | 13" diameter plastic tape and reel |
| S1PJHE3/84A <sup>(1)</sup>     | 0.024           | 84A                    | 3000          | 7" diameter plastic tape and reel  |
| S1PJHE3/85A <sup>(1)</sup>     | 0.024           | 85A                    | 10000         | 13" diameter plastic tape and reel |

**Note:**

(1) Automotive grade AEC Q101 qualified

**RATINGS AND CHARACTERISTICS CURVES**

(T<sub>A</sub> = 25 °C unless otherwise noted)




Figure 1. Maximum Forward Current Derating Curve




Figure 2. Forward Power Loss Characteristics




Figure 3. Maximum Non-Repetitive Peak Forward Surge Current




Figure 6. Typical Junction Capacitance




Figure 4. Typical Instantaneous Forward Characteristics




Figure 7. Typical Transient Thermal Impedance





Figure 5. Typical Reverse Leakage Characteristics



**PACKAGE OUTLINE DIMENSIONS** in inches (millimeters)

**DO-220AA (SMP)**





## Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View S1PBHE3/84A on WIN SOURCE](#)

 [Vishay Information](#)

## Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management