



**THE DATASHEET OF
STR-NIS5020-GEVB**





STR-NIS5020-GEVB: Strata Enabled NIS5020 12V, 14 mΩ, 10A eFuse

The STR-NIS5020-GEVB provides an evaluation board for the NIS5020 eFuse within the Strata Development Environment. The NIS5020 offers a programmable trip current limit, a programmable slew rate, and thermal protection features. The evaluation board provides an on board short circuit load to test the short circuit protection features of the eFuse. This evaluation board must be used with Strata to control the eFuse and monitor telemetry such as input/output voltage, input/output current, and temperature.



Features and Applications

Features

- Vin Range from 9.2V to 18V
- 2 independently controlled eFuses that can be placed in parallel
- Multiple overload current options
- Programmable slew rate

Applications

- Motherboards
- Hard Drives
- Servers
- Fan Drives

Evaluation/Development Tool Information

Product	Status	Compliance	Short Description	Parts Used
STR-NIS5020-GEVB	Active	Pb-free	Strata Enabled NIS5020 12V, 14 mΩ, 10A eFuse	NIS5020MT1TXG

<https://www.onsemi.com/support/evaluation-board/str-nis5020-gevb/2-11-20>

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

- ⊖ [View STR-NIS5020-GEVB on WIN SOURCE](#)
- ⊖ [ON Semiconductor Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

- ✓ Global Sourcing Solution
- ✓ Obsolete Management
- ✓ Cost Control Management
- ✓ Shortage Management
- ✓ Alternative Solution
- ✓ Excess Inventory Management