




**THE DATASHEET OF  
SIB-110-02-F-S-LC**



**FIG. 1**

SCALE= 2.5 : 1.0

SIB-110-02-X-S or SIB-110-02-X-S-LC



**TABLE 1: THREADED INSERT OPTION**


POS	"A"	"B"
-05	.750[19.05]	N/A
-10	1.250[31.75]	N/A
-15	1.750[44.45]	N/A
-20	2.550[64.77]	1.275[32.39]
-25	3.050[77.47]	1.475[37.47]

ALL DIMENSIONS ARE SYMMETRIC ABOUT THE CENTERLINE.

**FIG. 2**

SCALE= 1.5 : 1.0


-E & -M OPTIONS FOR POSITIONS -05, -10, -15  
(SAME AS FIGURE 1 UNLESS OTHERWISE STATED)



**FIG. 3**

SCALE= 1.5 : 1.0

-E & -M OPTIONS FOR POSITIONS -20, -25  
(SAME AS FIGURE 1 UNLESS OTHERWISE STATED)




**PROPRIETARY NOTE**  
THIS DOCUMENT CONTAINS INFORMATION CONFIDENTIAL AND PROPRIETARY TO SAMTEC, INC. AND SHALL NOT BE REPRODUCED OR TRANSFERRED TO OTHER DOCUMENTS OR DISCLOSED TO OTHERS OR USED FOR ANY PURPOSE OTHER THAN THAT WHICH IT WAS OBTAINED WITHOUT THE EXPRESSED WRITTEN CONSENT OF SAMTEC, INC.

**SAMTEC**  
520 PARK EAST BLVD, NEW ALBANY, IN 47150  
\* PHONE: 812.944.6733 FAX: 812.948.5047  
e-Mail: [INFO@SAMTEC.COM](mailto:INFO@SAMTEC.COM) CODE: 55322

NOTE:  
STENCIL TO BE .0060[.152] THICK.

**FIG. 4**

SCALE= 2.5 : 1.0




ALL DIMENSIONS ARE SYMMETRIC ABOUT THE CENTERLINE.

**FIG. 5**

SCALE= 1.5 : 1.0

-E & -M OPTIONS FOR POSITIONS -20, -25  
(SAME AS FIGURE 1 UNLESS OTHERWISE STATED)



**PROPRIETARY NOTE**  
THIS DOCUMENT CONTAINS INFORMATION CONFIDENTIAL AND PROPRIETARY TO SAMTEC, INC. AND SHALL NOT BE REPRODUCED OR TRANSFERRED TO OTHER DOCUMENTS OR DISCLOSED TO OTHERS OR USED FOR ANY PURPOSE OTHER THAN THAT WHICH IT WAS OBTAINED WITHOUT THE EXPRESSED WRITTEN CONSENT OF SAMTEC, INC.

**SAMTEC**

520 PARK EAST BLVD, NEW ALBANY, IN 47150  
\* PHONE: 812.944.6733 FAX: 812.948.5047  
e-Mail: [INFO@SAMTEC.COM](mailto:INFO@SAMTEC.COM) CODE: 55322

NOTE:  
PLATING TO BE .000030 INCHES GOLD WITH HARDNESS  
OF 120-200 KNOOP PER ASTM B488 TYPE 2, GRADE C.


ALL DIMENSIONS ARE SYMMETRIC ABOUT THE CENTERLINE.

C

**FIG. 6**

SCALE= 2.5 : 1.0

LOCKING CLIP & NON-LOCKING CLIP




**TABLE 1: THREADED INSERT OPTION**

POS	"C"	"D"
-05	.750[19.05]	N/A
-10	1.250[31.75]	N/A
-15	1.750[44.45]	N/A
-20	2.550[64.77]	1.275[32.39]
-25	3.050[77.47]	1.475[37.47]

**FIG. 7**

SCALE= 1.5 : 1.0


-E & -M OPTIONS FOR POSITIONS -05, -10, -15  
(SAME AS FIGURE 1 UNLESS OTHERWISE STATED)



**FIG. 8**

SCALE= 1.5 : 1.0

-E & -M OPTIONS FOR POSITIONS -20, -25  
(SAME AS FIGURE 1 UNLESS OTHERWISE STATED)



**PROPRIETARY NOTE**  
THIS DOCUMENT CONTAINS INFORMATION  
CONFIDENTIAL AND PROPRIETARY TO  
SAMTEC, INC. AND SHALL NOT BE REPRODUCED  
OR TRANSFERRED TO OTHER DOCUMENTS OR  
DISCLOSED TO OTHERS OR USED FOR ANY  
PURPOSE OTHER THAN THAT WHICH IT WAS  
OBTAINED WITHOUT THE EXPRESSED WRITTEN  
CONSENT OF SAMTEC, INC.

**SAMTEC**  
520 PARK EAST BLVD, NEW ALBANY, IN 47150  
\* PHONE: 812.944.6733 FAX: 812.948.5047  
e-Mail: [INFO@SAMTEC.COM](mailto:INFO@SAMTEC.COM) CODE: 55322

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View SIB-110-02-F-S-LC on WIN SOURCE](#)

 [Samtec Inc. Information](#)

## Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management