



**THE DATASHEET OF  
SLW-105-01-G-D**



# LOW PROFILE SOCKET STRIPS

(2.54 mm) .100" PITCH • SLW/CES SERIES



## SLW

### Mates:

TLW, TSW, MTLW, MTSW,  
HW, EW, ZW, HTSW,  
HMTSW, TSM

## CES

### Mates:

TLW, TSW, MTLW,  
MTSW, HW, EW, ZW,  
DW, HTSW, PHT, HMTSW

SLW	-	1	NO. PINS PER ROW	-	01	PLATING OPTION	-	ROW OPTION
-----	---	---	------------------	---	----	----------------	---	------------

01 thru 50



**-F**

= Gold flash on contact,  
Matte Tin on tail

**-S**

= Single Row

**-L**

= 10  $\mu$ " (0.25  $\mu$ m) Gold on contact,  
Matte Tin on tail

**-D**

= Double Row

**-G**

= 20  $\mu$ " (0.51  $\mu$ m) Gold on contact,  
Gold flash on balance

**-T**

= Matte Tin

## SPECIFICATIONS

### Insulator Material:

Black G.F. Polyester

### Contact Material:

Phosphor Bronze

### Plating:

Au or Sn over  
50  $\mu$ " (1.27  $\mu$ m) Ni

### SLW Current Rating (SLW/TSW):

5.2 A per pin  
(2 pins powered)

### CES Current Rating (TSW/CES):

5.5 A per pin  
(2 pins powered)

### Voltage Rating:

SLW: 406 VAC  
CES: 400 VAC

### Operating Temp Range:


-55 °C to +125 °C with Gold  
-55 °C to +105 °C with Tin

### Insertion Depth:

SLW: (2.16 mm) .085" to  
(2.92 mm) .115"  
CES: (2.62 mm) .103" to  
(4.06 mm) .160"

### Lead-Free Solderable:

No, Lead Wave only



## PROCESSING

### Lead-Free Solderable:

No, Lead Wave only

CES	-	1	NO. PINS PER ROW	-	LEAD STYLE	-	PLATING OPTION	-	ROW OPTION	-	RA OPTION
-----	---	---	------------------	---	------------	---	----------------	---	------------	---	-----------

01 thru 50

Specify  
LEAD  
STYLE  
from  
chart

**-L**

= 10  $\mu$ " (0.25  $\mu$ m)  
Gold contact,  
Matte Tin on tail

**-S**

= Single Row

**-RA**

= Right-angle  
version  
(Style -02 only  
Single Row only)

**-T**

= Matte Tin


**-D**

= Double Row

## ALSO AVAILABLE

MOQ Required

Other Platings



LEAD STYLE	A
-01	(3.25) .128
-02	(5.66) .223

### Note:

Some lengths, styles and  
options are non-standard,  
non-returnable.

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View SLW-105-01-G-D on WIN SOURCE](#)

 [Samtec Inc. Information](#)

## Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management