



**(1.27 mm) .050" PITCH • DISCRETE WIRE ASSEMBLY/COMPONENTS**

| SERIES  | POSITIONS PER ROW   | WIRE GAUGE   | PLATING OPTION  | ASSEMBLED LENGTH  | END OPTION   | END 2 OPTION   |
|---|---|--|---|---|--|--|
| <b>SFSD</b><br>= Double Row PVC Cable<br><br><b>SFSDT</b><br>= Double Row Blue *Teflon™ Fluoropolymer Cable | <b>-03, -04, -05, -07, -10, -15, -20, -25, -40, -50</b><br>(Standard sizes) | <b>-28</b><br>= 28 AWG<br><br><b>-28C</b><br>= Color Coded Cable (SFSD only)<br><br><b>-30</b><br>= 30 AWG | <b>-G</b><br>= 10 μ" (0.25 μm) Gold on contact, Gold Flash on balance | <b>-"XX.XX"</b><br>= Assembled Length in Inches (76.20 mm)<br>03.00" min. for -S end option (82.60 mm)<br>03.25" min. for -D end option | <b>-S</b><br>= Single Ended<br><br><b>-D</b><br>= Double Ended For -(X) specify "S" for single ended and "D" for double ended.<br><br><b>-(X)R</b><br>= Retention Latch (TFM-WT option required for mating)<br><br><b>-(X)S</b><br>= Screw Down (Not available in -03, -04 & -50 positions) (Mates with TFM-DS option) | Requires -D, -DS, -DR (End 1 Notch Up)<br><br><b>-NUS</b><br>= Notch up, straight (Pin 1 to Pin N-1)<br><br><b>-NDS</b><br>= Notch down, straight (Pin 1 to Pin 2)<br><br><b>-NUX</b><br>= Notch up, crossed (Pin 1 to Pin N)<br><br><b>-NDX</b><br>= Notch down, crossed (Pin 1 to Pin 1) |

**SFSD(T)**  
**Board Mates:**  
TFM, TFML, TFC  
(-SR & -DR requires -WT option)

| -28C CABLE COLOR CODING |        |
|-------------------------|--------|
| PIN                     | COLOR  |
| 1                       | BROWN  |
| 2                       | RED    |
| 3                       | ORANGE |
| 4                       | YELLOW |
| 5                       | GREEN  |
| 6                       | VIOLET |
| 7                       | GRAY   |
| 8                       | WHITE  |
| 9                       | BLACK  |
| 10                      | BLUE   |
| ETC                     | REPEAT |

**SPECIFICATIONS**

**Insulator Material:** Black LCP  
**Contact Material:** BeCu  
**Plating:** Au over 50 μ" (1.27 μm) Ni  
**Current Rating:** 2.9 A per pin (2 pins powered)  
**Operating Temp Range:** -10 °C to +80 °C (PVC) / -40 °C to +125 °C (\*Teflon™ Fluoropolymer)  
**Voltage Rating:** 280 VAC (PVC) / 313 VAC (\*Teflon™ Fluoropolymer)  
**Wire:** 28 or 30 AWG

**Notes:**  
Teflon™ Fluoropolymer cable is intended for crimp only. Contact Samtec for solderable cable applications.

For wiring option information refer to drawings on web.

View complete specifications at: [samtec.com?SFSD](http://samtec.com?SFSD) & [samtec.com?SFSdT](http://samtec.com?SFSdT)

| ISDF | POSITIONS PER ROW   | ROW OPTION                | OPTION  | SERIES  | WIRE GAUGE                     | 01 | PLATING  |
|------|---|---------------------------|---|---|--------------------------------|----|--|
|      | <b>-03, -04, -05, -07, -10, -15, -20, -25, -40, -50</b><br>(Standard sizes) | <b>-D</b><br>= Double Row | <b>-M</b><br>= Metal Retention Latch<br><br><b>-S</b><br>= Screw Down | <b>CC03R</b><br>= Contact, Full Reel (35,000 Parts per Reel)<br><br><b>CC03M</b><br>= Contact, Mini Reel (1,000 - 5,000 Parts per Reel) | <b>-2830</b><br>= 28 to 30 AWG |    | <b>-GF</b><br>= Gold flash contact<br><br><b>-G</b><br>= 10 μ" (0.25 μm) Gold on contact |

**TOOLING**

Hand Tool: CAT-HT-203-2830-12

Mini Applicator: CAT-MC-203-2830-XX-01

Clamp for mounting hand tool: CAT-HT-MNT-01



Extraction Tool: CAT-EX-169-01

**Note:**  
Some lengths, styles and options are non-standard, non-returnable.

View complete specifications at: [samtec.com?ISDF](http://samtec.com?ISDF), [samtec.com?CC03R](http://samtec.com?CC03R) & [samtec.com?CC03M](http://samtec.com?CC03M)

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

-  [View SFSD-19-28-G-06.00-DL-NDX on WIN SOURCE](#)
-  [Samtec Inc. Information](#)

## Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management