




**THE DATASHEET OF
800B102JT50XT1K**



RF/Microwave Capacitors

RF/Microwave Multilayer Capacitors (MLC)

800B Series NPO Porcelain, High RF Power Ultra-Low ESR



GENERAL DESCRIPTION

KYOCERA AVX's 800B Series offers superb performance in demanding high RF power applications requiring consistent and reliable operation. The combination of highly conductive metal electrode systems, optimized case geometries, and proprietary dielectrics, yields the lowest ESR. KYOCERA AVX's new NPO low loss rugged dielectrics are designed to provide superior heat transfer in high RF power applications. Ultra-low ESR and superior thermal performance insure that the 800B Series products are your best choice for high RF power applications from VHF through microwave frequencies.

TYPICAL APPLICATIONS

- Avionics
- Public Safety Radio
- Wireless Communications
- VHF / UHF / HDTV Broadcast Transmitters
- Telecom
- WiMAX
- Microwave Communication Systems and Satellite Systems

TYPICAL CIRCUIT APPLICATIONS

- High RF Power Filter Networks
- Matching Networks
- Couplers
- Combiners
- Output Coupling
- Antenna Coupling
- DC Blocking
- Bypassing


ENVIRONMENTAL TEST

Thermal Shock	MIL-STD-202, Method 107, Condition A
Moisture Resistance	MIL-STD-202, Method 106
Low Voltage Humidity	MIL-STD-202, Method 103, Condition A, with 1.5 Volts DC applied while subjected to an environment of 85°C with 85% relative humidity for 240 hours min.
Life Test	MIL-STD-202, Method 108, for 2000 hours, at 125°C 200% WVDC applied

FEATURES

- Case B Size (.110" x .110")
- Rugged, reliable NPO dielectric
- Case optimized for highest self resonant frequency
- Capacitance Range 0.1 pF to 1000 pF
- Lowest ESR
- Capable of highest RF Power
- RoHS Compliant/Lead-Free

PACKAGING OPTIONS



ENVIRONMENTAL CHARACTERISTICS

Quality Factor	Greater than 2,000 at 1 MHz (Cap Values <=10pf .0010 Max. @ 1MHz Cap Values >10pf .0005 Max. @ 1MHz)
Temperature Coefficient of Capacitance (TCC)	0 ±30 PPM/°C (-55°C to +125°C)
Insulation Resistance (IR)	0.1 pF to 1000 pF: 10 ⁵ Megohms min. @ +25°C at rated WVDC 10 ⁴ Megohms min. @ +125°C at rated WVDC
Working Voltage (WVDC)	See Capacitance Values Table
Dielectric Withstanding Voltage (DWV)	Case B: 250% of rated WVDC for 5 secs
Retrace	Less than ±(0.02% or 0.02 pF), whichever is greater
Aging Effects	None
Piezoelectric Effects	None
Capacitance Drift	±(0.02% or 0.02 pF), whichever is greater
Operating Temperature Range	From -55°C to +125°C (No derating of working voltage)
Termination Styles	See Mechanical Configurations
Terminal Strength	Terminations for chips withstand a pull of 5 lbs. min., 15 lbs. typical, for 5 seconds in direction perpendicular to the termination surface of the capacitor. Test per MIL-STD-202, method 211.

RF/Microwave Capacitors

RF/Microwave Multilayer Capacitors (MLC)

800B Series NP0 Porcelain, High RF Power Ultra-Low ESR




CAPACITANCE VALUES

Cap. Code	Cap. (pF)	Tol.	Rated WVDC	Cap. Code	Cap. (pF)	Tol.	Rated WVDC	Cap. Code	Cap. (pF)	Tol.	Rated WVDC	Cap. Code	Cap. (pF)	Tol.	Rated WVDC
0R1	0.1	B	500	2R4	2.4	B, C, D	500	200	20	F, G, J, K, M	500	151	150	F, G, J, K, M	300
0R2	0.2			2R7	2.7			220	22			161	160		
0R3	0.3	B, C		3R0	3.0			240	24			181	180		
0R4	0.4			3R3	3.3			270	27			201	200		
0R5	0.5	B, C, D		3R6	3.6			300	30			221	220		
0R6	0.6			3R9	3.9			330	33			241	240		
0R7	0.7			4R3	4.3			360	36			271	270		
0R8	0.8			4R7	4.7			390	39			301	300		
0R9	0.9			5R1	5.1			430	43			331	330		
1R0	1.0			5R6	5.6			470	47			361	360		
1R1	1.1			B, C, D	6R2			6.2	510			51	391		390
1R2	1.2				6R8			6.8	560			56	431		430
1R3	1.3		7R5		7.5	620	62	471	470						
1R4	1.4		B, C, D		8R2	8.2	680	68	511	510					
1R5	1.5				9R1	9.1	750	75	561	560					
1R6	1.6				100	10	820	82	621	620					
1R7	1.7	110			11	910	91	681	680						
1R8	1.8	120			12	101	100	751	750						
1R9	1.9	130			13	111	110	821	820						
2R0	2.0	B, C, D	150		15	121	120	911	910						
2R1	2.1		160		16	131	130	102	1000						
2R2	2.2		180		18										

VRMS = 0.707 X WVDC

• SPECIAL VALUES, TOLERANCES AND MATCHING AVAILABLE. PLEASE CONSULT FACTORY.

HOW TO ORDER



The above part number refers to a 800 B Series (case size B) 91 pF capacitor, J tolerance (±5%), 500 WVDC, with T termination (Tin Plated over Nickel Barrier Termination, RoHS Compliant), laser marking and tape and reel packaging.

RF/Microwave Capacitors

RF/Microwave Multilayer Capacitors (MLC)

800B Series NP0 Porcelain, High RF Power Ultra-Low ESR



MECHANICAL CONFIGURATION

Series & Case Size	Term. Code	Case Size & Type	Outline ES W/T is a Termination Surface	Body Dimensions inches (mm)			Lead and Termination Dimensions and Material		Pkg Type & Qty	Pkg Code
				Length (L)	Width (W)	Thickness (T)	Overlap (Y)	Materials		
800B	T	B Solderable Nickel Barrier		.110+.020-.010 (2.79+0.51-0.25)	.110 ±.015 (2.79 ±0.38)	.070 (1.78) max.	.015 (0.38) ±.010 (0.25)	RoHS Compliant Tin Plated over Nickel Barrier Termination	T&R, 1000 or 500 pcs Vertical T&R, 1000 or 500 pcs	T1K or T TV1K or TV
800B	W	B Solder Plate		.110+.020-.010 (2.79+0.51-0.25)	.110 ±.015 (2.79 ±0.38)					

NON-MAGNETIC CONFIGURATION

Series & Case Size	Term. Code	Case Size & Type	Non-Magnetic Configuration	Body Dimensions inches (mm)			Lead and Termination Dimensions and Material		Pkg Type & Qty	Pkg Code
				Length (L)	Width (W)	Thickness (T)	Overlap (Y)	Materials		
800B	TN	B Non-Mag Solderable Barrier		.110+.020-.010 (2.79+0.51-0.25)	.110 ±.015 (2.79 ±0.38)	.070 (1.78) max.	.015 (0.38) ±.010 (0.25)	RoHS Compliant Tin Plated over Non-Magnetic Barrier Termination	T&R, 1000 or 500 pcs Vertical T&R, 1000 or 500 pcs	T1K or T TV1K or TV

SUGGESTED MOUNTING PAD DIMENSIONS

Horizontal Electrode Orientation

Vertical Electrode Orientation

Case B Vertical Mount					
Cap Value .43	Pad Size	A Min.	B Min.	C Min.	D Min.
All Values	Normal	.090 (2.29)	.050 (1.27)	.075 (1.91)	.175 (4.45)
	High Density	.070 (1.78)	.030 (.762)	.075 (1.91)	.135 (3.43)

inches (mm)




Case B Horizontal Mount					
Cap Value .43	Pad Size	A Min.	B Min.	C Min.	D Min.
All Values	Normal	.130 (3.30)	.050 (1.27)	.075 (1.91)	.175 (4.45)
	High Density	.110 (2.79)	.030 (.762)	.075 (1.91)	.135 (3.43)

inches (mm)

RF/Microwave Capacitors
RF/Microwave Multilayer Capacitors (MLC)
800B Series NP0 Porcelain, High RF Power Ultra-Low ESR



PERFORMANCE DATA



RF/Microwave Capacitors

RF/Microwave Multilayer Capacitors (MLC)

800B Series NPO Porcelain, High RF Power Ultra-Low ESR



SAMPLE KITS

Kit #	RoHS Compliant	Item Number	Description	Cap. Value Range (pF)	Cap Value (pF)	Tol.	Price
Kit 83T		DK0083T	800B NPO Ceramic High RF Power MLCs 16 different values, 15 pcs. min. per value	1.0 to 10	1.0, 1.2, 1.5, 1.8, 2.0, 2.2, 2.4, 2.7, 3.0, 3.3..... 3.9, 4.7, 5.6, 6.8, 8.2 10	±0.1 ±0.25 ±5%	\$165.00
Kit 84T		DK0084T	800B NPO Ceramic High RF Power MLCs 16 different values, 15 pcs. min. per value	10 to 100	10, 12, 15, 18, 20, 22, 24, 27, 30, 33, 39, 47, 56, 68, 82, 100	±0.1	\$165.00
Kit 85T		DK0085T	800B NPO Ceramic High RF Power MLCs 16 different values, 15 pcs. min. per value	100 to 1000	100, 120, 150, 180, 200, 220, 240, 270, 300, 330, 390, 470..... 560, 680, 820, 1000.....	±5% ±10%	\$165.00

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

- ⊖ [View 800B102JT50XT1K on WIN SOURCE](#)
- ⊖ [American Technical Ceramics Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

- ✓ Global Sourcing Solution
- ✓ Obsolete Management
- ✓ Cost Control Management
- ✓ Shortage Management
- ✓ Alternative Solution
- ✓ Excess Inventory Management