



**THE DATASHEET OF  
SD02D1212A**





### FEATURES

- Efficiency up to 81%
- 2:1 Wide Input Range
- Fully regulated Output
- Operating Temperature Range -40°C to +85°C
- Moisture sensitivity level (MSL) 2
- Isolation Voltage 1500 VDC
- Complies with EN55022, class A
- Lead free, RoHs Compliant
- Short circuit protection
- 3 Years Product Warranty



The SD02S/D series are miniature, SMD Package, isolated 2W DC/DC converters with 1,500VDC isolation. The SD02S/D series features fully regulated output and wide 2:1 input voltage ranges. The most convenient advantage is the modules with a small footprint and low package height of 8.0 mm (0.31 inch) on the PCB. These isolated DC/DC converters are the latest offering from a world leader in power systems technology and manufacturing — Delta Electronics, Inc.

### Model List

| Model Number | Input Voltage (Range)<br>VDC | Output Voltage<br>VDC | Output Current |         | Input Current       |                   | Reflected Ripple Current<br>mA(typ.) | Max. capacitive Load<br>uF | Efficiency (typ.) |
|--------------|------------------------------|-----------------------|----------------|---------|---------------------|-------------------|--------------------------------------|----------------------------|-------------------|
|              |                              |                       | Max. mA        | Min. mA | @Max. Load mA(typ.) | @No Load mA(typ.) |                                      |                            | @Max. Load %      |
| SD02S0503A   | 5<br>(4.5 ~ 9)               | 3.3                   | 500            | 125     | 471                 | 40                | 100                                  | 2200                       | 70                |
| SD02S0505A   |                              | 5                     | 400            | 100     | 548                 |                   |                                      | 1000                       | 73                |
| SD02S0512A   |                              | 12                    | 167            | 42      | 534                 |                   |                                      | 170                        | 75                |
| SD02S0515A   |                              | 15                    | 134            | 33      | 582                 |                   |                                      | 110                        | 73                |
| SD02D0505A   |                              | ±5                    | ±200           | ±50     | 667                 |                   |                                      | 470*                       | 64                |
| SD02D0512A   |                              | ±12                   | ±83            | ±21     | 615                 |                   |                                      | 100*                       | 69                |
| SD02D0515A   |                              | ±15                   | ±67            | ±17     | 598                 |                   |                                      | 47*                        | 71                |
| SD02S1203A   |                              | 12<br>(9 ~ 18)        | 3.3            | 500     | 125                 |                   |                                      | 184                        | 20                |
| SD02S1205A   | 5                            |                       | 400            | 100     | 217                 | 1000              | 77                                   |                            |                   |
| SD02S1212A   | 12                           |                       | 167            | 42      | 209                 | 170               | 80                                   |                            |                   |
| SD02S1215A   | 15                           |                       | 134            | 33      | 220                 | 110               | 80                                   |                            |                   |
| SD02D1205A   | ±5                           |                       | ±200           | ±50     | 242                 | 470*              | 73                                   |                            |                   |
| SD02D1212A   | ±12                          |                       | ±83            | ±21     | 224                 | 100*              | 78                                   |                            |                   |
| SD02D1215A   | ±15                          |                       | ±67            | ±17     | 226                 | 47*               | 78                                   |                            |                   |
| SD02S2403A   | 24<br>(18 ~ 36)              |                       | 3.3            | 500     | 125                 | 96                | 10                                   | 15                         |                   |
| SD02S2405A   |                              | 5                     | 400            | 100     | 109                 | 1000              |                                      |                            | 77                |
| SD02S2412A   |                              | 12                    | 167            | 42      | 109                 | 170               |                                      |                            | 80                |
| SD02S2415A   |                              | 15                    | 134            | 33      | 108                 | 110               |                                      |                            | 81                |
| SD02D2405A   |                              | ±5                    | ±200           | ±50     | 119                 | 470*              |                                      |                            | 74                |
| SD02D2412A   |                              | ±12                   | ±83            | ±21     | 112                 | 100*              |                                      |                            | 78                |
| SD02D2415A   |                              | ±15                   | ±67            | ±17     | 110                 | 47*               |                                      |                            | 80                |
| SD02S4803A   |                              | 48<br>(36 ~ 75)       | 3.3            | 500     | 125                 | 49                |                                      |                            | 8                 |
| SD02S4805A   | 5                            |                       | 400            | 100     | 57                  | 1000              | 73                                   |                            |                   |
| SD02S4812A   | 12                           |                       | 167            | 42      | 53                  | 170               | 79                                   |                            |                   |
| SD02S4815A   | 15                           |                       | 134            | 33      | 55                  | 110               | 79                                   |                            |                   |
| SD02D4805A   | ±5                           |                       | ±200           | ±50     | 62                  | 470*              | 71                                   |                            |                   |
| SD02D4812A   | ±12                          |                       | ±83            | ±21     | 57                  | 100*              | 77                                   |                            |                   |
| SD02D4815A   | ±15                          |                       | ±67            | ±17     | 57                  | 47*               | 77                                   |                            |                   |

\* For each output



## Input Characteristics

| Parameter                         | Model            | Min.   | Typ. | Max. | Unit |
|-----------------------------------|------------------|--|------|------|------|
| Input Surge Voltage (1 sec. max.) | 5V Input Models  | -0.7   | ---  | 11   | VDC  |
|                                   | 12V Input Models | -0.7   | ---  | 25   |      |
|                                   | 24V Input Models | -0.7   | ---  | 50   |      |
|                                   | 48V Input Models | -0.7   | ---  | 100  |      |
| Start-Up Voltage                  | 5V Input Models  | 3.5  | 4    | 4.5  |      |
|                                   | 12V Input Models | 4.5  | 7    | 9    |      |
|                                   | 24V Input Models | 8  | 12   | 18   |      |
|                                   | 48V Input Models | 16   | 24   | 36   |      |
| Under Voltage Shutdown            | 5V Input Models  | ---  | 3.5  | 4    |      |
|                                   | 12V Input Models | ---  | 6.5  | 8.5  |      |
|                                   | 24V Input Models | ---  | 11   | 17   |      |
|                                   | 48V Input Models | ---  | 22   | 34   |      |
| Reverse Polarity Input Current    | All Models       | ---  | ---  | 1    | A    |
| Short Circuit Input Power         |                  | ---  | ---  | 1500 | mW   |
| Internal Power Dissipation        |                  | ---  | ---  | 1800 | mW   |
| Conducted EMI                     |                  | Compliance to EN 55022,class A and FCC part 15,class A |      |      |      |

## Output Characteristics

| Parameter                    | Conditions                  | Min. | Typ.  | Max.  | Unit              |
|------------------------------|-----------------------------|------|-------|-------|-------------------|
| Output Voltage Accuracy      |                             | ---  | ±1.0  | ±2.0  | %                 |
| Output Voltage Balance       | Dual Output, Balanced Loads | ---  | ±1.0  | ±2.0  | %                 |
| Line Regulation              | Vin=Min. to Max.            | ---  | ±0.3  | ±0.5  | %                 |
| Load Regulation              | Io=25% to 100%              | ---  | ±0.5  | ±0.75 | %                 |
| Ripple & Noise (20MHz)       |                             | ---  | 30    | 50    | mV <sub>P-P</sub> |
| Ripple & Noise (20MHz)       | Over Line, Load & Temp.     | ---  | ---   | 75    | mV <sub>P-P</sub> |
| Ripple & Noise (20MHz)       |                             | ---  | ---   | 15    | mV <sub>rms</sub> |
| Transient Recovery Time      | 25% Load Step Change        | ---  | 100   | 300   | µS                |
| Transient Response Deviation |                             | ---  | ±3    | ±5    | %                 |
| Temperature Coefficient      |                             | ---  | ±0.01 | ±0.02 | %/°C              |
| Short Circuit Protection     | Continuous                  |      |       |       |                   |

## General Characteristics

| Parameter                        | Conditions                        | Min.      | Typ. | Max. | Unit  |
|----------------------------------|-----------------------------------|-----------|------|------|-------|
| I/O Isolation Voltage (rated)    | 60 Seconds                        | 1500      | ---  | ---  | VDC   |
| I/O Isolation Resistance         | 500 VDC                           | 1000      | ---  | ---  | MΩ    |
| I/O Isolation Capacitance        | 100KHz, 1V                        | ---       | 250  | 420  | pF    |
| Switching Frequency              |                                   | ---       | 300  | ---  | KHz   |
| MTBF (calculated)                | MIL-HDBK-217F@25°C, Ground Benign | 1,000,000 | ---  | ---  | Hours |
| Moisture Sensitivity Level (MSL) | IPC/JEDEC J-STD-020D              | Level 2   |      |      |       |

## Recommended Input Fuse

| 5V Input Models       | 12V Input Models     | 24V Input Models     | 48V Input Models     |
|-----------------------|----------------------|----------------------|----------------------|
| 1000mA Slow-Blow Type | 500mA Slow-Blow Type | 250mA Slow-Blow Type | 120mA Slow-Blow Type |

## Environmental Specifications

| Parameter                                     | Conditions          | Min. | Max. | Unit     |
|---|---------------------|------|------|----------|
| Operating Temperature Range (with Derating)   | Ambient             | -40  | +85  | °C       |
| Case Temperature                              |                     | ---  | +90  | °C       |
| Storage Temperature Range                     |                     | -50  | +125 | °C       |
| Humidity (non condensing)                     |                     | ---  | 95   | % rel. H |
| Cooling                                       | Free-Air convection |      |      |          |
| Lead Temperature (1.5mm from case for 10Sec.) |                     | ---  | 260  | °C       |

## Power Derating Curve



## Notes


- 1 Specifications typical at  $T_a=+25^{\circ}\text{C}$ , resistive load, nominal input voltage and rated output current unless otherwise noted.
- 2 Transient recovery time is measured to within 1% error band for a step change in output load of 75% to 100%
- 3 Ripple & Noise measurement bandwidth is 0-20MHz.
- 4 These power converters require a minimum output loading to maintain specified regulation, operation under no-load conditions will not damage these modules; however they may not meet all specifications listed.
- 5 All DC/DC converters should be externally fused at the front end for protection.
- 6 Specifications subject to change without notice.
- 7 It is not recommended to use water-washing process on SMT units.

## Mechanical Drawing

### Mechanical Dimensions



### Connecting Pin Patterns



- ▶ All dimensions in mm (inches)
- ▶ Tolerance:  $X.X \pm 0.25$  ( $X.XX \pm 0.01$ )  
 $X.XXX \pm 0.13$  ( $X.XXX \pm 0.005$ )
- ▶ Pins  $\pm 0.05$  ( $\pm 0.002$ )

### Pin Connections

| Pin | Single Output | Dual Output |
|-----|---------------|-------------|
| 1   | -Vin          | -Vin        |
| 7   | NC            | NC          |
| 8   | NC            | Common      |
| 9   | +Vout         | +Vout       |
| 10  | -Vout         | -Vout       |
| 16  | +Vin          | +Vin        |

NC : No Connection

### Physical Outline

|               |  |
|---------------|--|
| Case Size     | : 24.0x13.7x8.0mm (0.94x0.54x0.31 Inches)                          |
| Case Material | : Non-Conductive Black Plastic<br>(flammability to UL 94V-0 rated) |
| Weight        | : 5.1g   |



| Part Numbering System |               |       |                   |               |                |                    |
|-----------------------|---------------|-------|-------------------|---------------|----------------|--------------------|
| S                     | D             | 02    | S                 | 05            | 05             | A                  |
| Form factor           | Family series | Watt  | Number of Outputs | Input Voltage | Output Voltage | Option Code        |
| D-DIP                 | A~Z           | 01:1W | S - Single        | 03:3.3V       | 03:3.3V        | A - Std. Functions |
| P-SIP                 |               | 02:2W | D- Dual           | 05: 5V        | 05: 5V         |                    |
| S-SMD                 |               | 03:3W |                   | 12:12V        | 12:12V         |                    |
|                       |               | 04:4W |                   | 24: 24V       | 15: 15V        |                    |
|                       |               | 06:6W |                   | 48:48V        | 24: 24V        |                    |

### WARRANTY

Delta offers a three(3) years limited warranty. Complete warranty information is listed on our web site or is available upon request from Delta.

Information furnished by Delta is believed to be accurate and reliable. However, no responsibility is assumed by Delta for its use, nor for any infringements of patents or other rights of third parties, which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Delta. Delta reserves the right to revise these specifications at any time, without notice.

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View SD02D1212A on WIN SOURCE](#)

 [Delta Electronics](#) Information

## Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management