



**THE DATASHEET OF  
SPHCW1HDNB25YHRT1G**



## High Voltage LED Series Chip on Board

# LCo19B Gen.2



High efficacy COB LED package,  
well-suited for use in spotlight applications

### Features & Benefits

- Chip on Board (COB) solution makes it easy to design in
- Simple assembly reduces manufacturing cost
- Low thermal resistance
- InGaN/GaN MQW LED with long time reliability
- Completed 6,000 hours of LM-80 Testing
- ENEC certified: Integral LED Module

### Applications

- Spotlight / Downlight
- LED Retrofit Bulbs
- Outdoor Illumination



## Table of Contents

|    |                                     |       |    |
|----|-------------------------------------|-------|----|
| 1. | Characteristics                     | ----- | 3  |
| 2. | Product Code Information            | ----- | 6  |
| 3. | Typical Characteristics Graphs      | ----- | 12 |
| 4. | Outline Drawing & Dimension         | ----- | 15 |
| 5. | Reliability Test Items & Conditions | ----- | 16 |
| 6. | Label Structure                     | ----- | 17 |
| 7. | Packing Structure                   | ----- | 19 |
| 8. | Precautions in Handling & Use       | ----- | 22 |

## 1. Characteristics

### a) Absolute Maximum Rating

| Item                            | Symbol    | Rating     | Unit | Condition |
|---------------------------------|-----------|------------|------|-----------|
| Ambient / Operating Temperature | $T_a$     | -40 ~ +105 | °C   | -         |
| Storage Temperature             | $T_{stg}$ | -40 ~ +120 | °C   | -         |
| LED Junction Temperature        | $T_j$     | 150        | °C   | -         |
| Case Temperature                | $T_c$     | 105        | °C   | *Note     |
| Forward Current                 | $I_F$     | 980        | mA   | -         |
| Power Dissipation               | $P_D$     | 36.3       | W    | -         |
| ESD (HBM)                       | -         | ±2         | kV   | -         |
| ESD (MM)                        | -         | ±0.5       | kV   | -         |

### b) Electro-optical Characteristics ( $I_F = 540 \text{ mA}$ , $T_c = 25 \text{ °C}$ )

| Item  | Unit | Rank   | Min. | Typ. | Max. |
|---|------|--------|------|------|------|
| Forward Voltage ( $V_F$ )                   | V    | YH     | 32.5 | 35.5 | 38.5 |
|   |      | 3      | 70   | -    | -    |
|   |      | 5      | 80   | -    | -    |
| Color Rendering Index ( $R_a$ )             | -    | 7      | 90   | -    | -    |
|   |      | 8      | 95   | -    | -    |
| Thermal Resistance (junction to chip point) | °C/W |        | -    | 1.5  | -    |
| Beam Angle                                  | °    |        | -    | 115  | -    |
| Nominal Power                               | W    |        |      | 19.2 |      |
| Eye Protection                              |      | Risk 1 | -    |      | -    |

#### Notes:

- 1) The COB is tested in pulsed condition at rated test current (10 ms pulse width) and rated temperature ( $T_j = T_c = T_a = 25 \text{ °C}$ )
- 2) Samsung maintains measurement tolerance of: forward voltage =  $\pm 5 \%$ , CRI =  $\pm 1$
- 3) Max  $T_c=105$  Current is ~~Current is~~ for ENEC condition. Refer to the derating curve, '3. Typical Characteristics Graph' designed within the range.

c) Luminous Flux Characteristics ( $I_F = 540 \text{ mA}$ )

| CRI (R <sub>a</sub> )<br>Min. | Nominal<br>CCT (K) | Flux<br>Rank | Flux<br>Bin | Sorting <sup>1)</sup> @ T <sub>c</sub> = 25 °C (lm) |      | Calculated Flux <sup>2)</sup> @ T <sub>c</sub> = 85 °C (lm) |      |
|-------------------------------|--------------------|--------------|-------------|---|------|---|------|
|                               |                    |              |             | Min.  | Max. | Min.  | Max. |
| 70                            | 3000               | 2F           | 21          | 2388  | 2714 | 2149  | 2443 |
|                               |                    |              | 22          | 2714  | 3040 | 2443  | 2736 |
|                               | 4000               | 2F           | 21          | 2508  | 2850 | 2257  | 2565 |
|                               |                    |              | 22          | 2850  | 3192 | 2565  | 2872 |
|                               | 5000               | 2F           | 21          | 2532  | 2877 | 2278  | 2589 |
|                               |                    |              | 22          | 2877  | 3222 | 2589  | 2900 |
| 80                            | 2700               | 1G           | 24          | 2487  | 2650 | 2263  | 2411 |
|                               |                    |              | 25          | 2650  | 2813 | 2411  | 2560 |
|                               |                    | 1H           | 25          | 2650  | 2813 | 2411  | 2560 |
|                               | 3000               | 1G           | 24          | 2646  | 2819 | 2408  | 2565 |
|                               |                    |              | 25          | 2819  | 2992 | 2565  | 2723 |
|                               |                    | 1H           | 25          | 2819  | 2992 | 2565  | 2723 |
|                               | 3500               | 1G           | 23          | 2547  | 2725 | 2318  | 2480 |
|                               |                    |              | 24          | 2725  | 2904 | 2480  | 2642 |
|                               |                    | 1H           | 24          | 2725  | 2904 | 2480  | 2642 |
|                               |                    |              | 25          | 2904  | 3082 | 2642  | 2805 |
|                               |                    |              | 24          | 2621  | 2805 | 2385  | 2552 |
|                               | 4000               | 1G           | 23          | 2621  | 2805 | 2385  | 2552 |
|                               |                    |              | 24          | 2805  | 2988 | 2552  | 2719 |
|                               |                    | 1H           | 24          | 2805  | 2988 | 2552  | 2719 |
|                               |                    |              | 25          | 2988  | 3172 | 2719  | 2886 |
|                               |                    |              | 23          | 2646  | 2831 | 2408  | 2576 |
|                               |                    |              | 24          | 2831  | 3016 | 2576  | 2745 |
|                               | 5000               | 1H           | 24          | 2831  | 3016 | 2576  | 2745 |
|                               |                    |              | 25          | 3016  | 3202 | 2745  | 2914 |
|                               |                    | 1G           | 23          | 2646  | 2831 | 2408  | 2576 |
|                               | 5700               | 1G           | 24          | 2831  | 3016 | 2576  | 2745 |
|                               |                    |              | 24          | 2831  | 3016 | 2576  | 2745 |
|                               |                    | 1H           | 24          | 2831  | 3016 | 2576  | 2745 |
|                               |                    |              |             | 25  | 3016 | 3202  | 2745 |

### c) Luminous Flux Characteristics (I<sub>F</sub> = 540 mA)

| CRI (R <sub>a</sub> )<br>Min. | Nominal<br>CCT (K) | Flux<br>Rank | Flux<br>Bin | Sorting <sup>1)</sup> @ T <sub>c</sub> = 25 °C (lm) |      | Calculated Flux <sup>2)</sup> @ T <sub>c</sub> = 85 °C (lm) |      |      |
|-------------------------------|--------------------|--------------|-------------|---|------|---|------|------|
|                               |                    |              |             | Min.  | Max. | Min.  | Max. |      |
| 90                            | 2700               | 2K           | 23          | 2084  | 2251 | 1897  | 2048 |      |
|                               |                    |              | 24          | 2251  | 2481 | 2048  | 2258 |      |
|                               | 3000               | 2K           | 23          | 2127  | 2297 | 1935  | 2090 |      |
|                               |                    |              | 24          | 2297  | 2527 | 2090  | 2299 |      |
|                               | 3500               | 2K           | 23          | 2191  | 2366 | 1993  | 2153 |      |
|                               |                    |              | 24          | 2366  | 2596 | 2153  | 2362 |      |
|                               | 4000               | 2K           | 23          | 2254  | 2435 | 2051  | 2216 |      |
|                               |                    |              | 24          | 2435  | 2665 | 2216  | 2425 |      |
|                               | 95                 | 2700         | 1F          | 11  | 1714 | 1905  | 1560 | 1733 |
|                               |                    |              |             | 12  | 1905 | 2095  | 1733 | 1907 |
| 3000                          |                    | 1F           | 11          | 1767  | 1964 | 1608  | 1787 |      |
|                               |                    |              | 12          | 1964  | 2160 | 1787  | 1966 |      |
| 3500                          |                    | 1F           | 11          | 1820  | 2023 | 1657  | 1841 |      |
|                               |                    |              | 12          | 2023  | 2225 | 1841  | 2025 |      |

#### Notes:

- 1) The COB is tested in pulsed condition at rated test current (10 ms pulse width) and rated temperature (T<sub>j</sub> = T<sub>c</sub> = T<sub>a</sub> = 25 °C)
- 2) Calculated flux values are for reference only
- 3) Samsung maintains measurement tolerance of: luminous flux = ±7 %, CRI = ±1

## 2. Product Code Information

|   |   |   |   |   |   |   |   |   |    |    |    |    |    |    |    |    |    |
|---|---|---|---|---|---|---|---|---|----|----|----|----|----|----|----|----|----|
| 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 | 16 | 17 | 18 |
| S | P | H | C | W | 1 | H | D | N | B  | 2  | 5  | Y  | H  | R  | T  | 2  | J  |

| Digit | PKG Information            | Code   | Specification  |   |
|-------|----------------------------|--|--|---|
| 1 2 3 | Samsung Package High Power | <b>SPH</b>   |  |   |
| 4 5   | Color                      | <b>WW</b><br><b>CW</b>   | Warm White (T/U/V/W Ranks)<br>Cool White (Q/R Ranks)   |   |
| 6     | Product Version            | <b>1</b>   |  |   |
| 7 8   | Form Factor                | <b>HD</b>  | COB  |   |
| 9     | Lens Type                  | <b>N</b>   | No lens  |   |
| 10    | Internal Code              | <b>B</b>   | LC019  |   |
| 11    | Chip Type                  | <b>2</b>   |  |   |
| 12    | CRI & Sorting Temperature  | <b>3</b><br><b>5</b><br><b>7</b><br><b>8</b>                         | Min. 70<br>Min. 80<br>Min. 90<br>Min 95  | 25 °C   |
| 13 14 | Forward Voltage (V)        | <b>YH</b>  | 32.5~38.5  |   |
| 15    | CCT (K)                    | <b>W</b><br><b>V</b><br><b>U</b><br><b>T</b><br><b>R</b><br><b>Q</b> | 2700 K<br>3000 K<br>3500 K<br>4000 K<br>5000 K<br>5700 K   | WA, WB (MacAdam Ellipse)<br>VA, VB (MacAdam Ellipse)<br>UA, UB (MacAdam Ellipse)<br>TA, TB (MacAdam Ellipse)<br>RA (MacAdam Ellipse)<br>Bin Code:<br>TW, TX, TY, TZ (ANSI bin)<br>RW, RX, RY, RZ (ANSI bin)<br>QW, QX, QY, QZ (ANSI bin)<br>VW, VX, VY, VZ (ANSI bin) |
| 16    | MacAdam / ANSI             | <b>2</b><br><b>3</b><br><b>T</b>                                     | MacAdam 2-step<br>MacAdam 3-step<br>ANSI bin   |   |
| 17 18 | Luminous Flux              | <b>1F</b><br><b>1G</b><br><b>1H</b><br><b>2F</b><br><b>2K</b>        | 11, 12 (95 CRI)<br>23, 24, 25 (80 CRI)<br>Bin Code:<br>24, 25 (80 CRI)<br>21, 22 (70 CRI)<br>23, 24 (90 CRI) |   |


a) Binning Structure ( $I_F = 540 \text{ mA}$ ,  $T_c = 25 \text{ }^\circ\text{C}$ )

| CRI ( $R_a$ )<br>Min. | Nominal<br>CCT (K) | Product Code       | $V_F$<br>Rank | Color<br>Rank     | Chrom.<br>Bin    | Flux<br>Rank       | Flux<br>Bin | Flux Range<br>( $\Phi_v$ , lm) |
|-----------------------|--------------------|--------------------|---------------|-------------------|------------------|--------------------|-------------|--------------------------------|
| 70                    | 3000               | SPHWW1HDNB23YHVT2F | YH            | VT                | VW, VX<br>VY, VZ | 2F                 | 21          | 2388 ~ 2714                    |
|                       |                    |                    |               |                   |                  |                    | 22          | 2714 ~ 3040                    |
|                       |                    | SPHWW1HDNB23YHTT2F | YH            | TT                | TW, TX<br>TY, TZ | 2F                 | 21          | 2508 ~ 2850                    |
|                       | 4000               | SPHWW1HDNB23YHRT2F | YH            | RT                | RW, RX<br>RY, RZ | 2F                 | 21          | 2532 ~ 2877                    |
|                       |                    |                    |               |                   |                  |                    | 22          | 2877 ~ 3222                    |
|                       |                    | SPHWW1HDNB25YHW21G | YH            | W2                | WB               | 1G                 | 24          | 2487 ~ 2650                    |
|                       | 2700               | SPHWW1HDNB25YHW31G | YH            | W3                | WA, WB           | 1G                 | 24          | 2487 ~ 2650                    |
|                       |                    |                    |               |                   |                  |                    | 25          | 2650 ~ 2813                    |
|                       |                    | SPHWW1HDNB25YHW21H | YH            | W2                | WB               | 1H                 | 25          | 2650 ~ 2813                    |
| 3000                  | SPHWW1HDNB25YHW31H | YH                 | W3            | WA, WB            | 1H               | 25                 | 2650 ~ 2813 |                                |
|                       |                    |                    |               |                   |                  | SPHWW1HDNB25YHV21G | YH          | V2                             |
|                       | SPHWW1HDNB25YHV31G | YH                 | V3            | VA, VB            | 1G               | 24                 | 2646 ~ 2819 |                                |
| 3500                  | SPHWW1HDNB25YHV21H | YH                 | W2            | WB                | 1H               | 25                 | 2819 ~ 2992 |                                |
|                       |                    |                    |               |                   |                  | SPHWW1HDNB25YHV31H | YH          | W3                             |
|                       | SPHWW1HDNB25YHU21G | YH                 | U2            | UB                | 1G               | 23                 | 2547 ~ 2725 |                                |
| 80                    | SPHWW1HDNB25YHU31G | YH                 | U3            | UA, UB            | 1G               | 24                 | 2725 ~ 2904 |                                |
|                       |                    |                    |               |                   |                  | 25                 | 2904 ~ 3082 |                                |
|                       | SPHWW1HDNB25YHU21H | YH                 | U2            | UB                | 1H               | 24                 | 2725 ~ 2904 |                                |
| 4000                  | SPHWW1HDNB25YHU31H | YH                 | U3            | UA, UB            | 1H               | 24                 | 2725 ~ 2904 |                                |
|                       |                    |                    |               |                   |                  | 25                 | 2904 ~ 3082 |                                |
|                       | SPHWW1HDNB25YHT21G | YH                 | T2            | TB                | 1G               | 23                 | 2621 ~ 2805 |                                |
| 5000                  | SPHWW1HDNB25YHT31G | YH                 | T3            | TA, TB            | 1G               | 24                 | 2805 ~ 2988 |                                |
|                       |                    |                    |               |                   |                  | 25                 | 2988 ~ 3172 |                                |
|                       | SPHWW1HDNB25YHT21H | YH                 | T2            | TB                | 1H               | 24                 | 2805 ~ 2988 |                                |
| 5700                  | SPHWW1HDNB25YHT31H | YH                 | T3            | TA, TB            | 1H               | 24                 | 2805 ~ 2988 |                                |
|                       |                    |                    |               |                   |                  | 25                 | 2988 ~ 3172 |                                |
|                       | SPHCW1HDNB25YHR31G | YH                 | R3            | RA                | 1G               | 23                 | 2646 ~ 2831 |                                |
| 5000                  | SPHCW1HDNB25YHR1G  | YH                 | RT            | RW, RX,<br>RY, RZ | 1G               | 24                 | 2831 ~ 3016 |                                |
|                       |                    |                    |               |                   |                  | 25                 | 3016 ~ 3202 |                                |
|                       | SPHCW1HDNB25YHR31H | YH                 | R3            | RA                | 1H               | 24                 | 2831 ~ 3016 |                                |
| 5700                  | SPHCW1HDNB25YHRT1H | YH                 | RT            | RW, RX,<br>RY, RZ | 1H               | 24                 | 2831 ~ 3016 |                                |
|                       |                    |                    |               |                   |                  | 25                 | 3016 ~ 3202 |                                |
|                       | SPHCW1HDNB25YHQT1G | YH                 | QT            | QW, QX<br>QY, QZ  | 1G               | 23                 | 2646 ~ 2831 |                                |
| 5700                  | SPHCW1HDNB25YHQT1H | YH                 | QT            | QW, QX<br>QY, QZ  | 1H               | 24                 | 2831 ~ 3016 |                                |
|                       |                    |                    |               |                   |                  | 25                 | 3016 ~ 3202 |                                |

a) Binning Structure ( $I_F = 540 \text{ mA}$ ,  $T_c = 25 \text{ }^\circ\text{C}$ )

| CRI (R <sub>a</sub> )<br>Min. | Nominal<br>CCT (K) | Product Code       | V <sub>F</sub><br>Rank | Color<br>Rank | Chrom.<br>Bin | Flux<br>Rank | Flux<br>Bin | Flux Range<br>(Φ <sub>v</sub> , lm) |
|-------------------------------|--------------------|--------------------|------------------------|---------------|---------------|--------------|-------------|-------------------------------------|
| 90                            | 2700               | SPHWW1HDNB27YHW22K | YH                     | W2            | WB            | 2K           | 23          | 2084 ~ 2251                         |
|                               |                    |                    |                        |               |               |              | 24          | 2251 ~ 2481                         |
|                               |                    | SPHWW1HDNB27YHW32K | YH                     | W3            | WA, WB        | 2K           | 23          | 2084 ~ 2251                         |
|                               |                    |                    |                        |               |               |              | 24          | 2251 ~ 2481                         |
|                               | 3000               | SPHWW1HDNB27YHV22K | YH                     | V2            | VB            | 2K           | 23          | 2127 ~ 2297                         |
|                               |                    |                    |                        |               |               |              | 24          | 2297 ~ 2527                         |
|                               |                    | SPHWW1HDNB27YHV32K | YH                     | V3            | VA, VB        | 2K           | 23          | 2127 ~ 2297                         |
|                               |                    |                    |                        |               |               |              | 24          | 2297 ~ 2527                         |
|                               | 3500               | SPHWW1HDNB27YHU22K | YH                     | U2            | UB            | 2K           | 23          | 2191 ~ 2366                         |
|                               |                    |                    |                        |               |               |              | 24          | 2366 ~ 2596                         |
|                               |                    | SPHWW1HDNB27YHU32K | YH                     | U3            | UA, UB        | 2K           | 23          | 2191 ~ 2366                         |
|                               |                    |                    |                        |               |               |              | 24          | 2366 ~ 2596                         |
|                               | 4000               | SPHWW1HDNB27YHT22K | YH                     | T2            | TB            | 2K           | 23          | 2254 ~ 2435                         |
|                               |                    |                    |                        |               |               |              | 24          | 2435 ~ 2665                         |
|                               |                    | SPHWW1HDNB27YHT32K | YH                     | T3            | TA, TB        | 2K           | 23          | 2254 ~ 2435                         |
|                               |                    |                    |                        |               |               |              | 24          | 2435 ~ 2665                         |
| 95                            | 2700               | SPHWW1HDNB28YHW21F | YH                     | W2            | WB            | 1F           | 11          | 1714 ~ 1905                         |
|                               |                    |                    |                        |               |               |              | 12          | 1905 ~ 2095                         |
|                               |                    | SPHWW1HDNB28YHW31F | YH                     | W3            | WA, WB        | 1F           | 11          | 1714 ~ 1905                         |
|                               |                    |                    |                        |               |               |              | 12          | 1905 ~ 2095                         |
|                               | 3000               | SPHWW1HDNB28YHV21F | YH                     | V2            | VB            | 1F           | 11          | 1767 ~ 1964                         |
|                               |                    |                    |                        |               |               |              | 12          | 1964 ~ 2160                         |
|                               |                    | SPHWW1HDNB28YHV31F | YH                     | V3            | VA, VB        | 1F           | 11          | 1767 ~ 1964                         |
|                               |                    |                    |                        |               |               |              | 12          | 1964 ~ 2160                         |
|                               | 3500               | SPHWW1HDNB28YHU21F | YH                     | U2            | UB            | 1F           | 11          | 1820 ~ 2023                         |
|                               |                    |                    |                        |               |               |              | 12          | 2023 ~ 2225                         |
|                               | SPHWW1HDNB28YHU31F | YH                 | U3                     | UA, UB        | 1F            | 11           | 1820 ~ 2023 |                                     |
|                               |                    |                    |                        |               |               | 12           | 2023 ~ 2225 |                                     |

b) Chromaticity Region & Coordinates ( $I_F = 540 \text{ mA}$ ,  $T_a = 25 \text{ }^\circ\text{C}$ )



| Region                 | CIE x  | CIE y  | Region | CIE x  | CIE y  |
|------------------------|--------|--------|--------|--------|--------|
| <b>V rank (3000 K)</b> |        |        |        |        |        |
| VW                     | 0.4223 | 0.399  | VY     | 0.4345 | 0.4033 |
|                        | 0.4345 | 0.4033 |        | 0.4468 | 0.4077 |
|                        | 0.4431 | 0.4213 |        | 0.4562 | 0.4260 |
| VX                     | 0.4299 | 0.4165 | VZ     | 0.4431 | 0.4213 |
|                        | 0.4223 | 0.399  |        | 0.4260 | 0.3854 |
|                        | 0.4147 | 0.3814 |        | 0.4373 | 0.3893 |
|                        | 0.4260 | 0.3854 |        | 0.4468 | 0.4077 |
|                        | 0.4345 | 0.4033 |        | 0.4345 | 0.4033 |
| <b>R rank (5000 K)</b> |        |        |        |        |        |
| RW                     | 0.3376 | 0.3616 | RY     | 0.3463 | 0.3687 |
|                        | 0.3463 | 0.3687 |        | 0.3551 | 0.3760 |
|                        | 0.3451 | 0.3554 |        | 0.3533 | 0.3620 |
|                        | 0.3371 | 0.3490 |        | 0.3451 | 0.3554 |
| RX                     | 0.3371 | 0.3490 | RZ     | 0.3451 | 0.3554 |
|                        | 0.3451 | 0.3554 |        | 0.3533 | 0.3620 |
|                        | 0.3440 | 0.3428 |        | 0.3515 | 0.3487 |
|                        | 0.3366 | 0.3369 |        | 0.3440 | 0.3428 |

| Region                 | CIE x  | CIE y  | Region | CIE x  | CIE y  |
|------------------------|--------|--------|--------|--------|--------|
| <b>T rank (4000 K)</b> |        |        |        |        |        |
| TW                     | 0.3736 | 0.3874 | TY     | 0.3871 | 0.3959 |
|                        | 0.3871 | 0.3959 |        | 0.4006 | 0.4044 |
|                        | 0.3828 | 0.3803 |        | 0.3952 | 0.388  |
|                        | 0.3703 | 0.3726 |        | 0.3828 | 0.3803 |
| TX                     | 0.3703 | 0.3726 | TZ     | 0.3828 | 0.3803 |
|                        | 0.3828 | 0.3803 |        | 0.3952 | 0.388  |
|                        | 0.3784 | 0.3647 |        | 0.3898 | 0.3716 |
|                        | 0.367  | 0.3578 |        | 0.3784 | 0.3647 |
| <b>Q rank (5700 K)</b> |        |        |        |        |        |
| QW                     | 0.3207 | 0.3462 | QY     | 0.3290 | 0.3538 |
|                        | 0.3290 | 0.3538 |        | 0.3376 | 0.3616 |
|                        | 0.3290 | 0.3417 |        | 0.3371 | 0.3490 |
|                        | 0.3215 | 0.3350 |        | 0.3290 | 0.3417 |
| QX                     | 0.3215 | 0.3350 | QZ     | 0.3290 | 0.3417 |
|                        | 0.3290 | 0.3417 |        | 0.3371 | 0.3490 |
|                        | 0.3290 | 0.3300 |        | 0.3366 | 0.3369 |
|                        | 0.3222 | 0.3243 |        | 0.3290 | 0.3300 |



b) Chromaticity Region & Coordinates ( $I_F = 540 \text{ mA}$ ,  $T_a = 25 \text{ }^\circ\text{C}$ )



| MacAdam Ellipse (WA, WB) |        |        |          |        |        |
|--------------------------|--------|--------|----------|--------|--------|
| Step                     | CIE x  | CIE y  | $\theta$ | a      | b      |
| 2-step                   | 0.4578 | 0.4101 | 53.70    | 0.0054 | 0.0028 |
| 3-step                   | 0.4578 | 0.4101 | 53.70    | 0.0081 | 0.0042 |

| MacAdam Ellipse (VA, VB) |        |        |          |        |        |
|--------------------------|--------|--------|----------|--------|--------|
| Step                     | CIE x  | CIE y  | $\theta$ | a      | b      |
| 2-step                   | 0.4338 | 0.403  | 53.22    | 0.0056 | 0.0027 |
| 3-step                   | 0.4338 | 0.4030 | 53.22    | 0.0083 | 0.0041 |

| MacAdam Ellipse (UA, UB) |        |        |          |        |        |
|--------------------------|--------|--------|----------|--------|--------|
| Step                     | CIE x  | CIE y  | $\theta$ | a      | b      |
| 2-step                   | 0.4073 | 0.3917 | 54.00    | 0.0062 | 0.0028 |
| 3-step                   | 0.4073 | 0.3917 | 54.00    | 0.0093 | 0.0041 |

| MacAdam Ellipse (TA, TB) |        |        |          |        |        |
|--------------------------|--------|--------|----------|--------|--------|
| Step                     | CIE x  | CIE y  | $\theta$ | a      | b      |
| 2-step                   | 0.3818 | 0.3797 | 53.72    | 0.0063 | 0.0027 |
| 3-step                   | 0.3818 | 0.3797 | 53.72    | 0.0094 | 0.0040 |

| MacAdam Ellipse (RA) |        |        |          |        |        |
|----------------------|--------|--------|----------|--------|--------|
| Step                 | CIE x  | CIE y  | $\theta$ | a      | b      |
| 3-step               | 0.3447 | 0.3553 | 59.62    | 0.0082 | 0.0035 |

**Note:**

Samsung maintains measurement tolerance of:  $C_x, C_y = \pm 0.005$




### 3. Typical Characteristics Graphs

#### a) Spectrum Distribution ( $I_F = 540 \text{ mA}$ , $T_c = 25^\circ \text{C}$ )

CCT: 2700 K




CCT: 3000 K



CCT: 3500 K




CCT: 4000 K




CCT: 5000 K





CCT: 5700 K



b) Forward Current Characteristics ( $T_c = 25^\circ\text{C}$ )





c) Temperature Characteristics ( $I_f = 540\text{ mA}$ )




d) Color Shift Characteristics

$T_c = 25^\circ\text{C}$


$I_f = 540\text{ mA}$



## e) Derating Curve

f) Beam Angle Characteristics ( $I_F = 540$  mA,  $T_c = 25$  °C)

4. Outline Drawing & Dimension



| Item                                  | Dimension | Tolerance | Unit |
|---------------------------------------|-----------|-----------|------|
| Length                                | 17.0      | ±0.15     | mm   |
| Width                                 | 17.0      | ±0.15     | mm   |
| Height                                | 1.50      | ±0.20     | mm   |
| Light Emitting Surface (LES) Diameter | 12.4      | ±0.15     | mm   |

Note: Denoted product information above is only an example  
 ( 19W8027 : 19W, CRI80+, 2700K )



## 5. Reliability Test Items & Conditions

### a) Test Items

| Test Item                           | Test Condition  | Test Hour / Cycle |
|-------------------------------------|---|-------------------|
| Room Temperature Life Test          | 25 °C, $I_F = \text{max}$   | 1000 h            |
| High Temperature Humidity Life Test | 85 °C, 85 % RH, DC Derating, $I_F = \text{max}$   | 1000 h            |
| High Temperature Life Test          | 105 °C, DC Derating, $I_F = \text{max}$   | 1000 h            |
| Low Temperature Life Test           | -40 °C, DC 980 mA   | 1000 h            |
| High Temperature Storage            | 120 °C  | 1000 h            |
| Low Temperature Storage             | -40 °C  | 1000 h            |
| Thermal Shock                       | -45 °C / 15 min ↔ 125 °C / 15 min<br>temperature change in 5 min  | 200 cycles        |
| Temperature Cycle On/Off Test       | -40 °C / 85 °C each 20 min, 100 min transfer<br>power on/off each 5 min, DC 540 mA  | 100 cycles        |
| Temperature Humidity Storage Test   | -10 °C ↔ 25 °C, 95 % RH ↔ 85 °C, 95 % RH<br>(24 h / cycle)  | 100 cycles        |
| ESD (HBM)                           | $R_1$ : 10 MΩ<br>$R_2$ : 1.5 kΩ<br>C: 100 pF<br>V: ±2 kV  | 5 times           |
| ESD (MM)                            | $R_1$ : 10 MΩ<br>$R_2$ : 0 kΩ<br>C: 200 pF<br>V: ±0.5 kV  | 5 times           |
| Vibration Test                      | 20 ~ 80 Hz (displacement: 0.06 inch, max. 20 g)<br>80 ~ 2 kHz (max. 20 g)<br>min. frequency ↔ max. frequency 4 min transfer | 4 times           |
| Mechanical Shock Test               | 1500 g, 0.5 ms<br>each of the 6 surfaces (3 axis x 2 sides)   | 5 times           |
| Salt Spray Test                     | 35 °C, 5 % salt water<br>8 h spray, 16 h dwell  | 2 cycles          |

### b) Criteria for Judging the Damage

| Item            | Symbol   | Test Condition<br>( $T_C = 25\text{ °C}$ ) | Limit        |              |
|-----------------|----------|--|--------------|--------------|
|                 |          |  | Min.         | Max.         |
| Forward Voltage | $V_F$    | $I_F = 540\text{ mA}$                      | L.S.L. * 0.9 | U.S.L. * 1.1 |
| Luminous Flux   | $\Phi_v$ | $I_F = 540\text{ mA}$                      | L.S.L. * 0.7 | U.S.L. * 1.3 |



## b) Lot Number

The lot number is composed of the following characters:


●◎◇◆□■△△△ / 1▲▲▲ / xxx PCS

- : Production site (S: Giheung, Korea, G: Tianjin, China)
- ◎ : L (LED)
- ◇ : Product state (A: Normal, B: Bulk, C: First Production, R: Reproduction, S: Sample)
- ◆ : Year (Y: 2014, Z: 2015, A: 2016, ...)
- : Month (1~9, A, B, C)
- : Day (1~9, A, B~V)
- △△△ : Product serial number (001 ~ 009)
- ▲▲▲ : Tray number (001 ~ 999)

## 7. Packing Structure


| Packing material | Max. quantity in pcs of COB | Dimension (mm) |       |        |           |
|------------------|-----------------------------|----------------|-------|--------|-----------|
|                  |                             | Length         | Width | Height | Tolerance |
| Tray             | 60                          | 322.6          | 135.9 | 10.8   | 1.0       |
| Aluminum Bag     | 480 (8 trays)               | 450            | 230   | -      | 10        |
| PE Foam Pad      | -                           | 280            | 130   | 10     | 2         |
| Inner Box        | 480 (1 aluminum bag)        | 338            | 148   | 55     | 2         |
| Outer Box        | 1,920 (4 inner boxes)       | 351            | 308   | 120    | 5         |
| Pallet           | 107,520 (56 outer boxes)    | 1000           | 1000  | 130    | 10        |

### a) Packing Structure




b) Tray


① COVER



② BODY



c) Aluminum Vinyl Packing Bag



d) Silica Gel & Humidity Indicator Card inside Aluminum Vinyl Packing Bag



## 8. Precautions in Handling & Use

- 1) This device should not be used in any type of fluid such as water, oil, organic solvent, etc. When cleaning is required, IPA is recommended as the cleaning agent. Some solvent-based cleaning agent may damage the silicone resins used in the device.
- 2) LEDs must be stored in a clean environment. If the LEDs are to be stored for three months or more after being shipped from Samsung, they should be packed with a nitrogen-filled container (shelf life of sealed bags is 12 months at temperature 0~40 °C, 0~90 % RH).
- 3) After storage bag is opened, device subjected to soldering, solder reflow, or other high temperature processes must be:
  - a. Mounted within 672 hours (28 days) at an assembly line with a condition of no more than 30 °C / 60 % RH, or
  - b. Stored at <10 % RH
- 4) Repack unused products with anti-moisture packing, fold to close any opening and then store in a dry place.
- 5) Devices require baking before mounting, if humidity card reading is >60 % at 23 ± 5 °C.
- 6) Devices must be baked for 1 hour at 60 ± 5 °C, if baking is required.
- 7) The LEDs are sensitive to the static electricity and surge current. It is recommended to use a wrist band or anti-electrostatic glove when handling the LEDs. If voltage exceeding the absolute maximum rating is applied to LEDs, it may cause damage or even destruction to LED devices. Damaged LEDs may show some unusual characteristics such as increase in leakage current, lowered turn-on voltage, or abnormal lighting of LEDs at low current.
- 8) VOCs (Volatile Organic Compounds) can be generated from adhesives, flux, hardener or organic additives used in luminaires (fixtures). Transparent LED silicone encapsulant is permeable to those chemicals and they may lead to a discoloration of encapsulant when they exposed to heat or light. This phenomenon can cause a significant loss of light emitted (output) from the luminaires. In order to prevent these problems, we recommend users to know the physical properties of materials used in luminaires and they must be carefully selected.
- 9) The resin area is very sensitive, please do not handle, press, touch, rub, clean, or pick by with tweezers on it. Instead, please pick at the handling area as indicated below.



## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View SPHCW1HDNB25YHRT1G on WIN SOURCE](#)

 [Samsung Information](#)

## Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management