



**THE DATASHEET OF  
SFSD0512N1BN1TO-E-ME-161-STD**



swissbit<sup>®</sup>

Product Fact Sheet

Industrial  
MICRO SD Memory Card

**S-200u Series**

SPI and SD compliant



# S-200U SERIES

## MICRO SD Memory Card

### 1 Feature summary

- Highly-integrated memory controller
  - Fully compliant with SD Memory Card specification 2.0 and Micro SD Memory Card specification 2.0 addendum
  - Four integrated 4KByte Sector Buffers for fast data transfer
- Standard MICRO SD Memory Card form factor
  - 15.0mm x 11.0mm x 0.7mm
- 2.7...3.6V normal operating voltage
- 2.0...3.6V basic communication (CMD0, 15, 55 ACMD41) voltage
- Low-power CMOS technology
- Wear Leveling: equal wear leveling of static and dynamic data.  
The wear leveling assures that dynamic data as well as static data is balanced evenly across the memory. With that the maximum write endurance of the device is guaranteed.
- Patented power-off reliability
  - No data loss of older sectors
  - Max. 16 sectors data loss (old data kept) if power off during writing
- High reliability
  - Best available SLC NAND Flash technology
  - Designed for embedded market
  - MTBF: > 3,000,000 hours
  - Number of insertions: >10,000
  - Extended Temperature range: -25° up to 85°C
  - Industrial Temperature range: -40° up to 85°C
- Hot swappable
- CPRM keys optional
- High performance
  - SD burst up to 25MB/s
  - SD Low speed 0...25MHz clock rate
  - SD High speed 25...50MHz clock rate
  - Up to 21/18 MB/s sustained read/write speed
  - Flash burst up to 40MB/s
  - "Default speed cards" with disabled high speed mode available
- Available densities
  - up to 2GBytes
- Controlled BOM
- Life Time Monitoring SD/SPI with standard or vendor commands



## 2 Order Information

### 2.1 Standard product list

Table 1: General Product List

Capacity	Part Number
512MB	SFSD0512NgBN1TO-t-ME-1x1-STD
1GB	SFSD1024NgBN1TO-t-DF-1x1-STD
2GB	SFSD2048NgBN1TO-t-QF-1x1-STD

g defines the product generation

t defines the temperature range (E=-25°C to +85°C, I=-40°C to +85°C)

x defines the FW

### 2.2 Current standard product list

Table 2: General Product List

Capacity	Part Number
<b>Extended Temperature Range</b>	
512MB	SFSD0512N1BN1TO-E-ME-171-STD
1GB	SFSD1024N1BN1TO-E-DF-171-STD
2GB	SFSD2048N1BN1TO-E-QF-171-STD
<b>Industrial Temperature Range</b>	
512MB	SFSD0512N1BN1TO-I-ME-171-STD
1GB	SFSD1024N1BN1TO-I-DF-171-STD
2GB	SFSD2048N1BN1TO-I-QF-171-STD

### 2.3 Offered options for customer projects

- Customer specified strings and IDs (MID, OID, PNM, PRV)
- Customer specified capacities
- Preload service
- Customized printing and lasering
- Permanent write protected (ROM) with preloaded software
- Default speed mode
- Diagnostic documentation for Card Status Register access or vendor command extension values
- ...

#### Disclaimer:



No part of this document may be copied or reproduced in any form or by any means, or transferred to any third party, without the prior written consent of an authorized representative of Swissbit AG ("SWISSBIT"). The information in this document is subject to change without notice. SWISSBIT assumes no responsibility for any errors or omissions that may appear in this document, and disclaims responsibility for any consequences resulting from the use of the information set forth herein. SWISSBIT makes no commitments to update or to keep current information contained in this document. The products listed in this document are not suitable for use in applications such as, but not limited to, aircraft control systems, aerospace equipment, submarine cables, nuclear reactor control systems and life support systems. Moreover, SWISSBIT does not recommend or approve the use of any of its products in life support devices or systems or in any application where failure could result in injury or death. If a customer wishes to use SWISSBIT products in applications not intended by SWISSBIT, said customer must contact an authorized SWISSBIT representative to determine SWISSBIT willingness to support a given application. The information set forth in this document does not convey any license under the copyrights, patent rights, trademarks or other intellectual property rights claimed and owned by SWISSBIT. The information set forth in this document is considered to be "Proprietary" and "Confidential" property owned by SWISSBIT.

ALL PRODUCTS SOLD BY SWISSBIT ARE COVERED BY THE PROVISIONS APPEARING IN SWISSBIT'S TERMS AND CONDITIONS OF SALE ONLY, INCLUDING THE LIMITATIONS OF LIABILITY, WARRANTY AND INFRINGEMENT PROVISIONS. SWISSBIT MAKES NO WARRANTIES OF ANY KIND, EXPRESS, STATUTORY, IMPLIED OR OTHERWISE, REGARDING INFORMATION SET FORTH HEREIN OR REGARDING THE FREEDOM OF THE DESCRIBED PRODUCTS FROM INTELLECTUAL PROPERTY INFRINGEMENT, AND EXPRESSLY DISCLAIMS ANY SUCH WARRANTIES INCLUDING WITHOUT LIMITATION ANY EXPRESS, STATUTORY OR IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.






©2016 SWISSBIT AG All rights reserved.

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

-  [View SFSD0512N1BN1TO-E-ME-161-STD on WIN SOURCE](#)
-  [Swissbit NA Inc. Information](#)

## Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management