



**THE DATASHEET OF  
SFSD2048L1BN2TO-I-DF-161-STD**



swissbit®

Product Fact Sheet

Industrial  
SD Memory Card

**S-200 Series**  
SPI, SD compliant



# S-200 Series Industrial SD Memory Card

## 1 Feature

- Custom-designed, highly-integrated memory controller
  - Fully compliant with SD Memory Card specification 2.0
  - Four integrated 4KByte Sector Buffers for fast data transfer
  - SPI Mode support
- Standard SD Memory Card form factor
  - 32.0mm x 24.0mm x 2.1mm
  - Write Protect slider
- 2.7...3.6V normal operating voltage
- 2.0...3.6V basic communication (CMD0, 15, 55 ACMD41) voltage
- Low-power CMOS technology
- Wear Leveling: equal wear leveling of static and dynamic data  
The wear leveling assures that dynamic data as well as static data is balanced evenly across the memory. With that the maximum write endurance of the device is guaranteed.
- Patented power-off reliability
  - No data loss of older sectors
  - Max. 16 sectors data loss (old data kept) if power off during writing
- High reliability
  - Best available SLC NAND Flash technology
  - Designed for embedded market
  - MTBF: > 3,000,000 hours
  - Number of insertions: >10,000
  - Extended Temperature range -25° up to 85°C
  - Optional industrial Temperature range available -40° up to 85°C
- Hot swappable
- High performance
  - SD burst up to 25MB/s
  - SD Low speed 0...25MHz clock rate
  - SD High speed 25...50MHz clock rate
  - Flash burst up to 40MB/s
- Available densities
  - up to 2GBytes (higher densities are in the SDHC S-220 Series available up to 8GB)
- Controlled BOM
- Life Time Monitoring SD/SPI with standard or vendor commands



## System Performance

System Performance		typ	max	Unit
Burst Data transfer Rate (max clock 50MHz)			25	MB/s
Sustained Sequential Read	2GB	23.6	24	
Sustained Sequential Write	2GB	15	18	

Current Consumption @3.3V		typ	max	Unit
Write (512MB / 1-2GB)		45/65	70/80	mA
Read		40	60	
Sleep Mode		0.2	0.3	

## Physical Dimensions

Physical Dimensions	value	Unit
Length	32.00±0.10	mm
Width	24.00±0.10	
Thickness	2.10±0.15	
Weight (typ.)	2	g

## Recommended Temperature Conditions

Parameter	min	typ	max	Unit
Extended Operating Temperature	-25	25	85	°C
Industrial Operating Temperature	-40	25	85	°C
Storage Temperature	-40	25	100	°C

## Humidity and ESD

Parameter	Operating	Non Operating
Humidity (non-condensing)	max 95%	
ESD according to IEC61000-4-2 Human body model ±4 kV 100 pf/1.5 kOhm Machine model ±0.25 kV 200 pf/0 Ohm	<b>Non Contact Pads area:</b> ±8 kV (coupling plane discharge) ±15 kV (air discharge) Human body model according to IEC61000-4-2	<b>Contact Pads:</b> ±4 kV, Human body model according to IEC61000-4-2

## Durability

Parameter	Operating	Non Operating
Salt water spray	3% NaCl/35°C; 24h acc. MIL STD Method 1009	
Solar Exposure / Impermeability	1000W/m <sup>2</sup> @ 400°C / IP67	
UV Light Exposure	UV: 254nm, 15Ws/cm <sup>2</sup>	
Insertions / Drop test	>10,000/ 1.5m free fall	
Bending / Torque / Bump	10N / 0.15Nm or ±2.5deg / 25g; 6ms; ±3 x 4000 shocks	
Shock / Vibration (peak -to-peak)	1000 g max. / 15G max.	
Minimum moving force of WP slider	0.4N	



For more information on SD Memory Card Spec 2.0, please visit SD association ([www.sdcard.org](http://www.sdcard.org))

## Why Swissbit?

Swissbit strives to create innovative technologies for future market opportunities utilizing a highly skilled in-house product research and development team. Swissbit maintains a marketing edge by continuing to manufacture world-class high quality memory products and providing customers with both high value and low cost of ownership achieved through efficient processes and procedures.

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

-  [View SFSD2048L1BN2TO-I-DF-161-STD on WIN SOURCE](#)
-  [Swissbit NA Inc. Information](#)

## Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management