



**THE DATASHEET OF
SF2005B-1**




Preliminary

March 11, 2003



SF2005B-1

**167.0 MHz
SAW Filter**



SMP53-S

- **Single Ended Input / Differential Output**
- **Low Insertion Loss**
- **Hermetic 13.3 x 6.5 mm Surface-mount Case**

Absolute Maximum Ratings

Rating	Value	Units
Maximum Incident Power in Passband	+10	dBm
Max. DC voltage between any 2 terminals	30	VDC
Storage Temperature Range	-40 to +85	°C
Max. Soldering Profile	265°C for 10 s	

Electrical Characteristics

Characteristic	Sym	Notes	Min	Typ	Max	Units
Nominal Frequency	f_C	1		167		MHz
Passband bandwidth	2dB BW		0.150			MHz
Insertion Loss	167 ±.075 MHz	1, 2,3			4.0	dB
Rejection	30 to 147 MHz		30			
	147 to 166.4 MHz		10			
	167.6 to 187 MHz		10			
	187 to 1000 MHz	30				
Amplitude ripple (p-p)	$f_C \pm .075$ MHz	Δ_a			0.5	
Operating Temperature		1	-5	+25	+85	°C
50 Ohm single ended match Input Return Loss			15			dB
50 Ohm differential Output Return Loss			10			dB
Group Delay Deviation $F_C \pm .075$ MHz	GDD				300	nsec

Impedance Matching	External L-C
Case Style	SMP-53-S 13.3 x 6.5 mm Nominal Footprint
Lid Symbolization (YY = year, WW = week, S=shift)	RFM SF2005B-1 YYWWS

Electrical Connections

Connection	Terminals
Port 1 Hot	10
Port 1 Gnd Return	1
Port 2 Hot	5
Port 2 Gnd Return	6
Case Ground	All Others
Single Ended Operation	Return is ground
Differential Operation	Return is hot





fig 1 values TBD

- Notes:**
1. Unless noted otherwise, all specifications apply over the operating temperature range with filter soldered to the specified demonstration board with impedance matching to 50 Ω and measured with 50 Ω network analyzer.
 2. Unless noted otherwise, all frequency specifications are referenced to the nominal center frequency, f_C .
 3. Rejection is measured as attenuation from f_C IL. Rejection in final user application is dependent on PCB layout and external impedance matching design. See Application Note No. 42 for details.
 4. Part to part absolute delay measurement records the absolute delay mean across 2 dB passband.
 5. "LRIP" or "L" after the part number indicates "low rate initial production" and "ENG" or "E" indicates "engineering prototypes."
 6. The design, manufacturing process, and specifications of this filter are subject to change.
 7. Either Port 1 or Port 2 may be used for either input or output in the design. However, impedances and impedance matching may vary between Port 1 and Port 2, so that the filter must always be installed in one direction per the circuit design.
 8. US and international patents may apply.
 9. Electrostatic Sensitive Device. Observe precautions for handling.



SMP-53-S Case

10-Terminal Ceramic Surface-Mount Case
13.3 x 6.5 mm Nominal Footprint




Case Dimensions

Dimension	mm			Inches		
	Min	Nom	Max	Min	Nom	Max
A		13.3			.524	
B		6.5			.256	
C			2.00			.078
D		2.3			.091	
E		1.91			.075	
F		1.02			.040	
G		1.0			0.039	

Electrical Connections


Connection	Terminals
Port 1 Hot	10
Port 1 Gnd Return	1
Port 2 Hot	5
Port 2 Gnd Return	6
Case Ground	All others
Single Ended Operation	Return is ground
Differential Operation	Return is hot




24mm Carrier Tape

Dimensions

Carrier Tape Dimensions		Cover Tape
Ao	.274 ± .004 (7.0)	21.3mm
Bo	.542 ± .004 (13.76)	
Ko	.088 ± .004 (2.2)	
P	12mm	
W	24mm	
Tape Length	86M	
Pockets/M	83/M	





COMPONENT ORIENTATION



Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

-  [View SF2005B-1 on WIN SOURCE](#)
-  [Murata Electronics North America Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management