



**THE DATASHEET OF
RCWE0603R750FKEA**



Thick Film Surface Mount Chip Resistors, Wraparound, Extremely Low Value (0.01 Ω to 0.976 Ω)



LINKS TO ADDITIONAL RESOURCES



FEATURES

- Extremely low resistance values (0.01 Ω to 0.976 Ω)
- Sulfur resistant (per ASTM B809-95 humid vapor test)
- Enhanced power rating due to long side terminal construction (0612, 1020 types)
- Suitable for current sensing and shunts
- Metal glaze on high quality ceramic
- Protective overglaze
- Lead (Pb)-free solder contacts on Ni barrier layer
- AEC-Q200 qualified
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912



RoHS
COMPLIANT
HALOGEN
FREE

| STANDARD ELECTRICAL SPECIFICATIONS | | | | | | |
|------------------------------------|-----------|---|-------------------------------------|-----------------------|-------------------------------|-------------------------|
| GLOBAL MODEL | CASE SIZE | POWER RATING $P_{70\text{ }^{\circ}\text{C}}$ W | TEMPERATURE COEFFICIENT + ppm/°C | RESISTANCE RANGE Ω | TOLERANCE ± % | E-SERIES ⁽²⁾ |
| RCWE0402 ⁽³⁾⁽⁴⁾ | 0402 | 0.125 | 400 | 0.033 to 0.05 | 5.0 | 24 |
| | | | 200 | 0.051 to 0.196 | 1.0, 5.0 | 24; 96 |
| | | | 100 | 0.2 to 0.976 | 0.5 ⁽¹⁾ , 1.0, 5.0 | |
| RCWE0603 ⁽⁴⁾ | 0603 | 0.2 | 700 | 0.010 to 0.018 | 5.0 | 24 |
| | | | 400 | 0.02 to 0.0324 | 1.0, 5.0 | 24; 96 |
| | | | 200 | 0.033 to 0.105 | 1.0, 5.0 | |
| RCWE0805 ⁽⁴⁾ | 0805 | 0.25 | 100 | 0.11 to 0.976 | 0.5 ⁽¹⁾ , 1.0, 5.0 | 24; 96 |
| | | | 400 | 0.010 to 0.018 | 5.0 | |
| | | | 300 | 0.02 to 0.0324 | 1.0, 5.0 | |
| RCWE0612 ⁽⁴⁾ | 0612 | 1.0 | 200 | 0.033 to 0.05 | 1.0, 5.0 | 24; 96 |
| | | | 100 | 0.051 to 0.976 | 0.5 ⁽¹⁾ , 1.0, 5.0 | |
| | | | 300 | 0.010 to 0.016 | 2.0, 5.0 | |
| RCWE1206 ⁽⁴⁾ | 1206 | 0.5 | 600 | 0.010 to 0.018 | 5.0 | 24 |
| | | | 300 | 0.02 to 0.0324 | 1.0, 5.0 | 24; 96 |
| | | | 200 | 0.033 to 0.05 | 1.0, 5.0 | |
| RCWE1210 ⁽⁴⁾ | 1210 | 1.0 | 100 | 0.051 to 0.976 | 0.5 ⁽¹⁾ , 1.0, 5.0 | 24; 96 |
| | | | 500 | 0.010 to 0.018 | 5.0 | |
| | | | 300 | 0.02 to 0.0324 | 1.0, 5.0 | |
| RCWE1020 ⁽⁴⁾ | 1020 | 2.0 | 200 | 0.010 to 0.016 | 2.0, 5.0 | 24 |
| | | | 100 | 0.0162 to 0.976 | 1.0, 5.0 | 24; 96 |
| | | | 600 | 0.010 to 0.018 | 5.0 | |
| RCWE2010 ⁽⁴⁾ | 2010 | 1.0 | 300 | 0.02 to 0.0324 | 1.0, 5.0 | 24; 96 |
| | | | 200 | 0.033 to 0.05 | 1.0, 5.0 | |
| | | | 100 | 0.051 to 0.976 | 0.5 ⁽¹⁾ , 1.0, 5.0 | |
| RCWE2512 ⁽⁴⁾ | 2512 | 2.0 | 600 | 0.010 to 0.018 | 5.0 | 24 |
| | | | 300 | 0.02 to 0.0324 | 1.0, 5.0 | 24; 96 |
| | | | 200 | 0.033 to 0.05 | 1.0, 5.0 | |
| | | | 100 | 0.051 to 0.976 | 0.5 ⁽¹⁾ , 1.0, 5.0 | |

Notes

- Power rating depends on the max. temperature at the solder point, the component placement density and the substrate material
- Part marking: Reference "Surface Mount Resistor Marking" (www.vishay.com/doc?20020)
- Temperature range of TCR rating is 0 °C to 150 °C. TCR values are (+) range only with no (-) range values; 1/2 of previous tolerance range
- ⁽¹⁾ Tight tolerance of 0.5 % is available for resistance values above 0.300 Ω (0402 size) and above 0.200 Ω (0603 to 2512 sizes)
- ⁽²⁾ Use E24 decades only for 5.0 % tolerance. E24 or E96 decades are available for 0.5 % and 1.0 % tolerance. Refer to standard decade table (www.vishay.com/doc?31001)
- ⁽³⁾ Terminal strength tested per AEC-Q200-006 with the exception of 0.75 kg force is used
- ⁽⁴⁾ Qualified to AEC-Q200 rev. D

GLOBAL PART NUMBER INFORMATION

 Global Part Numbering Example: RCWE060351L0FNEA (visit www.vishay.net Vishay Dale parts numbering manual for all options)

| | | | | | | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|--|--|
| R | C | W | E | 0 | 6 | 0 | 3 | 5 | 1 | L | 0 | F | N | E | A | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|--|--|

GLOBAL MODEL
(8 digits)

 RCWE0402
 RCWE0603
 RCWE0805
 RCWE0612
 RCWE1206
 RCWE1210
 RCWE1020
 RCWE2010
 RCWE2512

VALUE
(4 digits)

 L = mΩ *
 R = decimal
 10L0 = 0.01 Ω
 R470 = 0.47 Ω
Note:
 * Use "L" for resistance values < 0.1 Ω

TOLERANCE
(1 digit)

 D = ± 0.5 %
 F = ± 1.0 %
 G = ± 2.0 %
 J = ± 5.0 %

TCR
(1 digit)

 K = +100 ppm/°C
 N = +200 ppm/°C
 M = +300 ppm/°C
 Q = +400 ppm/°C
 P = +500 ppm/°C
 T = +600 ppm/°C
 G = +700 ppm/°C

PACKAGING
(2 digits)

EA = lead (Pb)-free, tape/reel

SPECIAL
(up to 2 digits)

(dash number) from 1 to 99 as applicable



TECHNICAL SPECIFICATIONS

| PARAMETER | UNIT | 0402 | 0603 | 0805 | 0612 | 1206 | 1210 | 1020 | 2010 | 2512 |
|--------------------------------------|------|----------------------|-------|-------|-------|-------|-------|-------|-------|-------|
| Operating temperature range | °C | -55 to +155 | | | | | | | | |
| Maximum operating voltage | V | $(P \times R)^{1/2}$ | | | | | | | | |
| Insulation voltage U_{ins} (1 min) | V | > 75 | > 100 | > 200 | > 100 | > 300 | > 300 | > 300 | > 300 | > 300 |
| Insulation resistance | Ω | > 10 ⁹ | | | | | | | | |
| Weight/1000 pieces (typical) | g | 0.7 | 3 | 5.5 | 11.5 | 10.5 | 17.5 | 27.5 | 26 | 40.5 |

DIMENSIONS

RCWE0402 to RCWE2512

RCWE0612, RCWE1020




| SIZE | DIMENSIONS in millimeters | | | | | | SOLDER PAD DIMENSIONS in millimeters | | | |
|------|---------------------------|-------------|-------------|------------|-------------|-------------|--------------------------------------|-----|-----|-----|
| | RESISTANCE RANGE Ω | L | W | H | T1 | T2 | a | b | l | |
| 0402 | 0.033 to 0.976 | 1.05 ± 0.05 | 0.55 ± 0.05 | 0.35 ± 0.1 | 0.3 ± 0.15 | 0.25 ± 0.1 | 0.7 | 0.7 | 0.3 | |
| 0603 | 0.01 to 0.03 | 1.6 ± 0.1 | 0.85 ± 0.1 | 0.5 ± 0.1 | 0.5 ± 0.2 | 0.3 ± 0.2 | 0.9 | 1.0 | 0.4 | |
| | 0.033 to 0.976 | | | | 0.3 ± 0.2 | | | | | 0.7 |
| 0805 | 0.01 to 0.03 | 2.0 ± 0.15 | 1.3 ± 0.1 | 0.55 ± 0.1 | 0.6 ± 0.2 | 0.35 ± 0.2 | 1.0 | 1.4 | 0.6 | |
| | 0.033 to 0.976 | | | | 0.4 ± 0.2 | | | | | 0.8 |
| 0612 | 0.01 to 0.976 | 1.6 ± 0.2 | 3.2 ± 0.2 | 0.6 ± 0.1 | 0.4 ± 0.15 | 0.25 ± 0.15 | 0.9 | 3.5 | 0.8 | |
| 1206 | 0.01 to 0.03 | 3.1 ± 0.15 | 1.6 ± 0.15 | 0.6 ± 0.1 | 0.9 ± 0.2 | 0.45 ± 0.2 | 1.3 | 1.8 | 1.0 | |
| | 0.033 to 0.05 | | | | 0.8 ± 0.2 | | | | | 1.2 |
| | 0.051 to 0.976 | | | | 0.45 ± 0.2 | | | | | 1.0 |
| 1210 | 0.01 to 0.03 | 3.1 ± 0.2 | 2.5 ± 0.2 | 0.6 ± 0.1 | 0.8 ± 0.2 | 0.4 ± 0.2 | 1.3 | 2.6 | 1.1 | |
| | 0.033 to 0.976 | | | | 0.4 ± 0.2 | | | | | 0.9 |
| 1020 | 0.01 to 0.976 | 2.5 ± 0.2 | 5.0 ± 0.2 | 0.6 ± 0.1 | 0.55 ± 0.15 | 0.30 ± 0.15 | 1.2 | 5.5 | 1.4 | |
| 2010 | 0.01 to 0.03 | 5.0 ± 0.2 | 2.5 ± 0.15 | 0.6 ± 0.1 | 1.6 ± 0.3 | 0.6 ± 0.2 | 2.3 | 3.0 | 1.4 | |
| | 0.033 to 0.05 | | | | 0.7 ± 0.3 | | | | | 1.4 |
| | 0.051 to 0.976 | | | | 0.7 ± 0.3 | | | | | 1.4 |
| 2512 | 0.01 to 0.03 | 6.3 ± 0.2 | 3.15 ± 0.15 | 0.6 ± 0.1 | 2.0 ± 0.3 | 0.6 ± 0.2 | 2.8 | 3.6 | 1.4 | |
| | 0.033 to 0.05 | | | | 0.8 ± 0.3 | | | | | 1.6 |
| | 0.051 to 0.976 | | | | 0.8 ± 0.3 | | | | | 1.6 |

Notes

- 3D models available: www.vishay.com/doc?31106
- Surface mount solder profile recommendations: www.vishay.com/doc?31052

DERATING



SINGLE PULSE



SINGLE PULSE





| PERFORMANCE | | |
|---------------------------|--|--------------------|
| TEST | CONDITIONS OF TEST | TEST LIMITS |
| Thermal shock | MIL-STD-202, method 107, -55 °C to +125 °C, 300 cycles at each extreme | ± 1.0 % + 0.0005 Ω |
| Short time overload | 2 x rated power; size and duration - 0402: 0.5 s, 0603 and 0805: 1 s, 1206 and larger: 2 s | ± 0.5 % + 0.0005 Ω |
| High temperature exposure | MIL-STD-202, method 108, 1000 h at T = 125 °C, 0 % power | ± 2.0 % + 0.0005 Ω |
| Temperature cycling | JESD 22, method JA-104, 1000 cycles (-55 °C to +125 °C) | ± 2.0 % + 0.0005 Ω |
| Biased humidity | MIL-STD-202, method 103, 1000 h 85 °C / 85 % RH, 10 % x (P x R) ^{1/2} | ± 2.0 % + 0.0005 Ω |
| Mechanical shock | MIL-STD-202, method 213, condition C, 10 g's, 6 ms (half sine), 3 directions | ± 1.0 % + 0.0005 Ω |
| Vibration | MIL-STD-202, method 204, 5 g's, 20 min, 12 cycles, 3 directions, 10 Hz to 2000 Hz | ± 1.0 % + 0.0005 Ω |
| Operational life | MIL-STD-202, method 108, 1000 h at T = 125 °C at rated power | ± 2.0 % + 0.0005 Ω |
| Resistance to solder heat | MIL-STD-202, method 210, +260 °C solder, 10 s to 12 s dwell, 25 mm/s emergence | ± 1.0 % + 0.0005 Ω |
| Moisture resistance | MIL-STD-202, method 106, 0 % power, 7a and 7b not required | ± 2.0 % + 0.0005 Ω |

Note

- Contact ww2bresistors@vishay.com for application specific performance requirements or qualification data. Typical performance is better than stated test limits

| PACKAGING | | | | | |
|-----------|--------------------------|-------------|-------|-------------|------|
| MODEL | REEL | | | | |
| | TAPE WIDTH | DIAMETER | PITCH | PIECES/REEL | CODE |
| RCWE0402 | 8 mm / punched paper | 180 mm / 7" | 2 mm | 10 000 | EA |
| RCWE0603 | 8 mm / punched paper | 180 mm / 7" | 4 mm | 5000 | EA |
| RCWE0805 | 8 mm / punched paper | 180 mm / 7" | 4 mm | 5000 | EA |
| RCWE0612 | 8 mm / punched paper | 180 mm / 7" | 4 mm | 5000 | EA |
| RCWE1206 | 8 mm / punched paper | 180 mm / 7" | 4 mm | 5000 | EA |
| RCWE1210 | 8 mm / punched paper | 180 mm / 7" | 4 mm | 5000 | EA |
| RCWE1020 | 12 mm / embossed plastic | 180 mm / 7" | 4 mm | 4000 | EA |
| RCWE2010 | 12 mm / embossed plastic | 180 mm / 7" | 4 mm | 4000 | EA |
| RCWE2512 | 12 mm / embossed plastic | 180 mm / 7" | 8 mm | 2000 | EA |

Notes

- Embossed carrier tape per EIA-481-1A
- Additional packaging details at: www.vishay.com/doc?31543

| LINKS TO RELATED DOCUMENTS | |
|---|--|
| SELECTOR GUIDE | |
| Overview of Automotive Grade Products | www.vishay.com/doc?49924 |
| TECHNICAL NOTES | |
| SMD Current Sense: AEC-Q200 vs. Vishay Qualification | www.vishay.com/doc?30416 |
| MIL-PRF vs. AEC-Q200: Do You Know What You Are Getting? | www.vishay.com/doc?11000 |
| WHITE PAPER | |
| Thermal Management for Surface-Mount Devices | www.vishay.com/doc?30380 |
| Temperature Coefficient of Resistance for Current Sensing | www.vishay.com/doc?30405 |



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View RCWE0603R750FKEA on WIN SOURCE](#)

 [Vishay Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management