




## Features

- Very Tight Tolerance on  $V_Z$
- Ideally Suited for Automated Assembly Processes
- **Totally Lead-Free & Fully RoHS Compliant (Notes 1 & 2)**
- **Halogen and Antimony Free. "Green" Device (Note 3)**
- **Qualified to AEC-Q101 Standards for High Reliability**
- **PPAP Capable (Note 4)**

## Mechanical Data

- Case: SOD123
- Case Material: Molded Plastic, "Green Molding Compound". UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020
- Terminal Connections: Cathode Band
- Terminals: Finish - Matte Tin Annealed over Alloy 42 Leadframe. Solderable per MIL-STD-202, Method 208 (E3)
- Weight: 0.01 grams (Approximate)



## Ordering Information (Notes 4 & 5)

| Part Number          | Qualification | Case   | Packaging         |
|----------------------|---------------|--------|-------------------|
| DDZ( $V_Z$ Rank)-7*  | Commercial    | SOD123 | 3,000/Tape & Reel |
| DDZ( $V_Z$ Rank)Q-7* | Automotive    | SOD123 | 3,000/Tape & Reel |

\* Example: The part number for the 6.2 Volt device would be DDZ6V2B-7.

- Notes:
1. No purposely added lead. Fully EU Directive 2002/95/EC (RoHS) & 2011/65/EU (RoHS 2) compliant.
  2. See [http://www.diodes.com/quality/lead\\_free.html](http://www.diodes.com/quality/lead_free.html) for more information about Diodes Incorporated's definitions of Halogen- and Antimony-free, "Green" and Lead-free.
  3. Halogen- and Antimony-free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.
  4. Automotive products are AEC-Q101 qualified and are PPAP capable. Automotive, AEC-Q101 and standard products are electrically and thermally the same, except where specified. For more information, please refer to [http://www.diodes.com/quality/product\\_compliance\\_definitions/](http://www.diodes.com/quality/product_compliance_definitions/).
  5. For packaging details, go to our website at <http://www.diodes.com/products/packages.html>.

## Marking Information



xx = Product Type Marking Code  
(See Electrical Characteristics Table)  
YM = Date Code Marking  
Y = Year (ex: E = 2017)  
M = Month (ex: 9 = September)

### Date Code Key

| Year | 2003 | 2004 | ... | 2012 | 2013 | 2014 | 2015 | 2016 | 2017 | 2018 | 2019 | 2020 |
|------|------|------|-----|------|------|------|------|------|------|------|------|------|
| Code | P    | R    | ... | Z    | A    | B    | C    | D    | E    | F    | G    | H    |

| Month | Jan | Feb | Mar | Apr | May | Jun | Jul | Aug | Sep | Oct | Nov | Dec |
|-------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| Code  | 1   | 2   | 3   | 4   | 5   | 6   | 7   | 8   | 9   | O   | N   | D   |

**Maximum Ratings** (@T<sub>A</sub> = +25°C, unless otherwise specified.)

| Characteristic                          | Symbol         | Value | Unit |
|---|----------------|-------|------|
| Forward Voltage @ I <sub>F</sub> = 10mA | V <sub>F</sub> | 0.9   | V    |

**Thermal Characteristics**

| Characteristic                                       | Symbol                            | Value       | Unit |
|--|-----------------------------------|-------------|------|
| Power Dissipation (Note 6) @T <sub>L</sub> = +75°C   | P <sub>D</sub>                    | 500         | mW   |
| Power Dissipation (Note 7) @T <sub>A</sub> = +25°C   | P <sub>D</sub>                    | 470         | mW   |
| Power Dissipation (Note 8) @T <sub>A</sub> = +25°C   | P <sub>D</sub>                    | 294         | mW   |
| Thermal Resistance, Junction to Ambient Air (Note 7) | R <sub>θJA</sub>                  | 266         | °C/W |
| Thermal Resistance, Junction to Ambient Air (Note 8) | R <sub>θJA</sub>                  | 425         | °C/W |
| Operating and Storage Temperature Range              | T <sub>J</sub> , T <sub>STG</sub> | -65 to +150 | °C   |

**Electrical Characteristics** (@T<sub>A</sub> = +25°C, unless otherwise specified.)

| Type Number | Marking Code | Zener Voltage Range (Note 9)     |         |                 | Maximum Zener Impedance f = 1kHz  |                                   |                 | Maximum Reverse Current (Note 9) |                  |
|-------------|--------------|----------------------------------|---------|-----------------|-----------------------------------|-----------------------------------|-----------------|----------------------------------|------------------|
|             |              | V <sub>Z</sub> @ I <sub>ZT</sub> |         | I <sub>ZT</sub> | Z <sub>ZT</sub> @ I <sub>ZT</sub> | Z <sub>ZK</sub> @ I <sub>ZK</sub> | I <sub>ZK</sub> | I <sub>R</sub>                   | @ V <sub>R</sub> |
|             |              | Min (V)                          | Max (V) | mA              | Ω                                 |                                   | mA              | μA                               | V                |
| DDZ5V1B     | KM           | 4.94                             | 5.20    | 20              | 17                                | 480                               | 1               | 5                                | 1.5              |
| DDZ5V6B     | KN           | 5.45                             | 5.73    | 20              | 11                                | 400                               | 1               | 0.5                              | 2.5              |
| DDZ6V2B     | KO           | 5.96                             | 6.27    | 20              | 7                                 | 150                               | 1               | 0.5                              | 4.0              |
| DDZ6V8B     | KP           | 6.49                             | 6.83    | 20              | 5                                 | 150                               | 0.5             | 0.5                              | 5.0              |
| DDZ6V8C     | YP           | 6.66                             | 7.01    | 20              | 5                                 | 150                               | 0.5             | 0.5                              | 5.0              |
| DDZ7V5B     | KQ           | 7.07                             | 7.45    | 20              | 6                                 | 120                               | 0.5             | 0.5                              | 6.0              |
| DDZ7V5C     | YQ           | 7.29                             | 7.67    | 20              | 6                                 | 120                               | 0.5             | 0.5                              | 6.0              |
| DDZ8V2B     | KR           | 7.78                             | 8.19    | 20              | 8                                 | 120                               | 0.5             | 0.5                              | 6.5              |
| DDZ8V2C     | YR           | 8.03                             | 8.45    | 20              | 8                                 | 120                               | 0.5             | 0.5                              | 6.5              |
| DDZ9V1B     | KS           | 8.57                             | 9.01    | 20              | 8                                 | 120                               | 0.5             | 0.5                              | 7.0              |
| DDZ9V1C     | YS           | 8.83                             | 9.30    | 20              | 8                                 | 120                               | 0.5             | 0.5                              | 7.0              |
| DDZ10B      | KT           | 9.41                             | 9.90    | 20              | 8                                 | 120                               | 0.5             | 0.1                              | 8.0              |
| DDZ10C      | YT           | 9.70                             | 10.20   | 20              | 8                                 | 120                               | 0.5             | 0.1                              | 8.0              |
| DDZ11B      | KU           | 10.50                            | 11.05   | 10              | 10                                | 120                               | 0.5             | 0.1                              | 8.4              |
| DDZ11C      | YU           | 10.82                            | 11.38   | 10              | 10                                | 120                               | 0.5             | 0.1                              | 8.4              |
| DDZ12B      | KV           | 11.44                            | 12.03   | 10              | 12                                | 110                               | 0.5             | 0.1                              | 9.1              |
| DDZ12C      | YV           | 11.74                            | 12.35   | 10              | 12                                | 110                               | 0.5             | 0.1                              | 9.1              |
| DDZ13B      | KW           | 12.55                            | 13.21   | 10              | 14                                | 110                               | 0.5             | 0.1                              | 10.0             |
| DDZ14       | GX           | 13.65                            | 14.35   | 10              | 16                                | 110                               | 0.5             | 0.05                             | 11.0             |
| DDZ14B      | KX           | 13.89                            | 14.62   | 10              | 16                                | 110                               | 0.5             | 0.05                             | 11.0             |
| DDZ15       | GY           | 14.80                            | 15.57   | 10              | 18                                | 150                               | 0.5             | 0.05                             | 12.0             |
| DDZ16B      | KY           | 15.25                            | 16.04   | 10              | 18                                | 150                               | 0.5             | 0.05                             | 12.0             |
| DDZ16       | YY           | 15.69                            | 16.51   | 10              | 18                                | 150                               | 0.5             | 0.05                             | 12.0             |
| DDZ17       | KZ           | 16.82                            | 17.70   | 10              | 23                                | 150                               | 0.5             | 0.05                             | 14.0             |
| DDZ18C      | YZ           | 17.42                            | 18.33   | 10              | 23                                | 150                               | 0.5             | 0.05                             | 14.0             |
| DDZ19       | ZJ           | 18.63                            | 19.59   | 10              | 28                                | 200                               | 0.5             | 0.05                             | 15.0             |
| DDZ20C      | PJ           | 19.23                            | 20.22   | 10              | 28                                | 200                               | 0.5             | 0.05                             | 15.0             |
| DDZ21       | ZK           | 20.64                            | 21.71   | 5               | 30                                | 200                               | 0.5             | 0.05                             | 17.0             |
| DDZ22D      | 2K           | 21.52                            | 22.63   | 5               | 30                                | 200                               | 0.5             | 0.05                             | 17.0             |
| DDZ23       | ZL           | 22.61                            | 23.77   | 5               | 35                                | 200                               | 0.5             | 0.05                             | 19.0             |
| DDZ24C      | PL           | 23.12                            | 24.31   | 5               | 35                                | 200                               | 0.5             | 0.05                             | 19.0             |
| DDZ26       | ZM           | 24.97                            | 26.26   | 5               | 45                                | 250                               | 0.5             | 0.05                             | 21.0             |
| DDZ27D      | 2M           | 26.29                            | 27.64   | 5               | 45                                | 250                               | 0.5             | 0.05                             | 21.0             |
| DDZ28       | ZN           | 27.70                            | 29.13   | 5               | 55                                | 250                               | 0.5             | 0.05                             | 23.0             |
| DDZ30D      | 2N           | 29.02                            | 30.51   | 5               | 55                                | 250                               | 0.5             | 0.05                             | 23.0             |
| DDZ31       | ZO           | 30.32                            | 31.88   | 5               | 65                                | 250                               | 0.5             | 0.05                             | 25.0             |
| DDZ33       | RP           | 32.14                            | 33.79   | 5               | 75                                | 250                               | 0.5             | 0.05                             | 27.0             |
| DDZ34       | ZP           | 32.79                            | 34.49   | 5               | 75                                | 250                               | 0.5             | 0.05                             | 27.0             |
| DDZ36       | ZQ           | 35.36                            | 37.19   | 5               | 85                                | 250                               | 0.5             | 0.05                             | 30.0             |
| DDZ39F      | 5Q           | 38.02                            | 39.98   | 5               | 85                                | 250                               | 0.5             | 0.05                             | 30.0             |
| DDZ43       | ZR           | 42.14                            | 43.86   | 5               | 90                                | —                                 | —               | 0.05                             | 33.0             |

- Notes:
- R<sub>θJL</sub> = 132°C/W
  - Device mounted on FR-4 PC board, single-sided, 25mm x 25mm x 1.6mm, 2oz copper traces, with copper pad area 1in<sup>2</sup>.
  - Device mounted on FR-4 PC board, single-sided, 25mm x 25mm x 1.6mm, 2oz copper traces with 1x minimum recommended pad layout.
  - Short duration pulse test used to minimize self-heating effect.



Figure 1 Power Derating Curve



Figure 2 Typical Forward Characteristics



Figure 3 Typical Zener Breakdown Characteristics



Fig. 4 Typical Zener Breakdown Characteristics, DDZ5V1B - DDZ9V1C



Fig. 5 Typical Zener Breakdown Characteristics, DDZ10C - DDZ14



Fig. 6 Typical Zener Breakdown Characteristics, DDZ15 - DDZ18C



Fig. 7 Typical Zener Breakdown Characteristics, DDZ20C - DDZ24C



Fig. 8 Typical Zener Breakdown Characteristics, DDZ27D - DDZ36



Fig. 9 Typical Zener Breakdown Characteristics, DDZ43



Fig. 10 Typical Total Capacitance vs. Nominal Zener Voltage




Fig. 11 Typical Zener Impedance Characteristics, DDZ5V6B - DDZ12C



Fig. 12 Typical Zener Impedance Characteristics, DDZ12C - DDZ18C



Fig. 13 Typical Zener Impedance Characteristics, DDZ18C - DDZ24C



Fig. 14 Typical Zener Impedance Characteristics, DDZ24C - DDZ33



Fig. 15 Typical Zener Impedance Characteristics, DDZ36 - DDZ43



Fig. 16 Typical Temperature Coefficient of Zener Voltage vs. Zener Voltage, DDZ5V1B-DDZ10C



Fig. 17 Typical Temperature Coefficient of Zener Voltage vs. Zener Voltage, DDZ10C-DDZ20C



Fig. 18 Typical Temperature Coefficient of Zener Voltage vs. Zener Voltage, DDZ20C-DDZ30D




Fig. 19 Typical Temperature Coefficient of Zener Voltage vs. Zener Voltage, DDZ30D-DDZ43

**Package Outline Dimensions**

Please see <http://www.diodes.com/package-outlines.html> for the latest version.

**SOD123**



| SOD123               |      |      |      |
|----------------------|------|------|------|
| Dim                  | Min  | Max  | Typ  |
| A                    | 1.00 | 1.35 | 1.05 |
| A1                   | 0.00 | 0.10 | 0.05 |
| b                    | 0.52 | 0.62 | 0.57 |
| c                    | 0.10 | 0.15 | 0.11 |
| D                    | 1.40 | 1.70 | 1.55 |
| E                    | 2.55 | 2.85 | 2.65 |
| He                   | 3.55 | 3.85 | 3.65 |
| L                    | 0.25 | 0.40 | 0.30 |
| a                    | 0°   | 8°   | --   |
| All Dimensions in mm |      |      |      |

**Suggested Pad Layout**

Please see <http://www.diodes.com/package-outlines.html> for the latest version.

**SOD123**



| Dimensions | Value (in mm) |
|------------|---------------|
| X          | 0.900         |
| X1         | 4.050         |
| Y          | 0.950         |

**Note:** The suggested land pattern dimensions have been provided for reference only, as actual pad layouts may vary depending on application. These dimensions may be modified based on user equipment capability or fabrication criteria. A more robust pattern may be desired for wave soldering and is calculated by adding 0.2 mm to the 'Z' dimension. For further information, please reference document IPC-7351A, Naming Convention for Standard SMT Land Patterns, and for International grid details, please see document IEC, Publication 97.

**Note:** For high voltage applications, the appropriate industry sector guidelines should be considered with regards to creepage and clearance distances between device Terminals and PCB tracking.

**IMPORTANT NOTICE**

DIODES INCORPORATED MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. Diodes Incorporated does not assume any liability arising out of the application or use of this document or any product described herein; neither does Diodes Incorporated convey any license under its patent or trademark rights, nor the rights of others. Any Customer or user of this document or products described herein in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on Diodes Incorporated website, harmless against all damages.

Diodes Incorporated does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel. Should Customers purchase or use Diodes Incorporated products for any unintended or unauthorized application, Customers shall indemnify and hold Diodes Incorporated and its representatives harmless against all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized application.

Products described herein may be covered by one or more United States, international or foreign patents pending. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks.

This document is written in English but may be translated into multiple languages for reference. Only the English version of this document is the final and determinative format released by Diodes Incorporated.

**LIFE SUPPORT**

Diodes Incorporated products are specifically not authorized for use as critical components in life support devices or systems without the express written approval of the Chief Executive Officer of Diodes Incorporated. As used herein:

A. Life support devices or systems are devices or systems which:

1. are intended to implant into the body, or
2. support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in significant injury to the user.

B. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or to affect its safety or effectiveness.



Customers represent that they have all necessary expertise in the safety and regulatory ramifications of their life support devices or systems, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of Diodes Incorporated products in such safety-critical, life support devices or systems, notwithstanding any devices- or systems-related information or support that may be provided by Diodes Incorporated. Further, Customers must fully indemnify Diodes Incorporated and its representatives against any damages arising out of the use of Diodes Incorporated products in such safety-critical, life support devices or systems.

Copyright © 2017, Diodes Incorporated

[www.diodes.com](http://www.diodes.com)

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

-  [View DDZ18C-7 on WIN SOURCE](#)
-  [Diodes Incorporated](#) Information

## Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management