




**THE DATASHEET OF
TDL 3-0521**



- Compact 3W Converter in DIP package
- I/O-isolation 1'500 VDC
- Fully regulated outputs
- Wide 2 : 1 input voltage range
- Operating temperature range -40°C to +80°C
- Short circuit protection
- 3-year product warranty



The TDL 3 series with 2:1 input voltage range is a selection of 3 Watt regulated dc/dc-converters. They come in a very compact DIP package (0.55 × 0.55 × 0.31 inch).

| Models | | | | |
|------------|--|----------------|---------------------|-----------------|
| Order code | Input voltage | Output voltage | Output current max. | Efficiency typ. |
| TDL 3-0510 | 4.5 – 10 VDC (5 VDC nominal) | 3.3 VDC | 600 mA | 79 % |
| TDL 3-0511 | | 5.0 VDC | 600 mA | 81 % |
| TDL 3-0512 | | 12 VDC | 250 mA | 85 % |
| TDL 3-0513 | | 15 VDC | 200 mA | 85 % |
| TDL 3-0521 | | ±5.0 VDC | ±300 mA | 82 % |
| TDL 3-0522 | | ±12 VDC | ±125 mA | 84 % |
| TDL 3-0523 | | ±15 VDC | ±100 mA | 85 % |
| TDL 3-1210 | 9 – 18 VDC (12 VDC nominal) | 3.3 VDC | 600 mA | 80 % |
| TDL 3-1211 | | 5.0 VDC | 600 mA | 83 % |
| TDL 3-1212 | | 12 VDC | 250 mA | 87 % |
| TDL 3-1213 | | 15 VDC | 200 mA | 87 % |
| TDL 3-1221 | | ±5.0 VDC | ±300 mA | 84 % |
| TDL 3-1222 | | ±12 VDC | ±125 mA | 86 % |
| TDL 3-1223 | | ±15 VDC | ±100 mA | 87 % |
| TDL 3-2410 | 18 – 36 VDC (24 VDC nominal) | 3.3 VDC | 600 mA | 80 % |
| TDL 3-2411 | | 5.0 VDC | 600 mA | 83 % |
| TDL 3-2412 | | 12 VDC | 250 mA | 87 % |
| TDL 3-2413 | | 15 VDC | 200 mA | 87 % |
| TDL 3-2421 | | ±5.0 VDC | ±300 mA | 84 % |
| TDL 3-2422 | | ±12 VDC | ±125 mA | 86 % |
| TDL 3-2423 | | ±15 VDC | ±100 mA | 87 % |
| TDL 3-4810 | 36 – 75 VDC (48 VDC nominal) | 3.3 VDC | 600 mA | 79 % |
| TDL 3-4811 | | 5.0 VDC | 600 mA | 82 % |
| TDL 3-4812 | | 12 VDC | 250 mA | 86 % |
| TDL 3-4813 | | 15 VDC | 200 mA | 86 % |
| TDL 3-4821 | | ±5.0 VDC | ±300 mA | 82 % |
| TDL 3-4822 | | ±12 VDC | ±125 mA | 85 % |
| TDL 3-4823 | | ±15 VDC | ±100 mA | 85 % |

Input Specifications

| | |
|--|--|
| Input current no load | 5 Vin models: 45 mA typ. 12 Vin models: 27 mA typ. 24 Vin models: 16 mA typ. 48 Vin models: 10 mA typ. |
| Surge voltage (1 sec. max.) | 5 Vin models: 12 V max. 12 Vin models: 25 V max. 24 Vin models: 50 V max. 48 Vin models: 100 V max. |
| Start-up voltage | 5 Vin models: 4.5 VDC max. 12 Vin models: 9.0 VDC max. 24 Vin models: 18 VDC max. 48 Vin models: 36 VDC max. |
| Input filter | internal capacitor |
| Conducted noise | EN 55022 class A or B (with ext. components) |
| ESD (electrostatic discharge) | EN 61000-4-2, air ± 8 kV, contact ± 6 kV, perf. criteria A |
| Radiated immunity | EN 61000-4-3, 10 V/m, perf. criteria A |
| Fast transient / surge (with external input capacitor) | EN 61000-4-4, ± 2 kV, perf. criteria A EN 61000-4-5, ± 1 kV perf. criteria A all models: Nippon chemi-con KY 220 μ F/100V -external input capacitor |
| Conducted immunity | EN 61000-4-6, 10 Vrms, perf. criteria A |
| Magnetic field immunity | EN 61000-4-8, 3 A/m, perf. criteria A |

Output Specifications

| | |
|--------------------------------------|---|
| Voltage set accuracy | ± 1.5 % max. |
| Voltage balance (dual output models) | 2 % max. |
| Regulation | - Input variation: 0.2 % max. - Load variation 0 – 100 %: 1 % max. dual output: 2 % max. (balanced load) cross regulation - dual output: 5 % max. (asymmetrical load 25 % / 100 %) |
| Minimum load | no minimum load required |
| Ripple and noise (20 MHz Bandwidth) | 70 mVp-p typ. |
| Transient response | - Recovery time (25% load step change): 500 μ s max. - Response deviation (25% load step change): 5 % max. |
| Short circuit protection | continuous, automatic recovery |
| Over load protection | at 170% of lout nom. (foldback) |
| Capacitive load | -Single output: all models: 100 μ F max. -Dual output: all models: 100 μ F max. (each output) |



General Specifications

| | |
|--------------------------------------|---|
| Temperature ranges | - Operating (convection cooling 20LFM, 0,1m/s): -40°C to +70°C (without derating) - Case temperature: +95°C max. - Storage temperature: -50°C to +125°C |
| Derating | 4.0%/K above 70°C |
| Humidity (non condensing) | 95 % rel H max. |
| Isolation voltage | - I/O isolation voltage (60 sec.): 1'500 VDC |
| Isolation capacitance (input/output) | 100 pF typ. |
| Isolation resistance (input/output) | >1 Gohm |
| Altitude during operation | 5'000 m |
| Temperature coefficient | ± 0.02 %/K max. |

All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

-  [View TDL 3-0521 on WIN SOURCE](#)
-  [Traco Power Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management