



**THE DATASHEET OF
ILC0603ERR18J**





Surface Mount, Multi Layer High Frequency Ceramic Inductors



MECHANICAL SPECIFICATIONS

Solderability: 95 % coverage after 3 s ± 1 s dip in 240 °C ± 5 °C solder following 60 s preheat at 150 °C and type R flux dip

Resistance to Solder Heat: 6 s ± 1 s in 265 °C ± 3 °C solder after preheat and flux above

Terminal Strength: 1.02 kg for 10 s

Flex: 3.0 mm min. mounted on 0.8 mm thick PC board

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature: -55 °C to +125 °C (including self-temperature rise)

Thermal Shock: 1000 cycles, -55 °C ± 5 °C to +125 °C ± 5 °C

Humidity: 85 °C ± 2 °C, 85 % ± 5 % RH, 1000 h ± 12 h

Load Life: 125 °C ± 2 °C for 1000 h ± 12 h at full rated current

FEATURES

- High reliability
- Surface mountable
- Reflow or wave solderable
- Tape and reel packaging per EIA specifications: 4000 pieces on 7" reel
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912




RoHS COMPLIANT
HALOGEN FREE

STANDARD ELECTRICAL SPECIFICATIONS											
PART NUMBER	IND. (nH)	TOL.	TEST FREQUENCY (MHz)	Q MIN.	Q TYPICAL			SRF (MHz)		DCR MAX. (Ω)	RATED DC CURRENT MAX. (mA)
					100 MHz	500 MHz	1000 MHz	MIN.	TYP.		
ILC0603ER1N0S	1.0	0.3 nH	100	8	15	43	63	10 000	15 000	0.05	300
ILC0603ER1N2S	1.2	0.3 nH	100	8	14	38	55	10 000	14 000	0.05	300
ILC0603ER1N5S	1.5	0.3 nH	100	8	11	28	40	6000	13 000	0.10	300
ILC0603ER1N8S	1.8	0.3 nH	100	8	10	24	35	6000	11 000	0.10	300
ILC0603ER2N2S	2.2	0.3 nH	100	8	14	35	40	6000	10 000	0.10	300
ILC0603ER2N7S	2.7	0.3 nH	100	10	12	29	45	6000	7000	0.10	300
ILC0603ER3N3S	3.3	0.3 nH	100	10	16	40	47	4000	5900	0.12	300
ILC0603ER3N9S	3.9	0.3 nH	100	10	11	25	35	3500	4500	0.14	300
ILC0603ER4N7S	4.7	0.3 nH	100	10	11	26	35	3500	4500	0.16	300
ILC0603ER5N6S	5.6	0.3 nH	100	10	15	36	46	3500	4000	0.18	300
ILC0603ER6N8J	6.8	5 %	100	10	15	38	47	3000	3600	0.22	300
ILC0603ER8N2J	8.2	5 %	100	10	13	31	41	3000	3500	0.24	300
ILC0603ER10NJ	10	5 %	100	12	15	34	47	2800	3000	0.26	300
ILC0603ER12NJ	12	5 %	100	12	12	27	49	2000	2500	0.28	300
ILC0603ER15NJ	15	5 %	100	12	15	30	36	2000	2200	0.32	300
ILC0603ER18NJ	18	5 %	100	12	15	28	31	1800	2000	0.35	300
ILC0603ER22NJ	22	5 %	100	12	17	34	36	1800	1900	0.40	300
ILC0603ER27NJ	27	5 %	100	12	15	31	30	1500	1700	0.45	300
ILC0603ER33NJ	33	5 %	100	12	15	28	24	1200	1500	0.55	300
ILC0603ER39NJ	39	5 %	100	12	14	31	28	1100	1300	0.60	300
ILC0603ER47NJ	47	5 %	100	12	17	31	28	900	1300	0.70	300
ILC0603ER56NJ	56	5 %	100	12	19	34	26	900	1200	0.75	300
ILC0603ER68NJ	68	5 %	100	12	17	30	20	700	1000	0.85	300
ILC0603ER82NJ	82	5 %	100	12	16	29	18	600	1000	0.95	300
ILC0603ERR10J	100	5 %	100	12	16	24	3	600	800	1.00	300
ILC0603ERR12J	120	5 %	100	8	17	21	-	500	800	1.20	300
ILC0603ERR15J	150	5 %	100	8	19	20	-	500	700	1.20	300
ILC0603ERR18J	180	5 %	100	8	18	13	-	400	600	1.30	300
ILC0603ERR22J	220	5 %	100	8	18	-	-	400	500	1.50	300
ILC0603ERR27J	270	5 %	100	8	19	-	-	350	490	1.90	300



DIMENSIONS in inches [millimeters]



DESCRIPTION

ILC-0603	10 nH	± 5 %	ER	e3
MODEL	INDUCTANCE VALUE	INDUCTANCE TOLERANCE	PACKAGE CODE	JEDEC® LEAD (Pb)-FREE STANDARD

GLOBAL PART NUMBER

I	L	C
---	---	---

PRODUCT FAMILY

0	6	0	3
---	---	---	---

SIZE

E	R
---	---

PACKAGE CODE

1	0	N
---	---	---

INDUCTANCE VALUE

J

TOL.



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View ILC0603ERR18J on WIN SOURCE](#)

 [Vishay Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management