




THE DATASHEET OF PIC32-HMZ144





PIC32-HMZ144

PIC32MZ2048 is a one of the most capable PIC32 processors ever designed by Microchip Technology Inc. The processor core reaches up to 200 MHz (up to 330 DMIPS). PIC32MZ2048 has a lot of interfaces: 48-channel ADC module; MMU for real time OS support; UART; I2C; PMP; EBI; SQI & analog comparators; SPI/I2S interfaces for audio processing and playback, Hi-Speed USB 2.0 device/host/OTG; 10/100 Mbps Ethernet MAC with MII and RMII interfaces; etc. The processor has a lot of GPIO ports. The latest revision of PIC32-HMZ144 comes with PIC32MZ2048EFG144 that also has a FPU and faster ADC (compared to PIC32MZ2048ECG).

FEATURES

- PIC32MZ2048EFG144 (512KB SRAM; 2MB flash) shipping after 27.10.2017 (older board revisions used PIC32MZ2048ECG144)
- USB-OTG interface with mini USB connector
- MicroSD card connector
- ICSP for debugging and programming
- JTAG pins exposed on 0.1" step 6 pins
- EXT1 and EXT2 50 pin 0.1" connectors that ease the access to the processor
- RESET and USER buttons
- PWR and STATUS LEDs
- Li-Po battery charger and connector
- UEXT connector
- Dimensions: (77 x 52)mm ~ (3 x 2)inch

<https://www.olimex.com/Products/PIC/Development/PIC32-HMZ144/open-source-hardware> 8-29-18

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View PIC32-HMZ144 on WIN SOURCE](#)

 [Olimex LTD Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management