









THE DATASHEET OF ZX20-B-SLDC



Jun.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD		USB2.0 SPECIFICATION AND MICRO-USB CABLES AND CONNECTORS SPECIFICATION 					
RATING	OPERATING TEMPERATURE RANGE	-30 °C TO +85° C 	STORAGE TEMPERATURE RANGE	-30 °C TO +85 °C 			
	VOLTAGE	-	OPERATING HUMIDITY RANGE	- % TO - %			
	CURRENT	-	APPLICABLE CABLE	-			
SPECIFICATIONS							
ITEM		TEST METHOD		REQUIREMENTS		QT	AT
CONSTRUCTION							
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.		X	X
MARKING		CONFIRMED VISUALLY.				X	X
	COUNT	DESCRIPTION OF REVISIONS		DESIGNED	CHECKED	DATE	
	3	DIS-E-001673		TS. SAKAI ZAWA	KN. ICHIKAWA	07. 07. 24	
REMARK					APPROVED	AO. SUZUKI	07. 03. 06
					CHECKED	HK. TANAKA	07. 03. 06
					DESIGNED	TS. SAKAI ZAWA	07. 03. 06
					DRAWN	TS. SAKAI ZAWA	07. 03. 06
Note QT:Qualification Test AT:Assurance Test X:Applicable Test				DRAWING NO.		ELC4-126148-00	
	SPECIFICATION SHEET			PART NO.	ZX20-B-SLDC		
	HIROSE ELECTRIC CO., LTD.			CODE NO.	CL242-0022-1-00		1/1

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

-  [View ZX20-B-SLDC on WIN SOURCE](#)
-  [Hirose Electric Co Ltd Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management