



**THE DATASHEET OF
DF50A-16S-1C**



Applicable standard								
Rating	Operating temperature range	-35°C to + 85°C (Note 1)			Storage temperature range	-10°C to + 60°C (Note 3)		
	Operating humidity range	20 % to 80 % (Note 2)			Storage humidity range	40 % to 70 % (Note 3)		
	Voltage	AC/DC 100V			Applicable connector	DF50A-*P-1V(##) DF50A-*P-1H(##)		
	Current △1	Contact	2	3to16		Applicable Contact △1	DF50-26SCFA(##)	
AWG26		2.0A	1.0A		DF50-2830SCFA(##)			
AWG28		2.0A	1.0A		DF50K-2830SCFA(##)			
AWG30		0.9A		DF50-3032SCFA(##)				
AWG32	0.7A							
Specifications								
Item		Test method			Requirements		QT	AT
Construction								
General examination		Visually and by measuring instrument.			According to drawing.		X	X
Marking		Confirmed visually.					X	X
Electric characteristics								
Insulation resistance		100V DC.			500MΩ MIN.		X	-
Voltage proof		300V AC for 1 min.			No flashover or breakdown.		X	-
Mechanical characteristics								
Mechanical operation		30times insertions and extractions.			No damage, crack or looseness of parts.		X	-
Vibration		Frequency 10 to 55 Hz, single amplitude 0.75 mm, at 10 cycles for each, for 3 directions.					X	-
Shock		490 m/s ² duration of pulse 11 ms At 3 times for 3 directions.					X	-
Environmental characteristics								
Damp heat (Steady state)		Exposed at 40 ± 2 °c, 90 to 95 %, 96 h.			① Insulation resistance: 100MΩ MIN. ② No damage, crack or looseness of parts.		X	-
Rapid change of temperature		Temperature -55→+85°C Time 30→ 30min. Under 5 cycles. (The transferring time of the tank is 2 to 3 min)			① Insulation resistance: 500MΩ MIN. ② No damage, crack or looseness of parts.		X	-
Remarks Note 1: Include the temperature rising by current. Note 2: No condensing. Note 3: Apply to the condition of long term storage for unused products before harness assembly. After harness assembly, operating temperature and humidity range is applied for interim storage during transportation.								
△	Count	Description of revisions			Designed	Checked	Date	
	3	DIS-H-00005434			HT. SATO	SZ. ONO	20191028	
Unless otherwise specified, refer to IEC 60512.						Approved	KI. AKIYAMA	20100706
						Checked	OM. MIYAMOTO	20100706
						Designed	TT. OHSAKO	2010070520100706
						Drawn	TT. OHSAKO	20100705
Note QT:Qualification Test AT:Assurance Test X:Applicable Test					Drawing no.		ELC-332936-00-00	
HRS	Specification sheet				Part no.	DF50A-*S-1C		
	Hirose electric co., ltd.				Code no.	CL665-	△	1/1

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

- [View DF50A-16S-1C on WIN SOURCE](#)
- [Hirose Electric Co Ltd Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

- ✓ Global Sourcing Solution
- ✓ Obsolete Management
- ✓ Cost Control Management
- ✓ Shortage Management
- ✓ Alternative Solution
- ✓ Excess Inventory Management