








**THE DATASHEET OF  
PA4332.102NLT**



# SMT Power Inductor

Shielded Drum Core - PA4332.XXXNLT Series



-  **Height:** 2.0mm Max
-  **Footprint:** 4.2mm x 4.2mm Max
-  **Current Rating:** up to 5.8A
-  **Inductance Range:** 1.0uH to 10.0uH
-  **Shielded magnetic circuit reduces leakage flux, Fe base metal core enables high saturation and metalized core termination results in excellent shock resistance.**

### Electrical Specifications @ 25°C - Operating Temperature -40°C to +125°C


| Part Number   | Inductance<br>1MHz, 1V<br>uH ±20% | Rated Current<br>A | Min. Self-Resonant Frequency<br>MHz | DC Resistance |      | Saturation Current (20°C)<br>A | Heating Current |
|---------------|-----------------------------------|--------------------|-------------------------------------|---------------|------|--------------------------------|-----------------|
|               |                                   |                    |                                     | MAX.          | TYP. |                                | ΔT ≈ 40°C       |
|               |                                   |                    |                                     | mΩ            | mΩ   |                                | A               |
| PA4332.102NLT | 1.0                               | 5.80               | 37                                  | 26            | 22   | 8.50                           | 5.80            |
| PA4332.152NLT | 1.5                               | 5.20               | 30                                  | 36            | 30   | 7.70                           | 5.20            |
| PA4332.222NLT | 2.2                               | 4.30               | 25                                  | 48            | 40   | 6.10                           | 4.30            |
| PA4332.332NLT | 3.3                               | 3.45               | 19                                  | 72            | 60   | 4.70                           | 3.45            |
| PA4332.472NLT | 4.7                               | 2.85               | 17                                  | 108           | 90   | 4.00                           | 2.85            |
| PA4332.682NLT | 6.8                               | 2.40               | 13                                  | 156           | 130  | 3.00                           | 2.40            |
| PA4332.103NLT | 10.0                              | 2.00               | 11                                  | 216           | 180  | 2.80                           | 2.00            |

#### Notes:

- Actual temperature of the component during system operation (ambient plus temperature rise) must be within the standard operating range.
- The rated current as listed is either the saturation current (@ 20°C) or the heating current (ΔT ≈ 40°C) depending on which value is lower.
- The saturation current is the current at which the initial inductance drops approximately 30% at the stated ambient temperature. This current is determined by placing the component in the specified ambient environment and applying a short duration pulse current (to eliminate self-heating effect) to the component.
- The heating current is the DC current required to raise the component temperature by approximately 40°C. Take note that the components' performance varies depending on the system condition. It is suggested that the component be tested at the system level, to verify the temperature rise of the component during system operation.
- Maximum voltage across terminals to be limited to <40Vdc

Mechanical


PA4332.XXXNLT



| Series        | A       | B       | C     | D     | E     | F     | G     | H     |
|---------------|---------|---------|-------|-------|-------|-------|-------|-------|
| PA4332.XXXNLT | 4.2 MAX | 2.0 MAX | (3.1) | (4.0) | (2.1) | (3.7) | (1.1) | (1.9) |

All Dimensions in mm.


TAPE & REEL INFO




|               | SURFACE MOUNTING TYPE, REEL/TAPE LIST |      |      |     |                |     |                |                |                |                |    |      |                | QTY<br>PCS/REEL |
|---------------|---------------------------------------|------|------|-----|----------------|-----|----------------|----------------|----------------|----------------|----|------|----------------|-----------------|
|               | REEL SIZE (mm)                        |      |      |     | TAPE SIZE (mm) |     |                |                |                |                |    |      |                |                 |
|               | A                                     | B    | G    | N   | E              | F   | D <sub>0</sub> | P <sub>1</sub> | P <sub>0</sub> | P <sub>2</sub> | W  | T    | K <sub>0</sub> |                 |
| PA4332.XXXNLT | Ø330                                  | 18.4 | 12.4 | 100 | 1.75           | 5.5 | 1.5            | 8              | 4              | 2              | 12 | 0.40 | 2.4            | 3000            |

TAPE & REEL INFO


PA4332.102NLT




PA4332.152NLT




PA4332.222NLT




PA4332.332NLT



PA4332.472NLT




PA4332.682NLT



# SMT Power Inductor

Shielded Drum Core - PA4332.XXXNLT Series



## For More Information:

Americas - [prodinfo\\_power\\_americas@yageo.com](mailto:prodinfo_power_americas@yageo.com) | Europe - [prodinfo\\_power\\_emea@yageo.com](mailto:prodinfo_power_emea@yageo.com) | Asia - [prodinfo\\_power\\_asia@yageo.com](mailto:prodinfo_power_asia@yageo.com)

Performance warranty of products offered on this data sheet is limited to the parameters specified. Data is subject to change without notice. Other brand and product names mentioned herein may be trademarks or registered trademarks of their respective owners. © Copyright, 2023. Pulse Electronics, Inc. All rights reserved.

YAGEO Corporation and its affiliates do not recommend the use of commercial or automotive grade products for high reliability applications or manned space flight.

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View PA4332.102NLT on WIN SOURCE](#)

 [Pulse Information](#)

## Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management