



**THE DATASHEET OF  
RDER71H102K0P1H03B**



## Reference Specification

Leaded MLCC for Consumer Electronics & Industrial Equipment  
RDE Series

Product specifications in this catalog are as of Apr. 2024, and are subject to change or obsolescence without notice.  
Please consult the approval sheet before ordering. Please read rating and Cautions first.

<Reference> Please kindly use our website.

Please refer to the product information page for more information on ceramic capacitors. → [Ceramic capacitor product information](#)

Various data can be obtained directly from the product search. → [Product search \(SMD\)](#) / [Product search \(Lead Type\)](#)

**⚠ CAUTION****1. OPERATING VOLTAGE**





Do not apply a voltage to the capacitor that exceeds the rated voltage as called out in the specifications.

1-1. Applied voltage between the terminals of a capacitor shall be less than or equal to the rated voltage.

(1) When AC voltage is superimposed on DC voltage, the zero-to-peak voltage shall not exceed the rated DC voltage. When AC voltage or pulse voltage is applied, the peak-to-peak voltage shall not exceed the rated DC voltage.

(2) Abnormal voltages (surge voltage, static electricity, pulse voltage, etc.) shall not exceed the rated DC voltage.

Typical Voltage Applied to the DC Capacitor

| DC Voltage  | DC+AC Voltage   | AC Voltage  | Pulse Voltage  |
|---|---|---|--|
|  |  |  |  |

(E: Maximum possible applied voltage.)

1-2. Influence of over voltage

Over voltage that is applied to the capacitor may result in an electrical short circuit caused by the breakdown of the internal dielectric layers. The time duration until breakdown depends on the applied voltage and the ambient temperature.

Use a safety standard certified capacitor in a power supply input circuit (AC filter), as it is also necessary to consider the withstand voltage and impulse withstand voltage defined for each device.

**2. OPERATING TEMPERATURE AND SELF-GENERATED HEAT**

Keep the surface temperature of a capacitor below the upper limit of its rated operating temperature range. Be sure to take into account the heat generated by the capacitor itself.

When the capacitor is used in a high-frequency current, pulse current or the like, it may have the self-generated heat due to dielectric-loss. In case of Class 2 capacitors (Temp.Char. : X7R,X7S,X8L, etc.), applied voltage should be the load such as self-generated heat is within 20 °C on the condition of atmosphere temperature 25 °C.

Since the self-heating is low in the Class 1 capacitors (Temp.Char.: C0G,U2J,X8G, etc.), the allowable power becomes extremely high compared to the Class 2 capacitors.

However, when a load with self-heating of 20°C is applied at the rated voltage, the allowable power may be exceeded. Please confirm that there is no rising trend of the capacitor's surface temperature and that the surface temperature of the capacitor does not exceed the maximum operating temperature.

Excessive generation of heat may cause deterioration of the characteristics and reliability of the capacitor.

When measuring the self-heating temperature, be aware that accurate measurement may not be possible due to the following effects.

- The heat generated by other parts
- Air flow such as convection and cooling fans
- Temperature sensor used for measuring surface temperature of capacitor

In the case using a thermocouple, it is recommended that use a K thermocouple of  $\Phi 0.1\text{mm}$  with less heat capacity.

**3. FAIL-SAFE**

Capacitors that are cracked by dropping or bending of the board may cause deterioration of the insulation resistance, and result in a short.

If the circuit being used may cause an electrical shock, smoke or fire when a capacitor is shorted, be sure to install fail-safe functions, such as a fuse, to prevent secondary accidents.

#### 4. OPERATING AND STORAGE ENVIRONMENT

The insulating coating of capacitors does not form a perfect seal; therefore, do not use or store capacitors in a corrosive atmosphere, especially where chloride gas, sulfide gas, acid, alkali, salt or the like are present. And avoid exposure to moisture. Before cleaning, bonding, or molding this product, verify that these processes do not affect product quality by testing the performance of a cleaned, bonded or molded product in the intended equipment. Store the capacitors where the temperature and relative humidity do not exceed 5 to 40 °C and 20 to 70%. Use capacitors within 6 months.

Use capacitors within 6 months after delivered. Check the solderability after 6 months or more.

Due to moisture condensation caused by rapid humidity changes, or the photochemical change caused by direct sunlight on the terminal electrodes, the solderability and electrical performance may deteriorate. Do not store capacitors under direct sunlight or in high humidity conditions.

#### 5. VIBRATION AND IMPACT

Do not expose a capacitor or its leads to excessive shock or vibration during use.

5-1. Mechanical shock due to being dropped may cause damage or a crack in the dielectric material of the capacitor.

Do not use a dropped capacitor because the quality and reliability may be deteriorated.

5-2. Excessive shock or vibration may cause to fatigue destruction of lead wires mounted on the circuit board. If necessary, take measures to hold a capacitor on the circuit boards by adhesive, molding resin or coating and other.

Please confirm there is no influence of holding measures on the product with an intended equipment.

#### 6. SOLDERING

When soldering this product to a PCB/PWB, do not exceed the solder heat resistance specification of the capacitor. Subjecting this product to excessive heating could melt the internal junction solder and may result in thermal shocks that can crack the ceramic element.

Please verify that the soldering process does not affect the quality of capacitors.

##### 6-1. Flow Soldering

|                        |               |
|------------------------|---------------|
| Soldering temperature  | : 260 °C max. |
| Soldering time         | : 7.5 s max.  |
| Preheating temperature | : 120 °C max. |
| Preheating time        | : 60 s max.   |



##### 6-2. Reflow Soldering

Do not apply reflow soldering.

##### 6-3. Soldering Iron

|                         |               |
|-------------------------|---------------|
| Temperature of iron-tip | : 350 °C max. |
| Soldering iron wattage  | : 60 W max.   |
| Soldering time          | : 3.5 s max.  |

## 7. BONDING AND RESIN MOLDING, RESIN COAT

In case of bonding, molding or coating this product, verify that these processes do not affect the quality of capacitor by testing the performance of a bonded or molded product in the intended equipment.

In case of the amount of applications, dryness / hardening conditions of adhesives and molding resins containing organic solvents (ethyl acetate, methyl ethyl ketone, toluene, etc.) are unsuitable, the outer coating resin of a capacitor is damaged by the organic solvents and it may result, worst case, in a short circuit.

The variation in thickness of adhesive or molding resin may cause a outer coating resin cracking and/or ceramic element cracking of a capacitor in a temperature cycling.

## 8. TREATMENT AFTER BONDING AND RESIN MOLDING, RESIN COAT

When the outer coating is hot (over 100 °C) after soldering, it becomes soft and fragile.

So please be careful not to give it mechanical stress.

Failure to follow the above cautions may result, worst case, in a short circuit and cause fuming or partial dispersion when the product is used.

## 9. LIMITATION OF APPLICATIONS

The products listed in the specification(hereinafter the product(s) is called as the "Product(s)") are designed and manufactured for applications specified in the specification. (hereinafter called as the "Specific Application")

We shall not warrant anything in connection with the Products including fitness, performance, adequateness, safety, or quality, in the case of applications listed in from (1) to (11) written at the end of this precautions, which may generally require high performance, function, quality, management of production or safety.

Therefore, the Product shall be applied in compliance with the specific application.

WE DISCLAIM ANY LOSS AND DAMAGES ARISING FROM OR IN CONNECTION WITH THE PRODUCTS INCLUDING BUT NOT LIMITED TO THE CASE SUCH LOSS AND DAMAGES CAUSED BY THE UNEXPECTED ACCIDENT, IN EVENT THAT (i) THE PRODUCT IS APPLIED FOR THE PURPOSE WHICH IS NOT SPECIFIED AS THE SPECIFIC APPLICATION FOR THE PRODUCT, AND/OR (ii) THE PRODUCT IS APPLIED FOR ANY FOLLOWING APPLICATION PURPOSES FROM (1) TO (11) (EXCEPT THAT SUCH APPLICATION PURPOSE IS UNAMBIGUOUSLY SPECIFIED AS SPECIFIC APPLICATION FOR THE PRODUCT IN OUR CATALOG SPECIFICATION FORMS, DATASHEETS, OR OTHER DOCUMENTS OFFICIALLY ISSUED BY US\*)

1. Aircraft equipment
2. Aerospace equipment
3. Undersea equipment
4. Power plant control equipment
5. Medical equipment
6. Transportation equipment
7. Traffic control equipment
8. Disaster prevention/security equipment
9. Industrial data-processing equipment
10. Combustion/explosion control equipment
11. Equipment with complexity and/or required reliability equivalent to the applications listed in the above.

For exploring information of the Products which will be compatible with the particular purpose other than those specified in the specification, please contact our sales offices, distribution agents, or trading companies with which you make a deal, or via our web contact form.

Contact form: <https://www.murata.com/contactform>

\*We may design and manufacture particular Products for applications listed in (1) to (11). Provided that, in such case we shall unambiguously specify such Specific Application in the specification without any exception.

Therefore, any other documents and/or performances, whether exist or non-exist, shall not be deemed as the evidence to imply that we accept the applications listed in (1) to (11).

**NOTICE****1. CLEANING**

- 1-1. Please evaluate the capacitor using actual cleaning equipment and conditions to confirm the quality, and select the solvent for cleaning.
- 1-2. Unsuitable cleaning may leave residual flux or other foreign substances, causing deterioration of electrical characteristics and the reliability of the capacitors.
- 1-3. To perform ultrasonic cleaning, observe the following conditions.
  - Rinse bath capacity : Output of 20 watts per liter or less.
  - Rinsing time : 5 min maximum.
  - Do not vibrate the PCB/PWB directly.
  - Excessive ultrasonic cleaning may lead to fatigue destruction of the lead wires.

**2. SOLDERING AND MOUNTING**

- 2-1. Insert the lead wire into the PCB with a distance appropriate to the lead space.  
If the lead wires are inserted into different spacing holes, cracks may occur in the outer resin or the internal element.
- 2-2. When bending the lead wire, excessive force applied to the capacitor body may cause cracks in the outer resin or the internal element. Hold the lead wire closer to the capacitor body than the lead wire bending position with the fixture, then bend it.

(See the right figure)



- 2-3. When cutting and clinching the lead wire, do not apply excessive force to the capacitor body.
- 2-4. When soldering, insert the lead wire into the PCB without mechanically stressing the lead wire.

**3. CAPACITANCE CHANGE OF CAPACITORS**

- Class 2 capacitors (Temp.Char. : X7R,X7S,X8L etc.)  
Class 2 capacitors an aging characteristic, whereby the capacitor continually decreases its capacitance slightly if the capacitor leaves for a long time. Moreover, capacitance might change greatly depending on a surrounding temperature or an applied voltage. So, it is not likely to be able to use for the time constant circuit.  
Please contact us if you need a detail information.

**4. CHARACTERISTICS EVALUATION IN THE ACTUAL SYSTEM**

- 4-1. Evaluate the capacitor in the actual system, to confirm that there is no problem with the performance and specification values in a finished product before using.
- 4-2. Since a voltage dependency and temperature dependency exists in the capacitance of Class 2 ceramic capacitors, the capacitance may change depending on the operating conditions in the actual system. Therefore, be sure to evaluate the various characteristics, such as the leakage current and noise absorptivity, which will affect the capacitance value of the capacitor.
- 4-3. In addition, voltages exceeding the predetermined surge may be applied to the capacitor by the inductance in the actual system.  
Evaluate the surge resistance in the actual system as required.
- 4-4. When using Class 2 ceramic capacitors in AC or pulse circuits, the capacitor itself vibrates at specific frequencies and noise may be generated. Moreover, when the mechanical vibration or shock is added to capacitor, noise may occur.

**⚠ NOTE**

1. Please make sure that your product has been evaluated in view of your specifications with our product being mounted to your product.
2. You are requested not to use our product deviating from this product specification.

1. Application

This product specification is applied to Leaded MLCC RDE series.

1. Specific applications:

- Consumer Equipment: Products that can be used in consumer equipment such as home appliances, audio/visual equipment, communication equipment, information equipment, office equipment, and household robotics, and whose functions are not directly related to the protection of human life and property.
- Industrial Equipment: Products that can be used in industrial equipment such as base stations, manufacturing equipment, industrial robotics equipment, and measurement equipment, and whose functions do not directly relate to the protection of human life and property.
- Medial Equipment [GHTF A/B/C] except for Implant Equipment: Products suitable for use in medical devices designated under the GHTF international classifications as Class A or Class B (the functions of which are not directly involved in protection of human life or property) or in medical devices other than implants designated under the GHTF international classifications as Class C (the malfunctioning of which is considered to pose a comparatively high risk to the human body).
- Automotive infotainment/comfort equipment: Products that can be used for automotive equipment such as car navigation systems and car audio systems that do not directly relate to human life and whose structure, equipment, and performance are not specifically required by law to meet technical standards for safety assurance or environmental protection.

2. Unsuitable Application: Applications listed in "Limitation of applications" in this product specification.

2. Rating

• Part Number Configuration

ex.)

|            |                             |               |             |                       |                 |            |                          |          |
|------------|-----------------------------|---------------|-------------|-----------------------|-----------------|------------|--------------------------|----------|
| <u>RDE</u> | <u>R7</u>                   | <u>2E</u>     | <u>225</u>  | <u>M</u>              | <u>U</u>        | <u>B1</u>  | <u>H03</u>               | <u>B</u> |
| Series     | Temperature Characteristics | Rated Voltage | Capacitance | Capacitance Tolerance | Dimension (LxW) | Lead Style | Individual Specification | Package  |

• Temperature Characteristics

| Code | Temp. Char.       | Temp. Range | Cap. Change | Standard Temp. | Operating Temp. Range |
|------|-------------------|-------------|-------------|----------------|-----------------------|
| R7   | X7R<br>(EIA code) | -55~125°C   | +/-15%      | 25°C           | -55~125°C             |

• Rated Voltage

| Code | Rated voltage |
|------|---------------|
| 2E   | DC250V        |
| 2H   | DC500V        |
| 2J   | DC630V        |
| 3A   | DC1000V       |

• Capacitance

The first two digits denote significant figures ; the last digit denotes the multiplier of 10 in pF.

ex.) In case of 225 .

$$22 \times 10^5 = 2200000 \text{ pF}$$

Reference only

- Capacitance Tolerance

| Code | Capacitance Tolerance |
|------|-----------------------|
| K    | +/-10%                |
| M    | +/-20%                |

- Dimension (LxW)

Please refer to [ Part number list ].

- Lead Style

\*Lead wire is "solder coated CP wire".

| Code | Lead Style               | Lead spacing (mm) |
|------|--------------------------|-------------------|
| B1   | Straight type            | 5.0+/-0.8         |
| E1   | Straight taping type     | 5.0+0.6/-0.2      |
| K1   | Inside crimp type        | 5.0+/-0.8         |
| M1   | Inside crimp taping type | 5.0+0.6/-0.2      |

- Individual Specification

Murata's control code.

Please refer to [ Part number list ].

- Package

| Code | Package             |
|------|---------------------|
| A    | Taping type of Ammo |
| B    | Bulk type           |

## 3. Marking

Temp. char. : Letter code : C (X7R Char. Except dimension code : 1)  
 Capacitance : 3 digit numbers  
 Capacitance tolerance : Code  
 Rated voltage : Letter code : 4 (DC250V. Except dimension code : 1)  
 Letter code : 9 (DC500V. Except dimension code : 1)  
 Letter code : 7 (DC630V)  
 Letter code : A (DC1000V)  
 Company name code : Abbreviation :  (Except dimension code : 1)

(Ex.)


| Rated voltage<br>Dimension code | DC250V  | DC500V  | DC630V  | DC1000V   |
|---------------------------------|---|---|---|---|
| 1                               |    |    | —   | —   |
| 2                               |   |   |   |   |
| 3,4                             |  |  |  |  |
| 5,U                             |  |  |  |  |

4. Part number list

- Inside Crimp  
(Lead Style : K\*)




- Straight Long  
(Lead Style : B1)




Unit : mm

| Customer Part Number | Murata Part Number | T.C. | DC Rated Volt. (V) | Cap.    | Cap. Tol. | Dimension (mm) |     |     |     |      | Dimension (LxW) Lead Style | Pack qty. (pcs) |
|----------------------|--------------------|------|--------------------|---------|-----------|----------------|-----|-----|-----|------|----------------------------|-----------------|
|                      |                    |      |                    |         |           | L              | W   | W1  | F   | T    |                            |                 |
|                      | RDER72E102K1K1H03B | X7R  | 250                | 1000pF  | ±10%      | 4.5            | 3.5 | 5.0 | 5.0 | 3.15 | 1K1                        | 500             |
|                      | RDER72E152K1K1H03B | X7R  | 250                | 1500pF  | ±10%      | 4.5            | 3.5 | 5.0 | 5.0 | 3.15 | 1K1                        | 500             |
|                      | RDER72E222K1K1H03B | X7R  | 250                | 2200pF  | ±10%      | 4.5            | 3.5 | 5.0 | 5.0 | 3.15 | 1K1                        | 500             |
|                      | RDER72E332K1K1H03B | X7R  | 250                | 3300pF  | ±10%      | 4.5            | 3.5 | 5.0 | 5.0 | 3.15 | 1K1                        | 500             |
|                      | RDER72E472K1K1H03B | X7R  | 250                | 4700pF  | ±10%      | 4.5            | 3.5 | 5.0 | 5.0 | 3.15 | 1K1                        | 500             |
|                      | RDER72E682K1K1H03B | X7R  | 250                | 6800pF  | ±10%      | 4.5            | 3.5 | 5.0 | 5.0 | 3.15 | 1K1                        | 500             |
|                      | RDER72E103K1K1H03B | X7R  | 250                | 10000pF | ±10%      | 4.5            | 3.5 | 5.0 | 5.0 | 3.15 | 1K1                        | 500             |
|                      | RDER72E153K1K1H03B | X7R  | 250                | 15000pF | ±10%      | 4.5            | 3.5 | 5.0 | 5.0 | 3.15 | 1K1                        | 500             |
|                      | RDER72E223K1K1H03B | X7R  | 250                | 22000pF | ±10%      | 4.5            | 3.5 | 5.0 | 5.0 | 3.15 | 1K1                        | 500             |
|                      | RDER72E333K2K1H03B | X7R  | 250                | 33000pF | ±10%      | 5.5            | 4.0 | 6.0 | 5.0 | 3.15 | 2K1                        | 500             |
|                      | RDER72E473K2K1H03B | X7R  | 250                | 47000pF | ±10%      | 5.5            | 4.0 | 6.0 | 5.0 | 3.15 | 2K1                        | 500             |
|                      | RDER72E683K2K1H03B | X7R  | 250                | 68000pF | ±10%      | 5.5            | 4.0 | 6.0 | 5.0 | 3.15 | 2K1                        | 500             |
|                      | RDER72E104K2K1H03B | X7R  | 250                | 0.1μF   | ±10%      | 5.5            | 4.0 | 6.0 | 5.0 | 3.15 | 2K1                        | 500             |
|                      | RDER72E154K3K1H03B | X7R  | 250                | 0.15μF  | ±10%      | 5.5            | 5.0 | 7.5 | 5.0 | 4.0  | 3K1                        | 500             |
|                      | RDER72E224K3K1H03B | X7R  | 250                | 0.22μF  | ±10%      | 5.5            | 5.0 | 7.5 | 5.0 | 4.0  | 3K1                        | 500             |
|                      | RDER72E334K4K1H03B | X7R  | 250                | 0.33μF  | ±10%      | 7.5            | 5.5 | 8.0 | 5.0 | 4.0  | 4K1                        | 500             |
|                      | RDER72E474K4K1H03B | X7R  | 250                | 0.47μF  | ±10%      | 7.5            | 5.5 | 8.0 | 5.0 | 4.0  | 4K1                        | 500             |
|                      | RDER72E684K5B1H03B | X7R  | 250                | 0.68μF  | ±10%      | 7.5            | 7.5 | -   | 5.0 | 4.0  | 5B1                        | 500             |
|                      | RDER72E105K5B1H03B | X7R  | 250                | 1.0μF   | ±10%      | 7.5            | 7.5 | -   | 5.0 | 4.0  | 5B1                        | 500             |

- Straight Long  
(Dimension(LxW) Lead Style:UB1)



- Inside Crimp  
(Lead Style:K\*)



Unit : mm

| Customer Part Number | Murata Part Number | T.C. | DC Rated Volt. (V) | Cap.    | Cap. Tol. | Dimension (mm) |      |     |     |      | Dimension (LxW) Lead Style | Pack qty. (pcs) |
|----------------------|--------------------|------|--------------------|---------|-----------|----------------|------|-----|-----|------|----------------------------|-----------------|
|                      |                    |      |                    |         |           | L              | W    | W1  | F   | T    |                            |                 |
|                      | RDER72E225MUB1H03B | X7R  | 250                | 2.2μF   | ±20%      | 7.7            | 12.5 | -   | 5.0 | 4.0  | UB1                        | 200             |
|                      | RDER72H102K1K1H03B | X7R  | 500                | 1000pF  | ±10%      | 4.5            | 3.5  | 5.0 | 5.0 | 3.15 | 1K1                        | 500             |
|                      | RDER72H152K1K1H03B | X7R  | 500                | 1500pF  | ±10%      | 4.5            | 3.5  | 5.0 | 5.0 | 3.15 | 1K1                        | 500             |
|                      | RDER72H222K1K1H03B | X7R  | 500                | 2200pF  | ±10%      | 4.5            | 3.5  | 5.0 | 5.0 | 3.15 | 1K1                        | 500             |
|                      | RDER72H332K1K1H03B | X7R  | 500                | 3300pF  | ±10%      | 4.5            | 3.5  | 5.0 | 5.0 | 3.15 | 1K1                        | 500             |
|                      | RDER72H472K1K1H03B | X7R  | 500                | 4700pF  | ±10%      | 4.5            | 3.5  | 5.0 | 5.0 | 3.15 | 1K1                        | 500             |
|                      | RDER72H682K1K1H03B | X7R  | 500                | 6800pF  | ±10%      | 4.5            | 3.5  | 5.0 | 5.0 | 3.15 | 1K1                        | 500             |
|                      | RDER72H103K1K1H03B | X7R  | 500                | 10000pF | ±10%      | 4.5            | 3.5  | 5.0 | 5.0 | 3.15 | 1K1                        | 500             |
|                      | RDER72H153K2K1H03B | X7R  | 500                | 15000pF | ±10%      | 5.5            | 4.0  | 6.0 | 5.0 | 3.15 | 2K1                        | 500             |
|                      | RDER72H223K2K1H03B | X7R  | 500                | 22000pF | ±10%      | 5.5            | 4.0  | 6.0 | 5.0 | 3.15 | 2K1                        | 500             |
|                      | RDER72H333K2K1H03B | X7R  | 500                | 33000pF | ±10%      | 5.5            | 4.0  | 6.0 | 5.0 | 3.15 | 2K1                        | 500             |
|                      | RDER72H473K2K1H03B | X7R  | 500                | 47000pF | ±10%      | 5.5            | 4.0  | 6.0 | 5.0 | 3.15 | 2K1                        | 500             |
|                      | RDER72H683K3K1H03B | X7R  | 500                | 68000pF | ±10%      | 5.5            | 5.0  | 7.5 | 5.0 | 4.0  | 3K1                        | 500             |
|                      | RDER72H104K3K1H03B | X7R  | 500                | 0.1μF   | ±10%      | 5.5            | 5.0  | 7.5 | 5.0 | 4.0  | 3K1                        | 500             |
|                      | RDER72H154K4K1H03B | X7R  | 500                | 0.15μF  | ±10%      | 7.5            | 5.5  | 8.0 | 5.0 | 4.0  | 4K1                        | 500             |
|                      | RDER72H224K4K1H03B | X7R  | 500                | 0.22μF  | ±10%      | 7.5            | 5.5  | 8.0 | 5.0 | 4.0  | 4K1                        | 500             |

• Straight Long  
(Lead Style : B1)



• Straight Long  
(Dimension(LxW) Lead Style:UB1)



Unit : mm

| Customer Part Number | Murata Part Number | T.C. | DC Rated Volt. (V) | Cap.         | Cap. Tol. | Dimension (mm) |      |    |     |     | Dimension (LxW) Lead Style | Pack qty. (pcs) |
|----------------------|--------------------|------|--------------------|--------------|-----------|----------------|------|----|-----|-----|----------------------------|-----------------|
|                      |                    |      |                    |              |           | L              | W    | W1 | F   | T   |                            |                 |
|                      | RDER72H334K5B1H03B | X7R  | 500                | 0.33 $\mu$ F | $\pm$ 10% | 7.5            | 7.5  | -  | 5.0 | 4.0 | 5B1                        | 500             |
|                      | RDER72H474K5B1H03B | X7R  | 500                | 0.47 $\mu$ F | $\pm$ 10% | 7.5            | 7.5  | -  | 5.0 | 4.0 | 5B1                        | 500             |
|                      | RDER72H684MUB1H03B | X7R  | 500                | 0.68 $\mu$ F | $\pm$ 20% | 7.7            | 12.5 | -  | 5.0 | 4.0 | UB1                        | 200             |
|                      | RDER72H105MUB1H03B | X7R  | 500                | 1.0 $\mu$ F  | $\pm$ 20% | 7.7            | 12.5 | -  | 5.0 | 4.0 | UB1                        | 200             |

- Inside Crimp  
(Lead Style: K\*)



- Straight Long  
(Lead Style: B1)




Unit : mm

| Customer Part Number | Murata Part Number | T.C. | DC Rated Volt. (V) | Cap.    | Cap. Tol. | Dimension (mm) |     |     |     |      | Dimension (LxW) Lead Style | Pack qty. (pcs) |
|----------------------|--------------------|------|--------------------|---------|-----------|----------------|-----|-----|-----|------|----------------------------|-----------------|
|                      |                    |      |                    |         |           | L              | W   | W1  | F   | T    |                            |                 |
|                      | RDER72J102K2K1H03B | X7R  | 630                | 1000pF  | ±10%      | 5.5            | 4.0 | 6.0 | 5.0 | 3.15 | 2K1                        | 500             |
|                      | RDER72J152K2K1H03B | X7R  | 630                | 1500pF  | ±10%      | 5.5            | 4.0 | 6.0 | 5.0 | 3.15 | 2K1                        | 500             |
|                      | RDER72J222K2K1H03B | X7R  | 630                | 2200pF  | ±10%      | 5.5            | 4.0 | 6.0 | 5.0 | 3.15 | 2K1                        | 500             |
|                      | RDER72J332K2K1H03B | X7R  | 630                | 3300pF  | ±10%      | 5.5            | 4.0 | 6.0 | 5.0 | 3.15 | 2K1                        | 500             |
|                      | RDER72J472K2K1H03B | X7R  | 630                | 4700pF  | ±10%      | 5.5            | 4.0 | 6.0 | 5.0 | 3.15 | 2K1                        | 500             |
|                      | RDER72J682K2K1H03B | X7R  | 630                | 6800pF  | ±10%      | 5.5            | 4.0 | 6.0 | 5.0 | 3.15 | 2K1                        | 500             |
|                      | RDER72J103K2K1H03B | X7R  | 630                | 10000pF | ±10%      | 5.5            | 4.0 | 6.0 | 5.0 | 3.15 | 2K1                        | 500             |
|                      | RDER72J153K2K1H03B | X7R  | 630                | 15000pF | ±10%      | 5.5            | 4.0 | 6.0 | 5.0 | 3.15 | 2K1                        | 500             |
|                      | RDER72J223K2K1H03B | X7R  | 630                | 22000pF | ±10%      | 5.5            | 4.0 | 6.0 | 5.0 | 3.15 | 2K1                        | 500             |
|                      | RDER72J333K3K1H03B | X7R  | 630                | 33000pF | ±10%      | 5.5            | 5.0 | 7.5 | 5.0 | 4.0  | 3K1                        | 500             |
|                      | RDER72J473K3K1H03B | X7R  | 630                | 47000pF | ±10%      | 5.5            | 5.0 | 7.5 | 5.0 | 4.0  | 3K1                        | 500             |
|                      | RDER72J683K4K1H03B | X7R  | 630                | 68000pF | ±10%      | 7.5            | 5.5 | 8.0 | 5.0 | 4.0  | 4K1                        | 500             |
|                      | RDER72J104K4K1H03B | X7R  | 630                | 0.1µF   | ±10%      | 7.5            | 5.5 | 8.0 | 5.0 | 4.0  | 4K1                        | 500             |
|                      | RDER72J154K5B1H03B | X7R  | 630                | 0.15µF  | ±10%      | 7.5            | 8.0 | -   | 5.0 | 4.0  | 5B1                        | 500             |
|                      | RDER72J224K5B1H03B | X7R  | 630                | 0.22µF  | ±10%      | 7.5            | 8.0 | -   | 5.0 | 4.0  | 5B1                        | 500             |

- Straight Long  
(Dimension(LxW) Lead Style:UB1)



- Inside Crimp  
(Lead Style:K\*)



Unit : mm

| Customer Part Number | Murata Part Number | T.C. | DC Rated Volt. (V) | Cap.    | Cap. Tol. | Dimension (mm) |      |     |     |      | Dimension (LxW) Lead Style | Pack qty. (pcs) |
|----------------------|--------------------|------|--------------------|---------|-----------|----------------|------|-----|-----|------|----------------------------|-----------------|
|                      |                    |      |                    |         |           | L              | W    | W1  | F   | T    |                            |                 |
|                      | RDER72J474MUB1H03B | X7R  | 630                | 0.47μF  | ±20%      | 7.7            | 13.0 | -   | 5.0 | 4.0  | UB1                        | 200             |
|                      | RDER73A471K2K1H03B | X7R  | 1000               | 470pF   | ±10%      | 5.5            | 4.0  | 6.0 | 5.0 | 3.15 | 2K1                        | 500             |
|                      | RDER73A681K2K1H03B | X7R  | 1000               | 680pF   | ±10%      | 5.5            | 4.0  | 6.0 | 5.0 | 3.15 | 2K1                        | 500             |
|                      | RDER73A102K2K1H03B | X7R  | 1000               | 1000pF  | ±10%      | 5.5            | 4.0  | 6.0 | 5.0 | 3.15 | 2K1                        | 500             |
|                      | RDER73A152K2K1H03B | X7R  | 1000               | 1500pF  | ±10%      | 5.5            | 4.0  | 6.0 | 5.0 | 3.15 | 2K1                        | 500             |
|                      | RDER73A222K2K1H03B | X7R  | 1000               | 2200pF  | ±10%      | 5.5            | 4.0  | 6.0 | 5.0 | 3.15 | 2K1                        | 500             |
|                      | RDER73A332K2K1H03B | X7R  | 1000               | 3300pF  | ±10%      | 5.5            | 4.0  | 6.0 | 5.0 | 3.15 | 2K1                        | 500             |
|                      | RDER73A472K2K1H03B | X7R  | 1000               | 4700pF  | ±10%      | 5.5            | 4.0  | 6.0 | 5.0 | 3.15 | 2K1                        | 500             |
|                      | RDER73A682K2K1H03B | X7R  | 1000               | 6800pF  | ±10%      | 5.5            | 4.0  | 6.0 | 5.0 | 3.15 | 2K1                        | 500             |
|                      | RDER73A103K2K1H03B | X7R  | 1000               | 10000pF | ±10%      | 5.5            | 4.0  | 6.0 | 5.0 | 3.15 | 2K1                        | 500             |
|                      | RDER73A153K3K1H03B | X7R  | 1000               | 15000pF | ±10%      | 5.5            | 5.0  | 7.5 | 5.0 | 4.0  | 3K1                        | 500             |
|                      | RDER73A223K3K1H03B | X7R  | 1000               | 22000pF | ±10%      | 5.5            | 5.0  | 7.5 | 5.0 | 4.0  | 3K1                        | 500             |
|                      | RDER73A333K4K1H03B | X7R  | 1000               | 33000pF | ±10%      | 7.5            | 5.5  | 8.0 | 5.0 | 4.0  | 4K1                        | 500             |
|                      | RDER73A473K4K1H03B | X7R  | 1000               | 47000pF | ±10%      | 7.5            | 5.5  | 8.0 | 5.0 | 4.0  | 4K1                        | 500             |

• Straight Long  
(Lead Style : B1)




• Straight Long  
(Dimension (LxW) Lead Style: UB1)




Unit : mm

| Customer Part Number | Murata Part Number | T.C. | DC Rated Volt. (V) | Cap.    | Cap. Tol. | Dimension (mm) |      |    |     |     | Dimension (LxW) Lead Style | Pack qty. (pcs) |
|----------------------|--------------------|------|--------------------|---------|-----------|----------------|------|----|-----|-----|----------------------------|-----------------|
|                      |                    |      |                    |         |           | L              | W    | W1 | F   | T   |                            |                 |
|                      | RDER73A683K5B1H03B | X7R  | 1000               | 68000pF | ±10%      | 7.5            | 8.0  | -  | 5.0 | 4.0 | 5B1                        | 500             |
|                      | RDER73A104K5B1H03B | X7R  | 1000               | 0.1μF   | ±10%      | 7.5            | 8.0  | -  | 5.0 | 4.0 | 5B1                        | 500             |
|                      | RDER73A224MUB1H03B | X7R  | 1000               | 0.22μF  | ±20%      | 7.7            | 13.0 | -  | 5.0 | 4.0 | UB1                        | 200             |

• Inside Crimp Taping  
(Lead Style: M\*)



• Straight Taping  
(Lead Style: E\*)




Unit : mm

| Customer Part Number | Murata Part Number | T.C. | DC Rated Volt. (V) | Cap.    | Cap. Tol. | Dimension (mm) |      |     |     |      |      | Dimension (LxW) Lead Style | Pack qty. (pcs) |
|----------------------|--------------------|------|--------------------|---------|-----------|----------------|------|-----|-----|------|------|----------------------------|-----------------|
|                      |                    |      |                    |         |           | L              | W    | W1  | F   | T    | H/H0 |                            |                 |
|                      | RDER72E102K1M1H03A | X7R  | 250                | 1000pF  | ±10%      | 4.5            | 3.5  | 5.0 | 5.0 | 3.15 | 16.0 | 1M1                        | 2000            |
|                      | RDER72E152K1M1H03A | X7R  | 250                | 1500pF  | ±10%      | 4.5            | 3.5  | 5.0 | 5.0 | 3.15 | 16.0 | 1M1                        | 2000            |
|                      | RDER72E222K1M1H03A | X7R  | 250                | 2200pF  | ±10%      | 4.5            | 3.5  | 5.0 | 5.0 | 3.15 | 16.0 | 1M1                        | 2000            |
|                      | RDER72E332K1M1H03A | X7R  | 250                | 3300pF  | ±10%      | 4.5            | 3.5  | 5.0 | 5.0 | 3.15 | 16.0 | 1M1                        | 2000            |
|                      | RDER72E472K1M1H03A | X7R  | 250                | 4700pF  | ±10%      | 4.5            | 3.5  | 5.0 | 5.0 | 3.15 | 16.0 | 1M1                        | 2000            |
|                      | RDER72E682K1M1H03A | X7R  | 250                | 6800pF  | ±10%      | 4.5            | 3.5  | 5.0 | 5.0 | 3.15 | 16.0 | 1M1                        | 2000            |
|                      | RDER72E103K1M1H03A | X7R  | 250                | 10000pF | ±10%      | 4.5            | 3.5  | 5.0 | 5.0 | 3.15 | 16.0 | 1M1                        | 2000            |
|                      | RDER72E153K1M1H03A | X7R  | 250                | 15000pF | ±10%      | 4.5            | 3.5  | 5.0 | 5.0 | 3.15 | 16.0 | 1M1                        | 2000            |
|                      | RDER72E223K1M1H03A | X7R  | 250                | 22000pF | ±10%      | 4.5            | 3.5  | 5.0 | 5.0 | 3.15 | 16.0 | 1M1                        | 2000            |
|                      | RDER72E333K2M1H03A | X7R  | 250                | 33000pF | ±10%      | 5.5            | 4.0  | 6.0 | 5.0 | 3.15 | 16.0 | 2M1                        | 2000            |
|                      | RDER72E473K2M1H03A | X7R  | 250                | 47000pF | ±10%      | 5.5            | 4.0  | 6.0 | 5.0 | 3.15 | 16.0 | 2M1                        | 2000            |
|                      | RDER72E683K2M1H03A | X7R  | 250                | 68000pF | ±10%      | 5.5            | 4.0  | 6.0 | 5.0 | 3.15 | 16.0 | 2M1                        | 2000            |
|                      | RDER72E104K2M1H03A | X7R  | 250                | 0.1μF   | ±10%      | 5.5            | 4.0  | 6.0 | 5.0 | 3.15 | 16.0 | 2M1                        | 2000            |
|                      | RDER72E154K3M1H03A | X7R  | 250                | 0.15μF  | ±10%      | 5.5            | 5.0  | 7.5 | 5.0 | 4.0  | 16.0 | 3M1                        | 2000            |
|                      | RDER72E224K3M1H03A | X7R  | 250                | 0.22μF  | ±10%      | 5.5            | 5.0  | 7.5 | 5.0 | 4.0  | 16.0 | 3M1                        | 2000            |
|                      | RDER72E334K4M1H03A | X7R  | 250                | 0.33μF  | ±10%      | 7.5            | 5.5  | 8.0 | 5.0 | 4.0  | 16.0 | 4M1                        | 1500            |
|                      | RDER72E474K4M1H03A | X7R  | 250                | 0.47μF  | ±10%      | 7.5            | 5.5  | 8.0 | 5.0 | 4.0  | 16.0 | 4M1                        | 1500            |
|                      | RDER72E684K5E1H03A | X7R  | 250                | 0.68μF  | ±10%      | 7.5            | 7.5  | -   | 5.0 | 4.0  | 17.5 | 5E1                        | 1500            |
|                      | RDER72E105K5E1H03A | X7R  | 250                | 1.0μF   | ±10%      | 7.5            | 7.5  | -   | 5.0 | 4.0  | 17.5 | 5E1                        | 1500            |
|                      | RDER72E225MUE1H03A | X7R  | 250                | 2.2μF   | ±20%      | 7.7            | 12.5 | -   | 5.0 | 4.0  | 17.5 | UE1                        | 1500            |
|                      | RDER72H102K1M1H03A | X7R  | 500                | 1000pF  | ±10%      | 4.5            | 3.5  | 5.0 | 5.0 | 3.15 | 16.0 | 1M1                        | 2000            |
|                      | RDER72H152K1M1H03A | X7R  | 500                | 1500pF  | ±10%      | 4.5            | 3.5  | 5.0 | 5.0 | 3.15 | 16.0 | 1M1                        | 2000            |
|                      | RDER72H222K1M1H03A | X7R  | 500                | 2200pF  | ±10%      | 4.5            | 3.5  | 5.0 | 5.0 | 3.15 | 16.0 | 1M1                        | 2000            |
|                      | RDER72H332K1M1H03A | X7R  | 500                | 3300pF  | ±10%      | 4.5            | 3.5  | 5.0 | 5.0 | 3.15 | 16.0 | 1M1                        | 2000            |
|                      | RDER72H472K1M1H03A | X7R  | 500                | 4700pF  | ±10%      | 4.5            | 3.5  | 5.0 | 5.0 | 3.15 | 16.0 | 1M1                        | 2000            |
|                      | RDER72H682K1M1H03A | X7R  | 500                | 6800pF  | ±10%      | 4.5            | 3.5  | 5.0 | 5.0 | 3.15 | 16.0 | 1M1                        | 2000            |
|                      | RDER72H103K1M1H03A | X7R  | 500                | 10000pF | ±10%      | 4.5            | 3.5  | 5.0 | 5.0 | 3.15 | 16.0 | 1M1                        | 2000            |
|                      | RDER72H153K2M1H03A | X7R  | 500                | 15000pF | ±10%      | 5.5            | 4.0  | 6.0 | 5.0 | 3.15 | 16.0 | 2M1                        | 2000            |
|                      | RDER72H223K2M1H03A | X7R  | 500                | 22000pF | ±10%      | 5.5            | 4.0  | 6.0 | 5.0 | 3.15 | 16.0 | 2M1                        | 2000            |
|                      | RDER72H333K2M1H03A | X7R  | 500                | 33000pF | ±10%      | 5.5            | 4.0  | 6.0 | 5.0 | 3.15 | 16.0 | 2M1                        | 2000            |
|                      | RDER72H473K2M1H03A | X7R  | 500                | 47000pF | ±10%      | 5.5            | 4.0  | 6.0 | 5.0 | 3.15 | 16.0 | 2M1                        | 2000            |
|                      | RDER72H683K3M1H03A | X7R  | 500                | 68000pF | ±10%      | 5.5            | 5.0  | 7.5 | 5.0 | 4.0  | 16.0 | 3M1                        | 2000            |
|                      | RDER72H104K3M1H03A | X7R  | 500                | 0.1μF   | ±10%      | 5.5            | 5.0  | 7.5 | 5.0 | 4.0  | 16.0 | 3M1                        | 2000            |
|                      | RDER72H154K4M1H03A | X7R  | 500                | 0.15μF  | ±10%      | 7.5            | 5.5  | 8.0 | 5.0 | 4.0  | 16.0 | 4M1                        | 1500            |
|                      | RDER72H224K4M1H03A | X7R  | 500                | 0.22μF  | ±10%      | 7.5            | 5.5  | 8.0 | 5.0 | 4.0  | 16.0 | 4M1                        | 1500            |
|                      | RDER72H334K5E1H03A | X7R  | 500                | 0.33μF  | ±10%      | 7.5            | 7.5  | -   | 5.0 | 4.0  | 17.5 | 5E1                        | 1500            |
|                      | RDER72H474K5E1H03A | X7R  | 500                | 0.47μF  | ±10%      | 7.5            | 7.5  | -   | 5.0 | 4.0  | 17.5 | 5E1                        | 1500            |
|                      | RDER72H684MUE1H03A | X7R  | 500                | 0.68μF  | ±20%      | 7.7            | 12.5 | -   | 5.0 | 4.0  | 17.5 | UE1                        | 1500            |
|                      | RDER72H105MUE1H03A | X7R  | 500                | 1.0μF   | ±20%      | 7.7            | 12.5 | -   | 5.0 | 4.0  | 17.5 | UE1                        | 1500            |
|                      | RDER72J102K2M1H03A | X7R  | 630                | 1000pF  | ±10%      | 5.5            | 4.0  | 6.0 | 5.0 | 3.15 | 16.0 | 2M1                        | 2000            |

• Inside Crimp Taping  
(Lead Style: M\*)



• Straight Taping  
(Lead Style: E\*)



Unit : mm

| Customer Part Number | Murata Part Number  | T.C. | DC Rated Volt. (V) | Cap.    | Cap. Tol. | Dimension (mm) |      |     |     |      |      | Dimension (LxW) Lead Style | Pack qty. (pcs) |
|----------------------|---------------------|------|--------------------|---------|-----------|----------------|------|-----|-----|------|------|----------------------------|-----------------|
|                      |                     |      |                    |         |           | L              | W    | W1  | F   | T    | H/H0 |                            |                 |
|                      | RDERR72J152K2M1H03A | X7R  | 630                | 1500pF  | ±10%      | 5.5            | 4.0  | 6.0 | 5.0 | 3.15 | 16.0 | 2M1                        | 2000            |
|                      | RDERR72J222K2M1H03A | X7R  | 630                | 2200pF  | ±10%      | 5.5            | 4.0  | 6.0 | 5.0 | 3.15 | 16.0 | 2M1                        | 2000            |
|                      | RDERR72J332K2M1H03A | X7R  | 630                | 3300pF  | ±10%      | 5.5            | 4.0  | 6.0 | 5.0 | 3.15 | 16.0 | 2M1                        | 2000            |
|                      | RDERR72J472K2M1H03A | X7R  | 630                | 4700pF  | ±10%      | 5.5            | 4.0  | 6.0 | 5.0 | 3.15 | 16.0 | 2M1                        | 2000            |
|                      | RDERR72J682K2M1H03A | X7R  | 630                | 6800pF  | ±10%      | 5.5            | 4.0  | 6.0 | 5.0 | 3.15 | 16.0 | 2M1                        | 2000            |
|                      | RDERR72J103K2M1H03A | X7R  | 630                | 10000pF | ±10%      | 5.5            | 4.0  | 6.0 | 5.0 | 3.15 | 16.0 | 2M1                        | 2000            |
|                      | RDERR72J153K2M1H03A | X7R  | 630                | 15000pF | ±10%      | 5.5            | 4.0  | 6.0 | 5.0 | 3.15 | 16.0 | 2M1                        | 2000            |
|                      | RDERR72J223K2M1H03A | X7R  | 630                | 22000pF | ±10%      | 5.5            | 4.0  | 6.0 | 5.0 | 3.15 | 16.0 | 2M1                        | 2000            |
|                      | RDERR72J333K3M1H03A | X7R  | 630                | 33000pF | ±10%      | 5.5            | 5.0  | 7.5 | 5.0 | 4.0  | 16.0 | 3M1                        | 2000            |
|                      | RDERR72J473K3M1H03A | X7R  | 630                | 47000pF | ±10%      | 5.5            | 5.0  | 7.5 | 5.0 | 4.0  | 16.0 | 3M1                        | 2000            |
|                      | RDERR72J683K4M1H03A | X7R  | 630                | 68000pF | ±10%      | 7.5            | 5.5  | 8.0 | 5.0 | 4.0  | 16.0 | 4M1                        | 1500            |
|                      | RDERR72J104K4M1H03A | X7R  | 630                | 0.1μF   | ±10%      | 7.5            | 5.5  | 8.0 | 5.0 | 4.0  | 16.0 | 4M1                        | 1500            |
|                      | RDERR72J154K5E1H03A | X7R  | 630                | 0.15μF  | ±10%      | 7.5            | 8.0  | -   | 5.0 | 4.0  | 17.5 | 5E1                        | 1500            |
|                      | RDERR72J224K5E1H03A | X7R  | 630                | 0.22μF  | ±10%      | 7.5            | 8.0  | -   | 5.0 | 4.0  | 17.5 | 5E1                        | 1500            |
|                      | RDERR72J474MUE1H03A | X7R  | 630                | 0.47μF  | ±20%      | 7.7            | 13.0 | -   | 5.0 | 4.0  | 17.5 | UE1                        | 1500            |
|                      | RDERR73A471K2M1H03A | X7R  | 1000               | 470pF   | ±10%      | 5.5            | 4.0  | 6.0 | 5.0 | 3.15 | 16.0 | 2M1                        | 2000            |
|                      | RDERR73A681K2M1H03A | X7R  | 1000               | 680pF   | ±10%      | 5.5            | 4.0  | 6.0 | 5.0 | 3.15 | 16.0 | 2M1                        | 2000            |
|                      | RDERR73A102K2M1H03A | X7R  | 1000               | 1000pF  | ±10%      | 5.5            | 4.0  | 6.0 | 5.0 | 3.15 | 16.0 | 2M1                        | 2000            |
|                      | RDERR73A152K2M1H03A | X7R  | 1000               | 1500pF  | ±10%      | 5.5            | 4.0  | 6.0 | 5.0 | 3.15 | 16.0 | 2M1                        | 2000            |
|                      | RDERR73A222K2M1H03A | X7R  | 1000               | 2200pF  | ±10%      | 5.5            | 4.0  | 6.0 | 5.0 | 3.15 | 16.0 | 2M1                        | 2000            |
|                      | RDERR73A332K2M1H03A | X7R  | 1000               | 3300pF  | ±10%      | 5.5            | 4.0  | 6.0 | 5.0 | 3.15 | 16.0 | 2M1                        | 2000            |
|                      | RDERR73A472K2M1H03A | X7R  | 1000               | 4700pF  | ±10%      | 5.5            | 4.0  | 6.0 | 5.0 | 3.15 | 16.0 | 2M1                        | 2000            |
|                      | RDERR73A682K2M1H03A | X7R  | 1000               | 6800pF  | ±10%      | 5.5            | 4.0  | 6.0 | 5.0 | 3.15 | 16.0 | 2M1                        | 2000            |
|                      | RDERR73A103K2M1H03A | X7R  | 1000               | 10000pF | ±10%      | 5.5            | 4.0  | 6.0 | 5.0 | 3.15 | 16.0 | 2M1                        | 2000            |
|                      | RDERR73A153K3M1H03A | X7R  | 1000               | 15000pF | ±10%      | 5.5            | 5.0  | 7.5 | 5.0 | 4.0  | 16.0 | 3M1                        | 2000            |
|                      | RDERR73A223K3M1H03A | X7R  | 1000               | 22000pF | ±10%      | 5.5            | 5.0  | 7.5 | 5.0 | 4.0  | 16.0 | 3M1                        | 2000            |
|                      | RDERR73A333K4M1H03A | X7R  | 1000               | 33000pF | ±10%      | 7.5            | 5.5  | 8.0 | 5.0 | 4.0  | 16.0 | 4M1                        | 1500            |
|                      | RDERR73A473K4M1H03A | X7R  | 1000               | 47000pF | ±10%      | 7.5            | 5.5  | 8.0 | 5.0 | 4.0  | 16.0 | 4M1                        | 1500            |
|                      | RDERR73A683K5E1H03A | X7R  | 1000               | 68000pF | ±10%      | 7.5            | 8.0  | -   | 5.0 | 4.0  | 17.5 | 5E1                        | 1500            |
|                      | RDERR73A104K5E1H03A | X7R  | 1000               | 0.1μF   | ±10%      | 7.5            | 8.0  | -   | 5.0 | 4.0  | 17.5 | 5E1                        | 1500            |
|                      | RDERR73A224MUE1H03A | X7R  | 1000               | 0.22μF  | ±20%      | 7.7            | 13.0 | -   | 5.0 | 4.0  | 17.5 | UE1                        | 1500            |

Reference only

| 5.Specification            |   |  |  |  |                |                           |               |                           |                |                           |       |                           |   |             |   |            |
|----------------------------|---|--|--|--|----------------|---------------------------|---------------|---------------------------|----------------|---------------------------|-------|---------------------------|---|-------------|---|------------|
| No.                        | Test Item                               |  | Specification  | Test Method (Ref. Standard:JIS C 5101(all parts), IEC60384(all parts))   |                |                           |               |                           |                |                           |       |                           |   |             |   |            |
| 1                          | Appearance                              |  | No defects or abnormalities.   | Visual inspection.   |                |                           |               |                           |                |                           |       |                           |   |             |   |            |
| 2                          | Dimension and Marking                   |  | Within the specified dimensions and Marking.   | Visual inspection, Using Caliper.  |                |                           |               |                           |                |                           |       |                           |   |             |   |            |
| 3                          | Dielectric Strength                     | Between Terminals  | No defects or abnormalities.   | The capacitor should not be damaged when voltage in Table is applied between the terminations for 1 to 5 seconds. (Charge/Discharge current $\leq 50\text{mA}$ .) <table border="1" style="margin: 10px auto;"> <thead> <tr> <th>Rated voltage</th> <th>Test voltage</th> </tr> </thead> <tbody> <tr> <td>DC250V</td> <td>200% of the rated voltage</td> </tr> <tr> <td>DC500V, DC630V</td> <td>150% of the rated voltage</td> </tr> <tr> <td>DC1kV</td> <td>120% of the rated voltage</td> </tr> </tbody> </table>  | Rated voltage  | Test voltage              | DC250V        | 200% of the rated voltage | DC500V, DC630V | 150% of the rated voltage | DC1kV | 120% of the rated voltage |   |             |   |            |
|                            |   | Rated voltage  | Test voltage   |  |                |                           |               |                           |                |                           |       |                           |   |             |   |            |
| DC250V                     | 200% of the rated voltage               |  |  |  |                |                           |               |                           |                |                           |       |                           |   |             |   |            |
| DC500V, DC630V             | 150% of the rated voltage               |  |  |  |                |                           |               |                           |                |                           |       |                           |   |             |   |            |
| DC1kV                      | 120% of the rated voltage               |  |  |  |                |                           |               |                           |                |                           |       |                           |   |             |   |            |
| Terminal To External Resin | No defects or abnormalities.            | The capacitor is placed in a container with metal balls of 1mm diameter so that each terminal, short-circuit, is kept approximately 2mm from the balls as shown in the figure, for 1 to 5 seconds between capacitor terminals and metal balls. (Charge/Discharge current $\leq 50\text{mA}$ .) <table border="1" style="margin: 10px auto;"> <thead> <tr> <th>Rated voltage</th> <th>Test voltage</th> </tr> </thead> <tbody> <tr> <td>DC250V, DC500V</td> <td>200% of the rated voltage</td> </tr> <tr> <td>DC630V, DC1kV</td> <td>DC1300V</td> </tr> </tbody> </table> | Rated voltage  | Test voltage   | DC250V, DC500V | 200% of the rated voltage | DC630V, DC1kV | DC1300V                   |                |                           |       |                           |   |             |   |            |
| Rated voltage              | Test voltage                            |  |  |  |                |                           |               |                           |                |                           |       |                           |   |             |   |            |
| DC250V, DC500V             | 200% of the rated voltage               |  |  |  |                |                           |               |                           |                |                           |       |                           |   |             |   |            |
| DC630V, DC1kV              | DC1300V                                 |  |  |  |                |                           |               |                           |                |                           |       |                           |   |             |   |            |
| 4                          | Insulation Resistance (I.R.)            | Between Terminals  | 10 000M $\Omega$ or 100M $\Omega$ · $\mu\text{F}$ min. (Whichever is smaller)  | The insulation resistance should be measured with DC500V (DC250V in case of rated voltage : DC250V) at normal temperature and humidity and within 2 minutes of charging. (Charge/Discharge current $\leq 50\text{mA}$ .)   |                |                           |               |                           |                |                           |       |                           |   |             |   |            |
| 5                          | Capacitance                             |  | Within the specified tolerance.  | The capacitance, D.F. should be measured at 25°C at the frequency and voltage shown in the table.  |                |                           |               |                           |                |                           |       |                           |   |             |   |            |
| 6                          | Dissipation Factor (D.F.)               |  | 0.025 max.   |  |                |                           |               |                           |                |                           |       |                           |   |             |   |            |
| 7                          | Capacitance Temperature Characteristics | within $\pm 15\%$  |  | The capacitance change should be measured at each specified temperature stage. <table border="1" style="margin: 10px auto;"> <thead> <tr> <th>Step</th> <th>Temperature(°C)</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>25<math>\pm 2</math></td> </tr> <tr> <td>2</td> <td>-55<math>\pm 3</math></td> </tr> <tr> <td>3</td> <td>25<math>\pm 2</math></td> </tr> <tr> <td>4</td> <td>125<math>\pm 3</math></td> </tr> <tr> <td>5</td> <td>25<math>\pm 2</math></td> </tr> </tbody> </table> • Pretreatment<br>Perform a heat treatment at 150+0/-10°C for one hour and then set at *room condition temperature for 24 $\pm 2$ hours. | Step           | Temperature(°C)           | 1             | 25 $\pm 2$                | 2              | -55 $\pm 3$               | 3     | 25 $\pm 2$                | 4 | 125 $\pm 3$ | 5 | 25 $\pm 2$ |
|                            |   | Step   | Temperature(°C)  |  |                |                           |               |                           |                |                           |       |                           |   |             |   |            |
| 1                          | 25 $\pm 2$                              |  |  |  |                |                           |               |                           |                |                           |       |                           |   |             |   |            |
| 2                          | -55 $\pm 3$                             |  |  |  |                |                           |               |                           |                |                           |       |                           |   |             |   |            |
| 3                          | 25 $\pm 2$                              |  |  |  |                |                           |               |                           |                |                           |       |                           |   |             |   |            |
| 4                          | 125 $\pm 3$                             |  |  |  |                |                           |               |                           |                |                           |       |                           |   |             |   |            |
| 5                          | 25 $\pm 2$                              |  |  |  |                |                           |               |                           |                |                           |       |                           |   |             |   |            |
| 8                          | Terminal Strength                       | Tensile Strength   | Termination not to be broken or loosened.  | As in the figure, fix the capacitor body, apply the force gradually to each lead in the radial direction of the capacitor until reaching 10N and then keep the force applied for 10 $\pm 1$ seconds.    |                |                           |               |                           |                |                           |       |                           |   |             |   |            |
|                            |   | Bending Strength   | Termination not to be broken or loosened.  | Each lead wire should be subjected to a force of 2.5N and then be bent 90° at the point of egress in one direction. Each wire is then returned to the original position and bent 90° in the opposite direction at the rate of one bend per 2 to 3 seconds.   |                |                           |               |                           |                |                           |       |                           |   |             |   |            |
| 9                          | Vibration Resistance                    | Appearance   | No defects or abnormalities.   | The capacitor should be subjected to a simple harmonic motion having a total amplitude of 1.5mm, the frequency being varied uniformly between the approximate limits of 10Hz and 55Hz. The frequency range, from 10Hz to 55Hz and return to 10Hz, shall be traversed in approximately 1 minute. This motion shall be applied for a period of 2 hours in each 3 mutually perpendicular directions (total of 6 hours).   |                |                           |               |                           |                |                           |       |                           |   |             |   |            |
|                            |   | Capacitance  | Within the specified tolerance.  |  |                |                           |               |                           |                |                           |       |                           |   |             |   |            |
|                            |   | D.F.   | 0.025max.  |  |                |                           |               |                           |                |                           |       |                           |   |             |   |            |
| 10                         | Solderability                           |  | Solder is deposited on unintermittently immersed portion in axial direction covering 3/4 or more in circumferential direction of lead wires. | The terminal of capacitor is dipped into a solution of rosin ethanol (25% rosin in weight propotion). Immerse in solder solution for 2 $\pm 0.5$ seconds. In both cases the depth of dipping is up to about 1.5 to 2mm from the terminal body. Temp. of solder : 245 $\pm 5$ °C (Sn-3.0Ag-0.5Cu)   |                |                           |               |                           |                |                           |       |                           |   |             |   |            |

\* "room condition" Temperature : 15 to 35°C, Relative humidity : 45 to 75%, Atmosphere pressure : 86 to 106kPa

Reference only

| No.  | Test Item  | Specification                           | Test Method (Ref. Standard:JIS C 5101(all parts), IEC60384(all parts))  |            |   |   |   |   |            |                              |            |                              |            |             |            |        |            |        |
|--|--|---|---|------------|---|---|---|---|------------|------------------------------|------------|------------------------------|------------|-------------|------------|--------|------------|--------|
| 11-1   | Resistance to Soldering Heat (Non-Preheat)           | Appearance                              | No defects or abnormalities.  |            |   |   |   |   |            |                              |            |                              |            |             |            |        |            |        |
|  |  | Capacitance Change                      | Within $\pm 7.5\%$  |            |   |   |   |   |            |                              |            |                              |            |             |            |        |            |        |
|  |  | Dielectric Strength (Between terminals) | No defects.   |            |   |   |   |   |            |                              |            |                              |            |             |            |        |            |        |
| 11-2   | Resistance to Soldering Heat (On-Preheat)            | Appearance                              | No defects or abnormalities.  |            |   |   |   |   |            |                              |            |                              |            |             |            |        |            |        |
|  |  | Capacitance Change                      | Within $\pm 7.5\%$  |            |   |   |   |   |            |                              |            |                              |            |             |            |        |            |        |
|  |  | Dielectric Strength (Between terminals) | No defects.   |            |   |   |   |   |            |                              |            |                              |            |             |            |        |            |        |
| 11-3   | Resistance to Soldering Heat (soldering iron method) | Appearance                              | No defects or abnormalities.  |            |   |   |   |   |            |                              |            |                              |            |             |            |        |            |        |
|  |  | Capacitance Change                      | Within $\pm 7.5\%$  |            |   |   |   |   |            |                              |            |                              |            |             |            |        |            |        |
|  |  | Dielectric Strength (Between terminals) | No defects.   |            |   |   |   |   |            |                              |            |                              |            |             |            |        |            |        |
| 12   | Temperature Cycle                                    | Appearance                              | No defects or abnormalities.  |            |   |   |   |   |            |                              |            |                              |            |             |            |        |            |        |
|  |  | Capacitance Change                      | Within $\pm 12.5\%$   |            |   |   |   |   |            |                              |            |                              |            |             |            |        |            |        |
|  |  | D.F.                                    | 0.05 max.   |            |   |   |   |   |            |                              |            |                              |            |             |            |        |            |        |
|  |  | I.R.                                    | 1,000M $\Omega$ or 50M $\Omega$ · $\mu$ F min. (Whichever is smaller)   |            |   |   |   |   |            |                              |            |                              |            |             |            |        |            |        |
|  |  | Dielectric Strength (Between Terminals) | No defects or abnormalities.  |            |   |   |   |   |            |                              |            |                              |            |             |            |        |            |        |
|  |  |   | Test condition<br>Temperature of iron-tip : 350 $\pm$ 10°C<br>Soldering time : 3.5 $\pm$ 0.5 seconds<br>Soldering position<br>Straight Lead : 1.5 to 2.0mm from the root of terminal.<br>Crimp Lead : 1.5 to 2.0mm from the end of lead bend.<br><br>• Pre-treatment<br>Capacitor should be stored at 150+0/-10°C for one hour, then place at *room condition for 24 $\pm$ 2 hours before initial measurement.<br>• Post-treatment<br>Capacitor should be stored for 24 $\pm$ 2 hours at *room condition. |            |   |   |   |   |            |                              |            |                              |            |             |            |        |            |        |
|  |  |   | Repeat 5 cycles according to the 4 heat treatments listed in the following table.<br>Set at *room condition for 24 $\pm$ 2 hours, then measure.   |            |   |   |   |   |            |                              |            |                              |            |             |            |        |            |        |
|  |  |   | <table border="1"> <thead> <tr> <th>Step</th> <th>1</th> <th>2</th> <th>3</th> <th>4</th> </tr> </thead> <tbody> <tr> <td>Temp. (°C)</td> <td>Min. Operating Temp. <math>\pm 3</math></td> <td>Room Temp.</td> <td>Max. Operating Temp. <math>\pm 3</math></td> <td>Room Temp.</td> </tr> <tr> <td>Time (min.)</td> <td>30<math>\pm</math>3</td> <td>3 max.</td> <td>30<math>\pm</math>3</td> <td>3 max.</td> </tr> </tbody> </table>   | Step       | 1 | 2 | 3 | 4 | Temp. (°C) | Min. Operating Temp. $\pm 3$ | Room Temp. | Max. Operating Temp. $\pm 3$ | Room Temp. | Time (min.) | 30 $\pm$ 3 | 3 max. | 30 $\pm$ 3 | 3 max. |
| Step   | 1  | 2                                       | 3   | 4          |   |   |   |   |            |                              |            |                              |            |             |            |        |            |        |
| Temp. (°C)   | Min. Operating Temp. $\pm 3$                         | Room Temp.                              | Max. Operating Temp. $\pm 3$  | Room Temp. |   |   |   |   |            |                              |            |                              |            |             |            |        |            |        |
| Time (min.)  | 30 $\pm$ 3   | 3 max.                                  | 30 $\pm$ 3  | 3 max.     |   |   |   |   |            |                              |            |                              |            |             |            |        |            |        |
|  |  |   | • Pretreatment<br>Perform a heat treatment at 150+0/-10°C for one hour and then set at *room condition for 24 $\pm$ 2 hours.  |            |   |   |   |   |            |                              |            |                              |            |             |            |        |            |        |
| 13   | Humidity (Steady State)                              | Appearance                              | No defects or abnormalities.  |            |   |   |   |   |            |                              |            |                              |            |             |            |        |            |        |
|  |  | Capacitance Change                      | Within $\pm 12.5\%$   |            |   |   |   |   |            |                              |            |                              |            |             |            |        |            |        |
|  |  | D.F.                                    | 0.05 max.   |            |   |   |   |   |            |                              |            |                              |            |             |            |        |            |        |
|  |  | I.R.                                    | 1,000M $\Omega$ or 50M $\Omega$ · $\mu$ F min. (Whichever is smaller)   |            |   |   |   |   |            |                              |            |                              |            |             |            |        |            |        |
|  |  | Marking                                 | Legible.  |            |   |   |   |   |            |                              |            |                              |            |             |            |        |            |        |
| 14   | Humidity Load  | Appearance                              | No defects or abnormalities.  |            |   |   |   |   |            |                              |            |                              |            |             |            |        |            |        |
|  |  | Capacitance Change                      | Within $\pm 12.5\%$   |            |   |   |   |   |            |                              |            |                              |            |             |            |        |            |        |
|  |  | D.F.                                    | 0.05 max.   |            |   |   |   |   |            |                              |            |                              |            |             |            |        |            |        |
|  |  | I.R.                                    | 500M $\Omega$ or 25M $\Omega$ · $\mu$ F min. (Whichever is smaller)   |            |   |   |   |   |            |                              |            |                              |            |             |            |        |            |        |
|  |  | Marking                                 | Legible.  |            |   |   |   |   |            |                              |            |                              |            |             |            |        |            |        |
|  |  |   | Set the capacitor at 40 $\pm$ 2°C and relative humidity 90 to 95% for 500+24/-0 hours.<br>Remove and set at *room condition for 24 $\pm$ 2 hours, then measure.<br><br>• Pretreatment<br>Perform a heat treatment at 150+0/-10°C for one hour and then set at *room condition for 24 $\pm$ 2 hours.   |            |   |   |   |   |            |                              |            |                              |            |             |            |        |            |        |
|  |  |   | Apply the rated voltage at 40 $\pm$ 2°C and relative humidity of 90 to 95% for 500+24/-0 hours.<br>Remove and set at *room condition for 24 $\pm$ 2 hours, then measure. (Charge/Discharge current $\leq$ 50mA.)<br><br>• Pretreatment<br>Perform a heat treatment at 150+0/-10°C for one hour and then set at *room condition for 24 $\pm$ 2 hours.  |            |   |   |   |   |            |                              |            |                              |            |             |            |        |            |        |
| * "room condition" Temperature : 15 to 35°C, Relative humidity : 45 to 75%, Atmosphere pressure : 86 to 106kPa |  |   |   |            |   |   |   |   |            |                              |            |                              |            |             |            |        |            |        |

Reference only

| No.         | Test Item                 | Specification  | Test Method (Ref. Standard:JIS C 5101(all parts), IEC60384(all parts))  |                           |              |        |                           |                |                           |       |                           |
|-------------|---------------------------|--|---|---------------------------|--------------|--------|---------------------------|----------------|---------------------------|-------|---------------------------|
| 15          | High Temperature Load     | Appearance   | Apply voltage in Table for 1000+48/-0 hours at the maximum operating temperature $\pm 3^{\circ}\text{C}$ .<br>Remove and set at *room condition for 24 $\pm$ 2 hours, then measure.<br>(Charge/Discharge current $\leq 50\text{mA}$ .)<br><table border="1" data-bbox="940 327 1369 445"> <thead> <tr> <th>Rated voltage</th> <th>Test voltage</th> </tr> </thead> <tbody> <tr> <td>DC250V</td> <td>150% of the rated voltage</td> </tr> <tr> <td>DC500V, DC630V</td> <td>120% of the rated voltage</td> </tr> <tr> <td>DC1kV</td> <td>110% of the rated voltage</td> </tr> </tbody> </table> | Rated voltage             | Test voltage | DC250V | 150% of the rated voltage | DC500V, DC630V | 120% of the rated voltage | DC1kV | 110% of the rated voltage |
|             |                           | Rated voltage  |   | Test voltage              |              |        |                           |                |                           |       |                           |
|             |                           | DC250V   |   | 150% of the rated voltage |              |        |                           |                |                           |       |                           |
|             |                           | DC500V, DC630V   |   | 120% of the rated voltage |              |        |                           |                |                           |       |                           |
| DC1kV       | 110% of the rated voltage |  |   |                           |              |        |                           |                |                           |       |                           |
| Capacitance | Within $\pm 12.5\%$       |  |   |                           |              |        |                           |                |                           |       |                           |
| Change      |                           |  |   |                           |              |        |                           |                |                           |       |                           |
| D.F.        | 0.04 max.                 |  |   |                           |              |        |                           |                |                           |       |                           |
|             | I.R.                      | 1,000M $\Omega$ or 50M $\Omega$ · $\mu\text{F}$ min.<br>(Whichever is smaller) |   |                           |              |        |                           |                |                           |       |                           |
| 16          | Solvent Resistance        | Appearance   | The capacitor should be fully immersed, unagitated, in reagent at 20 to 25 $^{\circ}\text{C}$ for 30 $\pm$ 5 seconds. and then remove gently. Marking on the surface of the capacitor shall immediately be visually examined.<br><br>Regent : Isopropyl alcohol   |                           |              |        |                           |                |                           |       |                           |
|             |                           | Marking  |   | Legible.                  |              |        |                           |                |                           |       |                           |

\* "room condition" Temperature : 15 to 35 $^{\circ}\text{C}$ , Relative humidity : 45 to 75%, Atmosphere pressure : 86 to 106kPa

## 6. Packing specification

- Bulk type (Packing style code : B)

The size of packing case and packing way



The number of packing = <sup>\*1</sup> Packing quantity × <sup>\*2</sup> n

\*1 : Please refer to [Part number list].

\*2 : Standard n = 20 (bag)


Note)

The outer package and the number of outer packing be changed by the order getting amount.

• Ammo pack taping type (Packing style code : A)

A crease is made every 25 pitches, and the tape with capacitors is packed zigzag into a case. When body of the capacitor is piled on other body under it.

The size of packing case and packing way



## 7. Taping specification

## 7-1. Dimension of capacitors on tape

Straight taping type &lt; Lead Style : E1 &gt;

Pitch of component 12.7mm / Lead spacing 5.0mm



Unit : mm

| Item  | Code | Dimensions                    | Remarks                                |
|---|------|-------------------------------|--|
| Pitch of component                          | P    | 12.7+/-1.0                    |  |
| Pitch of sprocket hole                      | P0   | 12.7+/-0.2                    |  |
| Lead spacing                                | F    | 5.0+0.6/-0.2                  |  |
| Length from hole center to component center | P2   | 6.35+/-1.3                    | Deviation of progress direction        |
| Length from hole center to lead             | P1   | 3.85+/-0.7                    |  |
| Deviation along tape, left or right defect  | ΔS   | 0+/-2.0                       | They include deviation by lead bend    |
| Carrier tape width                          | W    | 18.0+/-0.5                    |  |
| Position of sprocket hole                   | W1   | 9.0+0/-0.5                    | Deviation of tape width direction      |
| For straight lead type                      | H    | 17.5+/-0.5                    |  |
| Protrusion length                           | ℓ    | 0.5 max.                      |  |
| Diameter of sprocket hole                   | ΦD0  | 4.0+/-0.1                     |  |
| Lead diameter                               | Φd   | 0.5+/-0.05                    |  |
| Total tape thickness                        | t1   | 0.6+/-0.3                     | They include hold down tape thickness. |
| Total thickness of tape and lead wire       | t2   | 1.5 max.                      |  |
| Deviation across tape                       | Δh1  | 2.0 max. (Dimension code : U) |  |
|   | Δh2  | 1.0 max. (except as above)    |  |
| Portion to cut in case of defect            | L    | 11.0+0/-1.0                   |  |
| Hold down tape width                        | W0   | 9.5 min.                      |  |
| Hold down tape position                     | W2   | 1.5+/-1.5                     |  |
| Coating extension on lead                   | e    | 2.0 max. (Dimension code : U) |  |
|   |      | 1.5 max. (except as above)    |  |

Inside crimp taping type < Lead Style : M1 >

Pitch of component 12.7mm / Lead spacing 5.0mm




Unit : mm

| Item   | Code | Dimensions                    | Remarks                               |
|--|------|-------------------------------|---------------------------------------|
| Pitch of component                               | P    | 12.7+/-1.0                    |                                       |
| Pitch of sprocket hole                           | P0   | 12.7+/-0.2                    |                                       |
| Lead spacing                                     | F    | 5.0+0.6/-0.2                  |                                       |
| Length from hole center to component center      | P2   | 6.35+/-1.3                    | Deviation of progress direction       |
| Length from hole center to lead                  | P1   | 3.85+/-0.7                    |                                       |
| Deviation along tape, left or right defect       | ΔS   | 0+/-2.0                       | They include deviation by lead bend   |
| Carrier tape width                               | W    | 18.0+/-0.5                    |                                       |
| Position of sprocket hole                        | W1   | 9.0+0/-0.5                    | Deviation of tape width direction     |
| Lead distance between reference and bottom plane | H0   | 16.0+/-0.5                    |                                       |
| Protrusion length                                | ℓ    | 0.5 max.                      |                                       |
| Diameter of sprocket hole                        | ΦD0  | 4.0+/-0.1                     |                                       |
| Lead diameter                                    | Φd   | 0.5+/-0.05                    |                                       |
| Total tape thickness                             | t1   | 0.6+/-0.3                     | They include hold down tape thickness |
| Total thickness of tape and lead wire            | t2   | 1.5 max.                      |                                       |
| Deviation across tape                            | Δh1  | 2.0 max. (Dimension code : W) |                                       |
|  | Δh2  | 1.0 max. (except as above)    |                                       |
| Portion to cut in case of defect                 | L    | 11.0+0/-1.0                   |                                       |
| Hold down tape width                             | W0   | 9.5 min.                      |                                       |
| Hold down tape position                          | W2   | 1.5+/-1.5                     |                                       |
| Coating extension on lead                        | e    | Up to the end of crimp        |                                       |

7-2. Splicing way of tape


- 1) Adhesive force of tape is over 3N at test condition as below.



2) Splicing of tape


- (a) When base tape is spliced

- Base tape shall be spliced by cellophane tape.
- (Total tape thickness shall be less than 1.05mm.)



- (b) When hold down tape is spliced

- Hold down tape shall be spliced with overlapping.
- (Total tape thickness shall be less than 1.05mm.)



- (c) When both tape are spliced

- Base tape and hold down tape shall be spliced with splicing tape.

3) Missing components

- There should be no consecutive missing of more than three components.
- The number of missing components should be not more than 0.5 % of total components that should be present in a Ammo pack.

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

- ⊖ [View RDER71H102K0P1H03B on WIN SOURCE](#)
- ⊖ [Murata Electronics North America Information](#)

## Optimize Your Supply Chain with WIN SOURCE Solutions

- ✓ Global Sourcing Solution
- ✓ Obsolete Management
- ✓ Cost Control Management
- ✓ Shortage Management
- ✓ Alternative Solution
- ✓ Excess Inventory Management