




**THE DATASHEET OF**  
**2432**






- **Smooth, glossy head** provides easy glide and shiny finish.
- Close unneeded panel openings.
- Locking fingers snap into holes with fingertip pressure for quick and easy installation.
- Locking fingers in fractional increments up to the maximum panel thickness.
- Multiple sizes for use in .187” (4,7 mm) to 2.000” (50,8 mm) diameter holes.
- Lock firmly in panel up to .125” (3,2 mm) thick. (G parts)
- For use in panels thicker than .125” (3,2 mm). (GPT parts)
- Withstand a push back force of 35 pounds.



SINGLE PANEL THICKNESS DESIGN



MULTIPLE PANEL THICKNESS DESIGN

## Heyco® Glossy and Thick Panel Glossy Plugs

Mounting Hole Diameter Range: .187” (4,7 mm) to 2.000” (50,8 mm)

MOUNTING HOLE DIAMETER in.   mm.	PART NO.		DESCRIPTION	PART DIMENSIONS				
	Black	White		A Head Diameter in.   mm.		B Overall Height in.   mm.		
Single Locking Step for Panel Thickness up to .062” (1,6 mm)								
.187   4,7	2590	2591	DP 187*	.25	6,4	.23	5,9	
.250   6,4	2600	2601	G 250	.31	7,9	.31	7,9	
.312   7,9	2610	2611	G 312	.38	9,5			
Multiple Locking Steps for Panel Thickness up to .125” (3,2 mm)								
.375   9,5	2620	2621	G 375	.47	11,9	.41	10,3	
.437   11,1	2630	2631	G 437	.53	13,5			
.500   12,7	2640	2641	G 500	.56	14,3			
.562   14,3	2650	2651	G 562	.66	16,7			
.625   15,9	2660	2661	G 625	.73	18,6			
.750   19,1	2680	2681	G 750	.86	21,8	.45	11,5	
.875   22,2	2700	2701	G 875	.95	24,2			
1.000   25,4	2710	2711	G 1000	1.13	28,6			
1.093 - 1.125   27,8 - 28,6	2720	2721	G 1093	1.22	30,9			
1.187   30,1	2730	2731	G 1187	1.31	33,3			
1.375   34,9	2760	2761	G 1375	1.49	37,7	.56	14,3	
1.500   38,1	2770	2771	G 1500	1.61	40,8			
1.750   44,4	2780	2781	G 1750	1.88	47,6			
2.000   50,8	2795	2796	G 2000	2.13	54,8			
Multiple Locking Steps for Panel Thickness up to .250” (6,4 mm)								
.500   12,7	2430	2431	GPT 500	.56	14,3	.56	14,3	
.625   15,9	3134	3135	GPT 625**	.72	18,3	.52	13,1	
.750   19,1	3136	3137	GPT 750**	.85	21,6			
.875   22,2	3138	3139	GPT 875	.95	24,2	.56	14,3	
1.000   25,4	3140	3141	GPT 1000	1.13	28,6			
1.093 - 1.125   27,8 - 28,6	3142	3143	GPT 1093	1.22	30,9			
1.187   30,1	3144	3145	GPT 1187	1.31	33,3			
1.375   34,9	2432	2433	GPT 1375	1.49	37,7			
1.500   38,1	2428	2429	GPT 1500	1.61	40,8	.56	14,3	
1.750   44,4	2436	2437	GPT 1750	1.88	47,6			
2.000   50,8	2438	2439	GPT 2000	2.16	54,8			

Standard color black. Consult Heyco for other colors.

\*Convex, glossy finished head tapers to a thin edge.

\*\* Single locking steps for Panel Thickness up to .250” (6,4 mm)

Quick Specs

Material Certifications



Nylon 6/6  
Recognized under the Component Program of Underwriters' Laboratories, File E51579



Certified by Canadian Standards Association, File 8919

Flammability Rating  
Temperature Range

94V-2  
-40°F (-40°C) to 221°F (105°C)

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

-  [View 2432 on WIN SOURCE](#)
-  [Heyco Products Corporation](#) Information

## Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management