



**THE DATASHEET OF**  
**09150073001**



## R 15-7+E-ISK-STI



Image is for illustration purposes only. Please refer to product description.

Part number	09 15 007 3001
Specification	R 15-7+E-ISK-STI
HARTING eCatalogue	<a href="https://b2b.harting.com/09150073001">https://b2b.harting.com/09150073001</a>

### Identification

Category	Inserts
Series	R 15

### Version

Termination method	Crimp termination
Gender	Male
Number of contacts	7
Details	for thermoplastic hoods / housings

### Technical characteristics

Rated current	10 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	3
Rated voltage acc. to UL	600 V
Rated voltage acc. to CSA	600 V
Insulation resistance	$>10^{10} \Omega$
Limiting temperature	-40 ... +125 °C
Mating cycles	$\geq 500$

### Material properties

Material (insert)	Polyamide (PA)
Colour (insert)	RAL 7032 (pebble grey)



**Pushing Performance**  
Since 1945

## Material properties

Material flammability class acc. to UL 94	HB
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Yes
California Proposition 65 substances	Naphthalene

## Specifications and approvals

UL / CSA	UL 1977 ECBT2.E235076
	CSA-C22.2 No. 182.3 ECBT8.E235076

## Commercial data

Packaging size	10
Net weight	5.4 g
Country of origin	Romania
European customs tariff number	85366990
GTIN	5713140022676
ETIM	EC003557
eCl@ss	27440223 Contact insert for circular connectors

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

- ⊖ [View 09150073001](#) on WIN SOURCE
- ⊖ [HARTING](#) Information

## Optimize Your Supply Chain with WIN SOURCE Solutions

- ✓ Global Sourcing Solution
- ✓ Obsolete Management
- ✓ Cost Control Management
- ✓ Shortage Management
- ✓ Alternative Solution
- ✓ Excess Inventory Management