




**THE DATASHEET OF
KF66X-E15P-N**






D-SUBMINIATURE CONNECTORS:

KF66X Series

Right Angle PCB Mount With Ferrite

KF66X Series Dimensions

Dimensions in mm



Shell Size	A	B	C	C1	D	E
	In mm	± .015 ± 0.38	± .005 ± 0.13	± .010 ± 0.25	± .010 ± 0.25	± .005 ± 0.13
15 (E)	1.213 30.81	.984 24.99	.643 16.33	.666 16.92	.090 2.29	.010 0.25
26 (A)	1.541 39.14	1.312 33.32	.971 24.66	.994 25.25	.090 2.29	.020 0.51
44 (B)	2.088 53.04	1.852 47.04	1.511 38.38	1.534 38.96	.090 2.29	.020 0.51

C = Exterior of Female Shell (S)

C1 = Interior of Male Shell (P)

Electrical Characteristics

Rated Current: 1.5A

Rated Voltage: 29Vac

2D Drawing	IGES	STEP	3D PDF
Solder Profile	CofC RoHS Compliant	CofC REACH Compliant	UL Plastic File
Certificate of Origin	Check Stock	Request a Sample	Send Us An Email

Generated Part Number

Part Number Builder

Series - Shell Size Contact - Contact Type - Mounting Option - Plating Option

Series

KF66X - High Density D-Subminiature Connector, Right Angle PCB Termination, 0.350" Footprint, with Ferrite

Shell Size-Contact Option

E - 15 Contacts

A - 26 Contacts

B - 44 Contacts

Contact Type

P - Pin Contact (Plug)

S - Socket Contact (Receptacle)

Mounting Option

N - With Boardlocks and #4-40 UNC Threaded Insert

NJ - With Boardlocks and #4-40 Jackscrews Installed

Plating Option

Blank - Gold Flash

30 - 30µ" Gold

Contact Kycon for VESA and Other Options

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Kycon:

[KF66X-B44P-N](#) [KF66X-A26S-N](#) [KF66X-E15P-NJ](#) [KF66X-A26P-N](#) [KF66X-A26S-NJ](#) [KF66X-E15S-N-VESA](#) [KF66X-E15P-N](#) [KF66X-E15S-NJ-VESA](#) [KF66X-E15S-N](#) [KF66X-B44S-N](#) [KF66X-A26P-NJ](#) [KF66X-B44S-NJ](#) [KF66X-E15S-NJ](#) [KF66X-A26P-N30](#) [KF66X-B44P-NJ30](#) [KF66X-C62P-NJ](#) [KF66X-C62S-N](#) [KF66X-C62S-NJ](#) [KF66X-B44S-N30](#) [KF66X-A26P-NJ30](#) [KF66X-E15S-NJ30](#) [KF66X-C62P-N30](#) [KF66X-A26S-N30](#) [KF66X-C62P-N](#) [KF66X-C62S-N30](#) [KF66X-A26S-NJ30](#) [KF66X-E15P-N30](#) [KF66X-B44S-NJ30](#) [KF66X-C62S-NJ30](#) [KF66X-B44P-NJ](#) [KF66X-B44P-N30](#) [KF66X-E15S-N30](#) [KF66X-C62P-NJ30](#) [KF66X-E15P-NJ30](#) [KF66X-A26S-NT15](#) [KF66X-C62S-NR30](#) [KF66X-B44P-NT](#) [KF66X-B44P-N15](#) [KF66X-E15P-NR](#) [KF66X-A26P-NT30](#) [KF66X-A26S-NR15](#) [KF66X-E15P-NV15](#) [KF66X-A26P-NVJ](#) [KF66X-A26S-NVJ30](#) [KF66X-B44S-NT15](#) [KF66X-C62P-NR](#) [KF66X-E15S-NV15](#) [KF66X-A26S-N15](#) [KF66X-B44P-NVJ](#) [KF66X-E15P-NVJ15](#) [KF66X-A26S-NT](#) [KF66X-E15P-NT15](#) [KF66X-B44P-NV](#) [KF66X-C62P-N15](#) [KF66X-E15S-NT30](#) [KF66X-C62S-NV30](#) [KF66X-A26S-NT30](#) [KF66X-E15P-NVJ30](#) [KF66X-E15S-NT](#) [KF66X-A26P-NR](#) [KF66X-C62P-NR15](#) [KF66X-E15P-NR15](#) [KF66X-E15S-NVJ](#) [KF66X-A26S-NV](#) [KF66X-B44S-NVJ](#) [KF66X-E15S-NVJ15](#) [KF66X-A26P-NV](#) [KF66X-C62P-NV15](#) [KF66X-A26S-NV30](#) [KF66X-E15S-NR-VESA](#) [KF66X-E15P-NVJ](#) [KF66X-E15P-NR30](#) [KF66X-C62S-NVJ15](#) [KF66X-B44P-NJ15](#) [KF66X-E15S-NT15](#) [KF66X-B44P-NT30](#) [KF66X-B44P-NR](#) [KF66X-E15S-NV30](#) [KF66X-A26S-NVJ](#) [KF66X-B44P-NVJ30](#) [KF66X-B44S-NT30](#) [KF66X-B44P-NVJ15](#) [KF66X-E15S-NV](#) [KF66X-A26P-NT15](#) [KF66X-E15S-NVJ30](#) [KF66X-C62S-NR](#) [KF66X-B44P-NT15](#) [KF66X-E15P-N15](#) [KF66X-B44S-NV30](#) [KF66X-E15S-N15](#) [KF66X-E15P-NJ15](#) [KF66X-C62P-NVJ15](#) [KF66X-B44S-NT](#) [KF66X-A26P-NR30](#) [KF66X-A26P-NV15](#) [KF66X-B44S-NV15](#) [KF66X-C62S-NVJ30](#) [KF66X-B44S-NVJ30](#) [KF66X-C62P-NVJ30](#) [KF66X-C62P-NV30](#)

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View KF66X-E15P-N on WIN SOURCE](#)

 [Kycon, Inc. Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management