



**THE DATASHEET OF
ARJE-0028**



2.5 x 2.0 x 0.95 mm 32.768kHz CERAMIC SURFACE MOUNT CRYSTAL OSCILLATOR



2.5 x 2.0 x 0.95 mm

ASDK Series

Pb **RoHS**
Compliant

FEATURES:

- 32.768kHz in 2.5 x 2.0 x 0.95mm package
- Seam sealed assure high reliability performance
- Low current consumption 1.0mA (Vdd=1.8V)
- Suitable for RoHS compliant reflow
- Extend temperature range available

APPLICATIONS:

- Laptop
- Digital camera
- Wireless LAN
- Bluetooth and mobile communication
- LCD
- PDA and MP3 player
- Electricity, gas and water metering

STANDARD SPECIFICATIONS:

Parameters		Minimum	Typical	Maximum	Units	Notes
Frequency Range		-----	32.768	-----	kHz	
Operating Temperature		0	-----	+70	°C	See options
Storage Temperature		-55	-----	+125	°C	
Overall Frequency Stability		-100	-----	+100	ppm	See options
Supply Voltage (Vdd)		2.97	3.3	3.66	V	Standard
		2.375	2.5	2.625		Option 1
		1.71	1.8	1.89		Option 2
Supply Current (I _{dd})		-----	1.0	1.5	mA	Vdd=1.8V
			1.2	2.5		Vdd=2.5V
			2.2	3.5		Vdd=3.3V
Output Load		-----	-----	15	pF	CMOS
Output Voltage	V _{OH}	0.9*Vdd	-----	-----	V	
	V _{OL}	-----	-----	0.1*Vdd		
Tri-state function		"1" (V _{IH} ≥ 0.7*Vdd) Open: Oscillation "0" (V _{IL} < 0.3*Vdd) : Hi Z				
Aging		-3.0	-----	+3.0	ppm	@+25°C First year
Symmetry @1/2Vdd		40	50	60	%	Standard
		45	50	55		Option S
Start-up Time		-----	≤ 2	5	ms	
Rise/Fall Time (Tr/Tf)		-----	43	50	ns	
Disable Current				10	μA	

OPTIONS AND PART IDENTIFICATION (Left blank if standard)

ASDK - 32.768kHz - - - -

Supply Voltage
Blank: 3.3V±10%
1: 2.5 V±5%
2: 1.8 V±5%

Operating Temp.
Blank: 0°C ~ +70°C
E: -20°C ~ +70°C
F: -30°C ~ +70°C
N: -30°C ~ +85°C
L: -40°C ~ +85°C

Overall Freq. Stability
Blank: ±100ppm
J: ±20ppm (**)
R: ±25ppm
K: ±30 ppm
C: ±50 ppm

Symmetry
Blank: 40/60%
S: 45/55%

Packaging
Blank: Bulk
T: Tape & Reel

*Contact ABRACON for extended temperature range

** For Temp option E, F, N and 0° C to + 70° C only

2.5 x 2.0 x 0.95 mm 32.768kHz CERAMIC SURFACE MOUNT CRYSTAL OSCILLATOR



2.5 x 2.0 x 0.95 mm

ASDK Series

Pb RoHS Compliant

OUTLINE DRAWING:

Recommended Land Pattern

PIN	FUNCTION
1	Tri-state
2	GND
3	Output
4	Vdd

Note: Recommend using an approximately 0.01uF bypass capacitor between PIN 2 and 4.

Dimensions: inches (mm)

TAPE & REEL:(1,000pcs/reel)

REFLOW PROFILE

FEEDING (PULL) DIRECTION →

Dimensions: mm

Zone	Description	Temperature	Time
1	Preheat	$T_{SMIN} \sim T_{SMAX}$ 150°C ~ 180°C	60 ~ 120 sec.
2	Reflow	T_L 230°C	30 ~ 40 sec.
3	Peak Heat	T_p 260°C	10 sec. MAX



Need a test socket for the ASDK Series? To view compatible **PRECISION TEST & BURN-IN SOCKETS** for these parts, [click here](#). **AXS-2520-04-07**

ATTENTION: Abracon products are COTS – Commercial-Off-The-Shelf products; suitable for Commercial, Industrial and, where designated, Automotive Applications. Abracon's products are not specifically designed for Military, Aviation, Aerospace, Life-dependant Medical applications or any application requiring high reliability where component failure could result in loss of life and/or property. For applications requiring high reliability and/or presenting an extreme operating environment, written consent and authorization from Abracon is required. Please contact Abracon for more information.

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View ARJE-0028](#) on WIN SOURCE

 [Abracon LLC](#) Information

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management