

**WIN***SOURCE*  
ELECTRONICS


**THE DATASHEET OF**

**618009221923**

win-source.net



0086-755-83957316



TECHNICAL CHARACTERISTICS

MATERIAL  
 INSULATOR: PBT  
 FLAMABILITY RATING: UL94-V0  
 COLOR: BLUE  
 CONTACT MATERIAL: COPPER ALLOY  
 CONTACT TYPE: STAMPED  
 CONTACT PLATING: SELECTIVE GOLD  
 SHIELDING: STEEL TIN PLATED  
 QUALITY CLASS: 3 AS PER CECC 75 301-802

ENVIRONMENTAL  
 OPERATING TEMPERATURE: -40 UP TO 85°C  
 COMPLIANCE: LEAD FREE AND ROHS

ELECTRICAL  
 CURRENT RATING: 3A  
 WORKING VOLTAGE: 125V AC  
 INSULATOR RESISTANCE: >5000 MOHM  
 DIELECTRIC WITHSTANDING VOLTAGE: 1000V AC/MN  
 CONTACT RESISTANCE: 30 MOHM MAX


PACKAGING  
 TRAY + BAG\*

\*Strain relief is always delivered in a separate bag for optional use

DIMENSION

PINS	A	B	C	D	E	H
9	24.99	30.80	11.08	8.31	16.10	16.33
15	33.32	39.10	19.39	16.62	24.00	24.66
25	47.04	53.09	33.24	30.47	38.14	38.38
37	63.50	69.04	49.86	47.09	54.60	54.84

RoHS Compliant			
G			
F			
E			
D	05-NOV-12	UL	GG
C	06-JAN-10	DIMENSION	JP
B	07-DEC-09	WORKING VOLT.	JP
A	19-NOV-09	STANDARD	JP
REV	DATE	FILE	BY



GENERAL TOLERANCE  
 .X = +/- 0.2  
 .XX = +/- 0.15



APPROVAL: RJ

UNIT: MM

DESCRIPTION: D-SUB FEMALE IDC

SCALE:

WERI PART NO: 618 0xx 221 923

SHEET: 1/1

DRAW: PEARL

SIZE

**A4**



## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View 618009221923 on WIN SOURCE](#)

 [Wurth Electronics Inc](#) Information

## Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management