



**THE DATASHEET OF  
TFI143-400-12\_14MM**





**TET ESTEL AS**  
ESTONIA

**April**  
**2014**

**Series**  
**TFI143-400**

**High Frequency Inverter grade**  
**Capsule Thyristor**  
**Type TFI143-400**

Low turn-off time  
Low reverse recovery charge  
Distributed amplified gate for high di/dt

Maximum mean on-state current	$I_{TAV}$ <b>400 A</b>				
Maximum repetitive peak off-state and reverse voltage	$U_{DRM}$ <b>800 ÷ 1200 V</b>				
Turn-off time	$U_{RRM}$ <b>6,3; 8; 10 <math>\mu</math>s</b>				
	$t_q$				
$U_{DRM}, U_{RRM}, V$	800	900	1000	1100	1200
Voltage code	8	9	10	11	12
$T_{vj}, ^\circ C$	- 60 ÷ 125				

**MAXIMUM ALLOWABLE RATINGS**

Symbols and parameters		Units	TFI143-400	Conditions
$I_{TAV}$	Mean on-state current	A	400 716	$T_c=90^\circ C,$ $T_c=55^\circ C,$ 180° half-sine wave, 50 Hz
$I_{TRMS}$	RMS on-state current	A	628	$T_c=90^\circ C$
$I_{TSM}$	Surge on-state current	kA	10,0 11,0	$T_{vj}=125^\circ C$ $T_{vj}=25^\circ C$ tp=10 ms
$I^2t$	Limiting load integral	$kA^2s$	500 605	$T_{vj}=125^\circ C$ $T_{vj}=25^\circ C$ $U_R=0$
$U_{DRM}, U_{RRM}$	Repetitive peak off-state and reverse voltage	V	800÷1200	$T_j \min \leq T_{vj} \leq T_{jM}$ 180° half-sine wave, 50 Hz Gate open
$U_{DSM}, U_{RSM}$	Non-repetitive peak off-state and reverse voltage	V	880÷1300	$T_j \min \leq T_{vj} \leq T_{jM}$ 180° half-sine wave tp=10 ms, Single pulse Gate open
(diT/dt) crit	Critical rate of rise of on-state current : non - repetitive repetitive	$A/\mu s$	2000 1250	$T_{vj}=125^\circ C ; U_D=0,67 U_{DRM},$ Gate pulse : 10V, 5 $\Omega,$ 1 $\mu s$ rise time, 10 $\mu s$
$U_{RGM}$	Peak reverse gate voltage	V	5	$T_j \min \leq T_{vj} \leq T_{jM}$
$T_{stg}$	Storage temperature	$^\circ C$	-60÷80	
$T_{vj}$	Junction temperature	$^\circ C$	-60÷125	

**CHARACTERISTICS**

$U_{TM}$	Peak on-state voltage	V	2,55	$T_{vj}=25^\circ C, I_{TM}=3,14 I_{TAV}$
$U_{T(TO)}$	Threshold voltage	V	1,45	$T_{vj}=125^\circ C$
$R_T$	On-state slope resistance	$m\Omega$	0,65	$1,57 I_{TAV} < I_T < 4,71 I_{TAV}$
$I_{DRM}$ $I_{RRM}$	Repetitive peak off-state and reverse current	mA	50 50	$T_{vj}=125^\circ C,$ $U_D = U_{DRM}$ $U_R = U_{RRM}$



## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

- ⊖ [View TFI143-400-12\\_14mm](#) on WIN SOURCE
- ⊖ [TET Estel](#) Information

## Optimize Your Supply Chain with WIN SOURCE Solutions

- ✓ Global Sourcing Solution
- ✓ Obsolete Management
- ✓ Cost Control Management
- ✓ Shortage Management
- ✓ Alternative Solution
- ✓ Excess Inventory Management