




**THE DATASHEET OF
MCA1206MD3304BP500**





High Stability Thin Film Flat Chip Resistors



FEATURES

- Rated dissipation P_{70} up to 0.52 W for size 1206
- AEC-Q200 qualified
- IECQ-CECC approved to EN 140401-801
- Operating temperature up to 175 °C
- Superior temperature cycling robustness
- Superior moisture resistivity, $|\Delta R/R| < 0.1 \%$ (85 °C; 85 % RH; 1000 h)
- Advanced sulfur resistance verified according to ASTM B 809
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912



RoHS COMPLIANT

Vishay Automotive Grade MC AT thin film chip resistors are the perfect choice for most fields of modern electronics where reliability and stability is of major concern. Typical applications include automotive, industrial, telecommunication and medical equipment, as well as precision test and measuring equipment.

APPLICATIONS

- Automotive
- Industrial equipment with enhanced requirements
- Telecommunication
- Medical equipment

TECHNICAL SPECIFICATIONS				
DESCRIPTION	MCS 0402 AT	MCT 0603 AT	MCU 0805 AT	MCA 1206 AT
Imperial size	0402	0603	0805	1206
Metric size code	RR1005M	RR1608M	RR2012M	RR3216M
Resistance range	1 Ω to 1 MΩ; 0 Ω	1 Ω to 2 MΩ; 0 Ω	1 Ω to 7.5 MΩ; 0 Ω	1 Ω to 10 MΩ; 0 Ω
Resistance tolerance	± 1 %; ± 0.5 %; ± 0.1 %	± 1 %; ± 0.5 %; ± 0.1 %; ± 0.05 %	± 1 %; ± 0.5 %; ± 0.1 %	
Temperature coefficient	± 50 ppm/K; ± 25 ppm/K; ± 15 ppm/K; ± 10 ppm/K	± 50 ppm/K; ± 25 ppm/K; ± 15 ppm/K; ± 10 ppm/K; ± 5 ppm/K	± 50 ppm/K; ± 25 ppm/K; ± 15 ppm/K; ± 10 ppm/K	
Rated dissipation P_{70} ⁽¹⁾	0.130 W	0.210 W	0.260 W	0.520 W
Operating voltage, U_{max} . AC _{RMS} /DC	50 V	75 V	150 V	200 V
Permissible film temperature, $\vartheta_{F max}$. ⁽¹⁾	175 °C			
Operating temperature range ⁽²⁾	-55 °C to 175 °C			
Internal thermal resistance (typical) ⁽¹⁾	90 K/W	63 K/W	38 K/W	32 K/W
Permissible voltage against ambient (insulation): 1 min; U_{ins}	75 V	100 V	200 V	300 V
Failure rate: FIT _{observed}	≤ 0.1 x 10 ⁻⁹ /h			

Notes

- ⁽¹⁾ Please refer to APPLICATION INFORMATION, see below
⁽²⁾ Please refer to table MAXIMUM RESISTANCE CHANGE AT RATED DISSIPATION, see below

APPLICATION INFORMATION

When the resistor dissipates power, a temperature rise above the ambient temperature occurs, dependent on the thermal resistance of the assembled resistor together with the printed circuit board. The rated dissipation applies only if the permitted film temperature is not exceeded.

Please consider the application note “Thermal Management in Surface-Mounted Resistor Applications” (www.vishay.com/doc?28844) for information on the general nature of thermal resistance.

These resistors do not feature a limited lifetime when operated within the permissible limits. However, resistance value drift increasing over operating time may result in exceeding a limit acceptable to the specific application, thereby establishing a functional lifetime.



MAXIMUM RESISTANCE CHANGE AT RATED DISSIPATION							
OPERATION MODE		GENERAL		POWER		ADVANCED	
Rated dissipation, P_{70}	MCS 0402 AT	0.070 W		0.105 W		0.130 W	
	MCT 0603 AT	0.110 W		0.170 W		0.210 W	
	MCU 0805 AT	0.140 W		0.220 W		0.260 W	
	MCA 1206 AT	0.270 W		0.420 W		0.520 W	
Operating temperature range		-55 °C to 125 °C		-55 °C to 155 °C		-55 °C to 175 °C	
Permissible film temperature, ϑ_F max.		125 °C		155 °C		175 °C	
Max. resistance change at P_{70} for resistance range, $ \Delta R/R $ after:	MCS 0402 AT	1 Ω to \leq 47 k Ω	> 47 k Ω to 1 M Ω	1 Ω to \leq 47 k Ω	> 47 k Ω to 1 M Ω	1 Ω to \leq 47 k Ω	> 47 k Ω to 1 M Ω
	MCT 0603 AT	1 Ω to \leq 100 k Ω	> 100 k Ω to 2 M Ω	1 Ω to \leq 100 k Ω	> 100 k Ω to 2 M Ω	1 Ω to \leq 100 k Ω	> 100 k Ω to 2 M Ω
	MCU 0805 AT	1 Ω to \leq 100 k Ω	> 100 k Ω to 7.5 M Ω	1 Ω to \leq 100 k Ω	> 100 k Ω to 7.5 M Ω	1 Ω to \leq 100 k Ω	> 100 k Ω to 7.5 M Ω
	MCA 1206 AT	1 Ω to \leq 100 k Ω	> 100 k Ω to 10 M Ω	1 Ω to \leq 100 k Ω	> 100 k Ω to 10 M Ω	1 Ω to \leq 100 k Ω	> 100 k Ω to 10 M Ω
	1000 h	\leq 0.05 %	\leq 0.1 %	\leq 0.1 %	\leq 0.2 %	\leq 0.2 %	\leq 0.5 %
8000 h	\leq 0.1 %	\leq 0.2 %	\leq 0.2 %	\leq 0.4 %	-	-	
225 000 h	\leq 0.3 %	\leq 0.6 %	\leq 0.6 %	-	-	-	

Note

- The presented operation modes do not refer to different types of resistors, but actually show examples of different loads, that lead to different film temperatures and different achievable load-life stability (drift) of the resistance value. A suitable low thermal resistance of the circuit board assembly must be safeguarded in order to maintain the film temperature of the resistors within the specified limits. Please consider the application note "Thermal Management in Surface-Mounted Resistor Applications" (www.vishay.com/doc?28844) for information on the general nature of thermal resistance

TEMPERATURE COEFFICIENT AND RESISTANCE RANGE (1)				
TYPE / SIZE	TCR	TOLERANCE	RESISTANCE	E-SERIES
MCS 0402 AT	\pm 50 ppm/K	\pm 1 %	1 Ω to 221 k Ω	E24; E96
	\pm 25 ppm/K	\pm 0.5 %	10 Ω to 221 k Ω	E24; E192
	\pm 25 ppm/K	\pm 0.1 %	47 Ω to 1 M Ω	E24; E192
	\pm 15 ppm/K		47 Ω to 100 k Ω	
	\pm 10 ppm/K		47 Ω to 47 k Ω	
Jumper (2); $I_{max.} = 0.63$ A		\leq 20 m Ω	0 Ω	-
MCT 0603 AT	\pm 50 ppm/K	\pm 1 %	1 Ω to 511 k Ω	E24; E96
	\pm 25 ppm/K	\pm 0.5 %	10 Ω to 511 k Ω	E24; E192
	\pm 25 ppm/K	\pm 0.1 %	47 Ω to 2 M Ω	E24; E192
	\pm 15 ppm/K		47 Ω to 221 k Ω	
	\pm 10 ppm/K		47 Ω to 100 k Ω	
	\pm 5 ppm/K		3.9 k Ω to 100 k Ω	
	\pm 5 ppm/K	\pm 0.05 %	3.9 k Ω to 100 k Ω	
Jumper (2); $I_{max.} = 1$ A		\leq 20 m Ω	0 Ω	-
MCU 0805 AT	\pm 50 ppm/K	\pm 1 %	1 Ω to 1 M Ω	E24; E96
	\pm 25 ppm/K	\pm 0.5 %	10 Ω to 1 M Ω	E24; E192
	\pm 25 ppm/K	\pm 0.1 %	47 Ω to 7.5 M Ω	E24; E192
	\pm 15 ppm/K		47 Ω to 332 k Ω	
	\pm 10 ppm/K		47 Ω to 100 k Ω	
Jumper (2); $I_{max.} = 1.5$ A		\leq 20 m Ω	0 Ω	-
MCA 1206 AT	\pm 50 ppm/K	\pm 1 %	1 Ω to 1 M Ω	E24; E96
	\pm 25 ppm/K	\pm 0.5 %	10 Ω to 1 M Ω	E24; E192
	\pm 25 ppm/K	\pm 0.1 %	47 Ω to 10 M Ω	E24; E192
	\pm 15 ppm/K		47 Ω to 511 k Ω	
	\pm 10 ppm/K		47 Ω to 100 k Ω	
	Jumper (2); $I_{max.} = 2$ A		\leq 20 m Ω	0 Ω

Notes

- (1) For the approved IECQ-CECC resistance range, including stability class information, please refer to www.vishay.com/doc?28945
- (2) The temperature coefficient of resistance (TCR) is not specified for 0 Ω jumpers



PACKAGING						
TYPE / SIZE	CODE	QUANTITY	PACKAGING STYLE	WIDTH	PITCH	PACKAGING DIMENSIONS
MCS 0402 AT	E5	5000	Paper tape acc. IEC 60286-3, type 1a	8 mm	2 mm	Ø 180 mm / 7"
	E0	10 000				Ø 180 mm / 7"
MCT 0603 AT	P5	5000		8 mm	4 mm	Ø 180 mm / 7"
	PW	20 000				Ø 330 mm / 13"
MCU 0805 AT	P5	5000		8 mm	4 mm	Ø 180 mm / 7"
	PW	20 000				Ø 330 mm / 13"
MCA 1206 AT	P5	5000	8 mm	4 mm	Ø 180 mm / 7"	

PART NUMBER AND PRODUCT DESCRIPTION

Part Number: MCT0603MD4641DPW00
 Part Number: MCT0603MZ0000ZP500

M	C	T	0	6	0	3	M	D	4	6	4	1	D	P	W	0	0
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

TYPE / SIZE	VERSION	TCR	RESISTANCE	TOLERANCE	PACKAGING	SPECIAL
MCS0402 MCT0603 MCU0805 MCA1206	M = AT (automotive)	G = ± 5 ppm/K F = ± 10 ppm/K E = ± 15 ppm/K D = ± 25 ppm/K C = ± 50 ppm/K Z = jumper	3 digit value 1 digit multiplier Multiplier 8 = *10 ⁻² 9 = *10 ⁻¹ 0 = *10 ⁰ 1 = *10 ¹ 2 = *10 ² 3 = *10 ³ 4 = *10 ⁴ 5 = *10 ⁵	A = ± 0.05 % B = ± 0.1 % D = ± 0.5 % F = ± 1 % Z = jumper	E5 E0 P5 PW	Up to 2 digits 00 = standard

Product Description: MCT 0603-25 0.5 % AT PW 4K64
 Product Description: MCT 0603 AT P5 0R0

MCT	0603	-25	0.5 %	AT	PW	4K64
TYPE	SIZE	TCR	TOLERANCE	VERSION	PACKAGING	RESISTANCE
MCS MCT MCU MCA	0402 0603 0805 1206	± 5 ppm/K ± 10 ppm/K ± 15 ppm/K ± 25 ppm/K ± 50 ppm/K	± 0.05 % ± 0.1 % ± 0.5 % ± 1 %	AT = automotive	E5 E0 P5 PW	4K64 = 4.64 kΩ 0R0 = jumper

Note

- Products can be ordered using either the PART NUMBER or PRODUCT DESCRIPTION



DESCRIPTION

Production is strictly controlled and follows an extensive set of instructions established for reproducibility. A homogeneous film of special metal alloy is deposited on a high grade ceramic substrate (Al_2O_3) and conditioned to achieve the desired temperature coefficient. Specially designed inner contacts are deposited on both sides. A special laser is used to achieve the target value by smoothly cutting a meander groove in the resistive layer without damaging the ceramics. The resistor elements are covered by a unique protective coating designed for electrical, mechanical and climatic protection. The terminations receive a final pure matte tin on nickel plating.

The result of the determined production is verified by an extensive testing procedure and optical inspection performed on 100 % of the individual chip resistors. This includes full screening for the elimination of products with potential risk of early field failures (feasible for $R \geq 10 \Omega$). Only accepted products are laid directly into the paper tape in accordance with **IEC 60286-3 Type 1a** ⁽¹⁾.

ASSEMBLY

The resistors are suitable for processing on automatic SMD assembly systems. They are suitable for automatic soldering using wave, reflow or vapour phase as shown in **IEC 61760-1** ⁽¹⁾. The encapsulation is resistant to all cleaning solvents commonly used in the electronics industry, including alcohols, esters and aqueous solutions. The suitability of conformal coatings, potting compounds and their processes, if applied, shall be qualified by appropriate means to ensure the long-term stability of the whole system.

The resistors are RoHS-compliant; the pure matte tin plating provides compatibility with lead (Pb)-free and lead-containing soldering processes. Solderability is specified for 2 years after production or requalification. The permitted storage time is 20 years. The immunity of the plating against tin whisker growth has been proven under extensive testing.

MATERIALS

Vishay acknowledges the following systems for the regulation of hazardous substances:

- IEC 62474, Material Declaration for Products of and for the Electrotechnical Industry, with the list of declarable substances given therein ⁽²⁾
- The Global Automotive Declarable Substance List (GADSL) ⁽³⁾
- The REACH regulation (1907/2006/EC) and the related list of substances with very high concern (SVHC) ⁽⁴⁾ for its supply chain

Notes

- (1) The quoted IEC standards are also released as EN standards with the same number and identical contents
- (2) The IEC 62474 list of declarable substances is maintained in a dedicated database, which is available at <http://std.iec.ch/iec62474>
- (3) The Global Automotive Declarable Substance List (GADSL) is maintained by the American Chemistry Council and available at www.gadsl.org
- (4) The SVHC list is maintained by the European Chemical Agency (ECHA) and available at <http://echa.europa.eu/candidate-list-table>
- (5) For the approved IECQ-CECC resistance range, please refer to www.vishay.com/doc?28945

The products do not contain any of the banned substances as per IEC 62474, GADSL, or the SVHC list, see www.vishay.com/how/leadfree.


Hence the products fully comply with the following directives:

- 2000/53/EC End-of-Life Vehicle Directive (ELV) and Annex II (ELV II)
- 2011/65/EU Restriction of the Use of Hazardous Substances Directive (RoHS) with amendment 2015/863/EU
- 2012/19/EU Waste Electrical and Electronic Equipment Directive (WEEE)

Vishay pursues the elimination of conflict minerals from its supply chain, see the Conflict Minerals Policy at www.vishay.com/doc?49037.

APPROVALS

Where applicable, the resistors are approved within the IECQ-CECC Quality Assessment System for Electronic Components to the detail specification **EN 140401-801** which refers to **EN 60115-1**, **EN 60115-8** and the variety of environmental test procedures of the **IEC 60068** ⁽¹⁾ series.

Conformity is attested by the use of the **CECC** ⁽⁵⁾ logo () as the mark of conformity on the package label.

Vishay Beyschlag has achieved “**Approval of Manufacturer**” in accordance with **IECQ 03-1**. The release certificate for “**Technology Approval Schedule**” in accordance with **CECC 240001** based on **IECQ 03-3-1** is granted for the Vishay Beyschlag manufacturing process.

The resistors are qualified according to AEC-Q200.

RELATED PRODUCTS

Chip resistor arrays may be used in sensing applications or precision amplifiers where close matching between multiple resistors is necessary. Please refer to the **ACAS AT - Precision** datasheet (www.vishay.com/doc?28770).


MC AT series is also available with gold termination for conductive gluing: **MC ATAU - Precision**. Please refer to the datasheet (www.vishay.com/doc?28877).

For high power and high temperature applications **MCW AT** wide terminal thin film chip resistors offer extremely high power ratings and extraordinary temperature cycling robustness. Please refer to the datasheets: www.vishay.com/doc?28847 and www.vishay.com/doc?28796.


These wide-terminal products are also available in low-ohmic values, **NCW AT** (www.vishay.com/doc?28849).




FUNCTIONAL PERFORMANCE




Derating - General Operation



Derating - Power Operation




Derating - Advanced Operation




Maximum pulse load, single pulse; applicable if $\bar{P} \rightarrow 0$ and $n \leq 1000$ and $\hat{U} \leq \hat{U}_{max}$; for permissible resistance change equivalent to 8000 h operation in standard operation mode

Single Pulse (1)



Maximum pulse load, continuous pulses; applicable if $\bar{P} \leq P(\vartheta_{amb})$ and $\hat{U} \leq \hat{U}_{max}$; for permissible resistance change equivalent to 8000 h operation in standard operation mode

Continuous Pulse (1)




Maximum pulse voltage, single and continuous pulses; applicable if $\hat{P} \leq \hat{P}_{max}$; for permissible resistance change equivalent to 8000 h operation in standard operation mode

Pulse Voltage (1)


Note

(1) Measured on components with $\pm 0.5\%$ or $\pm 1\%$ tolerance




Pulse load rating in accordance with EN 60115-1 clause 4.27; 1.2 μ s/50 μ s;
5 pulses at 12 s intervals; for permissible resistance change $\pm (0.5 \% R + 0.05 \Omega)$

1.2/50 Pulse ⁽¹⁾



Pulse load rating in accordance with EN 60115-1 clause 4.27; 10 μ s/700 μ s;
10 pulses at 1 minute intervals; for permissible resistance change $\pm (0.5 \% R + 0.05 \Omega)$

10/700 Pulse ⁽¹⁾




In accordance with IEC 60195

Current Noise Voltage Ratio

Note

⁽¹⁾ Measured on components with $\pm 0.5 \%$ or $\pm 1 \%$ tolerance



|Z|/R for 49.9 chip resistor

RF-Behavior



TESTS AND REQUIREMENTS

All tests are carried out in accordance with the following specifications:

- EN 60115-1, generic specification
- EN 60115-8, sectional specification
- EN 140401-801, detail specification
- IEC 60068-2-xx, test methods

When applicable, the components are approved under the IECQ-CECC quality assessment system for electronic components.

The parameters stated in the Test Procedures and Requirements table are based on the required tests and permitted limits of EN 140401-801. The table presents only the most important tests, for the full test schedule refer to the documents listed above. However, some additional tests and a number of improvements against those minimum requirements have been included.

The testing also covers most of the requirements specified by EIA/ECA-703 and JIS-C-5201-1.

The tests are carried out under standard atmospheric conditions in accordance with IEC 60068-1, 4.3, whereupon the following values are applied:

Temperature: 15 °C to 35 °C

Relative humidity: 25 % to 75 %

Air pressure: 86 kPa to 106 kPa (860 mbar to 1060 mbar)

A climatic category LCT / UCT / 56 is applied, defined by the lower category temperature (LCT), the upper category temperature (UCT), and the duration of exposure in the damp heat, steady state test (56 days).

The components are mounted for testing on printed circuit boards in accordance with EN 60115-8, 2.4.2, unless otherwise specified.

TEST PROCEDURES AND REQUIREMENTS					
EN 60115-1 CLAUSE	IEC 60068-2 (1) TEST METHOD	TEST	PROCEDURE	REQUIREMENTS PERMISSIBLE CHANGE (ΔR)	
				HIGH ACCURACY	REGULAR ACCURACY
			Stability for product types:		
			MCS 0402 AT	1 Ω to \leq 47 k Ω	> 47 k Ω to 1 M Ω
			MCT 0603 AT	1 Ω to \leq 100 k Ω	> 100 k Ω to 2 M Ω
			MCU 0805 AT	1 Ω to \leq 100 k Ω	> 100 k Ω to 7.5 M Ω
			MCA 1206 AT	1 Ω to \leq 100 k Ω	> 100 k Ω to 10 M Ω
4.5	-	Resistance		$\pm 1 \% R$; $\pm 0.5 \% R$; $\pm 0.1 \% R$; $\pm 0.05 \% R$	
4.8	-	Temperature coefficient	At (20 / -55 / 20) °C and (20 / 155 / 20) °C	± 50 ppm/K; ± 25 ppm/K; ± 15 ppm/K; ± 10 ppm/K; ± 5 ppm/K	
4.25.1	-	Endurance at 70 °C: general operation mode	$U = \sqrt{P_{70}} \times R$ or $U = U_{max.}$; whichever is the less severe; 1.5 h on; 0.5 h off; 70 °C; 1000 h 70 °C; 8000 h 70 °C; 225 000 h	$\pm (0.05 \% R + 0.01 \Omega)$ $\pm (0.10 \% R + 0.02 \Omega)$ $\pm (0.30 \% R + 0.02 \Omega)$	$\pm (0.10 \% R + 0.02 \Omega)$ $\pm (0.20 \% R + 0.02 \Omega)$ $\pm (0.60 \% R + 0.05 \Omega)$
		Endurance at 70 °C: power operation mode	$U = \sqrt{P_{70}} \times R$ or $U = U_{max.}$; whichever is the less severe; 1.5 h on; 0.5 h off; 70 °C; 1000 h 70 °C; 8000 h 70 °C; 225 000 h	$\pm (0.10 \% R + 0.01 \Omega)$ $\pm (0.20 \% R + 0.02 \Omega)$ $\pm (0.60 \% R + 0.05 \Omega)$	$\pm (0.20 \% R + 0.02 \Omega)$ $\pm (0.40 \% R + 0.05 \Omega)$
		Endurance at 70 °C: advanced operation mode	$U = \sqrt{P_{70}} \times R$ or $U = U_{max.}$; whichever is the less severe; 1.5 h on; 0.5 h off; 70 °C; 1000 h	$\pm (0.20 \% R + 0.05 \Omega)$	$\pm (0.50 \% R + 0.05 \Omega)$
4.25.3	-	Endurance at upper category temperature	125 °C; 1000 h 155 °C; 1000 h 175 °C; 1000 h	$\pm (0.05 \% R + 0.01 \Omega)$ $\pm (0.10 \% R + 0.02 \Omega)$ $\pm (0.50 \% R + 0.05 \Omega)$	$\pm (0.15 \% R + 0.02 \Omega)$ $\pm (0.30 \% R + 0.02 \Omega)$ $\pm (0.50 \% R + 0.05 \Omega)$
4.24	78 (Cab)	Damp heat, steady state	(40 \pm 2) °C; (93 \pm 3) % RH; 56 days	$\pm (0.10 \% R + 0.01 \Omega)$	$\pm (0.10 \% R + 0.02 \Omega)$
4.37	67 (Cy)	Damp heat, steady state accelerated: general operation mode	(85 \pm 2) °C (85 \pm 5) % RH $U = \sqrt{0.1} \times P_{70} \times R$; $U \leq 0.3 \times U_{max.}$; 1000 h	$\pm (0.10 \% R + 0.05 \Omega)$	$\pm (0.50 \% R + 0.05 \Omega)$



TEST PROCEDURES AND REQUIREMENTS					
EN 60115-1 CLAUSE	IEC 60068-2 (1) TEST METHOD	TEST	PROCEDURE	REQUIREMENTS PERMISSIBLE CHANGE (ΔR)	
				HIGH ACCURACY	REGULAR ACCURACY
			Stability for product types:		
			MCS 0402 AT	1 Ω to \leq 47 k Ω	> 47 k Ω to 1 M Ω
			MCT 0603 AT	1 Ω to \leq 100 k Ω	> 100 k Ω to 2 M Ω
			MCU 0805 AT	1 Ω to \leq 100 k Ω	> 100 k Ω to 7.5 M Ω
			MCA 1206 AT	1 Ω to \leq 100 k Ω	> 100 k Ω to 10 M Ω
4.23	2 (Bb)	Climatic sequence: general operation mode	125 °C; 16 h 55 °C; 24 h; \geq 90 % RH; 1 cycle -55 °C; 2 h 8.5 kPa; 2 h; (25 \pm 10) °C 55 °C; 24 h; 90 % RH; 5 cycles $U = \sqrt{P_{70}} \times \bar{R} \leq U_{max.}$; 1 min	\pm (0.25 % R + 0.02 Ω)	
4.23.2		Dry heat			
4.23.3		Damp heat, cyclic			
4.23.4		Cold			
4.23.5		Low air pressure			
4.23.6		Damp heat, cyclic			
4.23.7		DC load			
-	1 (Aa)	Cold / storage at low temperature	-55 °C; 2 h	\pm (0.05 % R + 0.01 Ω)	
4.19	14 (Na)	Rapid change of temperature	30 min at -55 °C and 30 min at 155 °C; 1000 cycles	\pm (0.10 % R + 0.01 Ω) $R < 47R$: \pm (0.25 % R + 0.05 Ω)	\pm (0.25 % R + 0.02 Ω)
		Extended rapid change of temperature	30 min at -40 °C; 30 min at 125 °C; MCS 0402 AT: 3000 cycles MCT 0603 AT: 2000 cycles MCU 0805 AT: 1500 cycles MCA 1206 AT: 1000 cycles	\pm (0.25 % R + 0.05 Ω); (\geq 50 % of initial shear force)	
4.13	-	Short time overload: general operation mode	$U = 2.5 \times \sqrt{P_{70}} \times \bar{R}$ or $U = 2 \times U_{max.}$; whichever is the less severe; 5 s	\pm (0.05 % R + 0.01 Ω)	
		Short time overload: power operation mode	$U = 2.5 \times \sqrt{P_{70}} \times \bar{R}$ or $U = 2 \times U_{max.}$; whichever is the less severe; 5 s	\pm (0.1 % R + 0.01 Ω)	\pm (0.25 % R + 0.05 Ω)
4.27	-	Single pulse high voltage overload: general operation mode	$U = 10 \times \sqrt{P_{70}} \times \bar{R}$ or $U = 2 \times U_{max.}$; whichever is the less severe; 10 pulses 10 μ s/700 μ s	\pm (0.25 % R + 0.05 Ω)	
		Single pulse high voltage overload: power operation mode	$U = 10 \times \sqrt{P_{70}} \times \bar{R}$ or $U = 2 \times U_{max.}$; whichever is the less severe; 10 pulses 10 μ s/700 μ s	\pm (0.50 % R + 0.05 Ω)	
4.39	-	Periodic electric overload: general operation mode	$U = \sqrt{15 \times P_{70}} \times \bar{R}$ or $U = 2 \times U_{max.}$; whichever is the less severe; 0.1 s on; 2.5 s off; 1000 cycles	\pm (0.50 % R + 0.05 Ω)	
		Periodic electric overload: power operation mode	$U = \sqrt{15 \times P_{70}} \times \bar{R}$ or $U = 2 \times U_{max.}$; whichever is the less severe; 0.1 s on; 2.5 s off; 1000 cycles	\pm (1.0 % R + 0.05 Ω)	




TEST PROCEDURES AND REQUIREMENTS					
EN 60115-1 CLAUSE	IEC 60068-2 (1) TEST METHOD	TEST	PROCEDURE	REQUIREMENTS PERMISSIBLE CHANGE (ΔR)	
				HIGH ACCURACY	REGULAR ACCURACY
			Stability for product types:		
			MCS 0402 AT	1 Ω to \leq 47 k Ω	> 47 k Ω to 1 M Ω
			MCT 0603 AT	1 Ω to \leq 100 k Ω	> 100 k Ω to 2 M Ω
			MCU 0805 AT	1 Ω to \leq 100 k Ω	> 100 k Ω to 7.5 M Ω
			MCA 1206 AT	1 Ω to \leq 100 k Ω	> 100 k Ω to 10 M Ω
4.38	-	Electro static discharge (human body model)	IEC 61340-3-1; 3 pos. + 3 neg.; (MIL-STD-883, method 3015) MCS 0402 AT: 500 V MCT 0603 AT: 1000 V MCU 0805 AT: 1500 V MCA 1206 AT: 2000 V	$\pm (0.5 \% R + 0.05 \Omega)$	
4.22	6 (Fc)	Vibration	Endurance by sweeping; 10 Hz to 2000 Hz; no resonance; amplitude 1.5 mm or \leq 200 m/s ² ; 7.5 h	$\pm (0.05 \% R + 0.01 \Omega)$ no visible damage	
4.17	58 (Td)	Solderability	Solder bath method; SnPb40; non-activated flux (215 \pm 3) °C; (3 \pm 0.3) s	Good tinning (95 % covered); no visible damage	
			Solder bath method; SnAg3Cu0.5 or SnAg3.5; non-activated flux; (235 \pm 3) °C; (2 \pm 0.2) s	Good tinning (95 % covered); no visible damage	
4.18	58 (Td)	Resistance to soldering heat	Solder bath method; (260 \pm 5) °C; (10 \pm 1) s	$\pm (0.05 \% R + 0.01 \Omega)$	$\pm (0.05 \% R + 0.01 \Omega)$ $R > 221 \text{ k}\Omega$ in 0402: $\pm (0.10 \% R + 0.01 \Omega)$ $R > 511 \text{ k}\Omega$ in 0603: $\pm (0.10 \% R + 0.01 \Omega)$ $R > 1 \text{ M}\Omega$ in 0805 / 1206: $\pm (0.10 \% R + 0.01 \Omega)$
4.29	45 (XA)	Component solvent resistance	Isopropyl alcohol +50 °C; method 2	No visible damage	
4.32	21 (Ue ₃)	Shear (adhesion)	MCS 0402 AT and MCT 0603 AT: 9 N	No visible damage	
			MCU 0805 AT and MCA 1206 AT: 45 N		
4.33	21 (Ue ₁)	Substrate bending	Depth 2 mm, 3 times	$\pm (0.05 \% R + 0.01 \Omega)$ no visible damage; no open circuit in bent position	
4.7	-	Voltage proof	$U_{RMS} = U_{ins}$; (60 \pm 5) s	No flashover or breakdown	
4.35	-	Flammability	IEC 60695-11-5, needle flame test; 10 s	No burning after 30 s	

Note

(1) The quoted IEC standards are also released as EN standards with the same number and identical contents



DIMENSIONS



DIMENSIONS AND MASS							
TYPE / SIZE	H (mm)	L (mm)	W (mm)	W _T (mm)	T _t (mm)	T _b (mm)	MASS (mg)
MCS 0402 AT	0.32 ± 0.05	1.0 ± 0.05	0.5 ± 0.05	> 75 % of W	0.2 + 0.1 / - 0.15	0.2 ± 0.1	0.6
MCT 0603 AT	0.45 + 0.1 / - 0.05	1.55 ± 0.05	0.85 ± 0.1	> 75 % of W	0.3 + 0.15 / - 0.2	0.3 + 0.15 / - 0.2	1.9
MCU 0805 AT	0.52 ± 0.1	2.0 ± 0.1	1.25 ± 0.15	> 75 % of W	0.4 + 0.1 / - 0.2	0.4 + 0.1 / - 0.2	4.6
MCA 1206 AT	0.55 ± 0.1	3.2 + 0.1 / - 0.2	1.6 ± 0.15	> 75 % of W	0.5 ± 0.25	0.5 ± 0.25	9.2

SOLDERING RECOMMENDATIONS

For recommended solder pad dimensions please refer to www.vishay.com/doc?28950.

For recommended soldering profiles please refer to www.vishay.com/doc?31090.



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Vishay products are not designed for use in life-saving or life-sustaining applications or any application in which the failure of the Vishay product could result in personal injury or death unless specifically qualified in writing by Vishay. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View MCA1206MD3304BP500 on WIN SOURCE](#)

 [Vishay Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management