



**THE DATASHEET OF
MAL215262479E3**



Aluminum Electrolytic Capacitors Radial Miniature, High Voltage




Fig. 1

| QUICK REFERENCE DATA | |
|---|-------------------------|
| DESCRIPTION | VALUE |
| Nominal case sizes (Ø D x L in mm) | 10 x 12 to 18 x 35 |
| Rated capacitance range, C _R | 1.5 µF to 220 µF |
| Tolerance on C _R | ± 20 % |
| Rated voltage range, U _R | 200 V to 450 V |
| Category temperature range | -40 °C to +105 °C |
| Endurance test at 105 °C | 2000 h |
| Useful life at 105 °C: | |
| Case Ø D = 10 mm and 12.5 mm | 3000 h |
| Case Ø D = 16 mm and 18 mm | 4000 h |
| Useful life at 40 °C, 1.6 x I _R applied: | |
| Case Ø D = 10 mm and 12.5 mm | 200 000 h |
| Case Ø D = 16 mm and 18 mm | 260 000 h |
| Shelf life at 0 V, 105 °C | 1000 h |
| Based on sectional specification | IEC 60384-4 / EN 130300 |
| Climatic category IEC 60068 | 40 / 105 / 56 |

FEATURES

- Long useful life: 3000 h to 4000 h at 105 °C
- AEC-Q200 qualified
- Miniaturized, ultra high CV-product per unit volume
- High reliability
- Polarized aluminum electrolytic capacitors, non-solid electrolyte
- Radial leads, cylindrical aluminum case, insulated with a blue sleeve
- Pressure relief
- Charge and discharge proof
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912

 AUTOMOTIVE
GRADE

RoHS
COMPLIANT

APPLICATIONS

- Automotive
- High-reliability and professional applications
- Lighting, monitors, consumer electronics, general industrial
- Filtering of high voltages in power supplies

MARKING

The capacitors are marked (where possible) with the following information:

- Rated capacitance value (in µF)
- Tolerance on rated capacitance, code letter in accordance with IEC 60062 (M for ± 20 %)
- Rated voltage (in V)
- Date code, in accordance with IEC 60062
- Code indicating factory of origin
- Name of manufacturer
- Upper category temperature (105 °C)
- Negative terminal identification
- Series number (152)

| SELECTION CHART FOR C _R , U _R , AND RELEVANT NOMINAL CASE SIZES (Ø D x L in mm) | | | | |
|---|--------------------|-----------|-----------|-----------|
| C _R (µF) | U _R (V) | | | |
| | 200 | 250 | 400 | 450 |
| 1.5 | - | - | - | 10 x 12 |
| 2.2 | - | - | 10 x 12 | 10 x 16 |
| 4.7 | - | - | 10 x 16 | 10 x 20 |
| | - | - | 10 x 12 | - |
| 6.8 | - | - | 10 x 16 | 12.5 x 20 |
| 10 | 10 x 12 | 10 x 16 | 10 x 20 | 12.5 x 20 |
| | 10 x 16 | 12.5 x 20 | 12.5 x 25 | 16 x 25 |
| 22 | - | - | 16 x 20 | 18 x 20 |
| | 10 x 20 | 12.5 x 20 | 16 x 20 | 16 x 35 |
| 33 | - | - | - | 18 x 25 |
| | 12.5 x 20 | 12.5 x 25 | 16 x 25 | 18 x 35 |
| 47 | - | 16 x 20 | - | - |
| | 12.5 x 25 | - | 16 x 35 | - |
| 100 | 16 x 20 | 16 x 25 | 18 x 35 | - |
| 220 | 16 x 35 | - | - | - |


DIMENSIONS in millimeters AND AVAILABLE FORMS


Fig. 2 - Form CA: Long leads




Fig. 3 - Form CB: Cut leads




Fig. 4 - Form TFA: Taped in box (ammopack)

Table 1

| DIMENSIONS in millimeters, MASS AND PACKAGING QUANTITIES | | | | | | | | | |
|--|-----------|-----|---------------------|-------------------|-----------|----------|----------------------|---------|----------|
| NOMINAL CASE SIZE Ø D x L | CASE CODE | Ø d | Ø D _{max.} | L _{max.} | F | MASS (g) | PACKAGING QUANTITIES | | |
| | | | | | | | FORM CA | FORM CB | FORM TFA |
| 10 x 12 | 14 | 0.6 | 10.5 | 13.5 | 5.0 ± 0.5 | ≈ 1.6 | 1000 | 500 | 800 |
| 10 x 16 | 15 | 0.6 | 10.5 | 17.5 | 5.0 ± 0.5 | ≈ 1.9 | 500 | 500 | 800 |
| 10 x 20 | 16 | 0.6 | 10.5 | 22.0 | 5.0 ± 0.5 | ≈ 2.2 | 500 | 500 | 800 |
| 12.5 x 20 | 17 | 0.6 | 13.0 | 22.0 | 5.0 ± 0.5 | ≈ 4.0 | 500 | 500 | 500 |
| 12.5 x 25 | 18 | 0.6 | 13.0 | 27.0 | 5.0 ± 0.5 | ≈ 5.0 | 250 | 250 | 500 |
| 16 x 20 | 19a | 0.8 | 16.5 | 22.0 | 7.5 ± 0.5 | ≈ 6.0 | 250 | 250 | 250 |
| 16 x 25 | 19 | 0.8 | 16.5 | 27.0 | 7.5 ± 0.5 | ≈ 8.0 | 250 | 250 | 250 |
| 16 x 35 | 21 | 0.8 | 16.5 | 37.5 | 7.5 ± 0.5 | ≈ 11.0 | 100 | 100 | - |
| 18 x 20 | 1820 | 0.8 | 18.5 | 22.0 | 7.5 ± 0.5 | ≈ 8.0 | 100 | 100 | - |
| 18 x 25 | 1825 | 0.8 | 18.5 | 27.0 | 7.5 ± 0.5 | ≈ 10.0 | 100 | 100 | - |
| 18 x 35 | 22 | 0.8 | 18.5 | 37.5 | 7.5 ± 0.5 | ≈ 14.5 | 100 | 100 | - |

Note

- For detailed tape dimensions please see www.vishay.com/doc?28360

| ELECTRICAL DATA | |
|-----------------|--|
| SYMBOL | DESCRIPTION |
| C _R | Rated capacitance at 100 Hz, tolerance ± 20 % |
| I _R | Rated RMS ripple current at 100 Hz, 105 °C |
| I _{L1} | Max. leakage current after 1 min at U _R |
| tan δ | Max. dissipation factor at 100 Hz |
| Z | Max. impedance at 10 kHz |

Note

- Unless otherwise specified, all electrical values in Table 2 apply at T_{amb} = 20 °C, P = 86 kPa to 106 kPa, RH = 45 % to 75 %.

ORDERING EXAMPLE

Electrolytic capacitor 152 series

4.7 µF / 400 V; ± 20 %

Nominal case size: Ø 10 mm x 16 mm; form TFA

Ordering code: MAL215236478E3

Former 12NC: 2222 152 36478



Table 2

| ELECTRICAL DATA AND ORDERING INFORMATION | | | | | | | | | |
|--|----------------------------------|---|--|----------------------------------|-----------------|--------------------|-----------------------------|---------|----------|
| U _R (V) | C _R 100 Hz (μF) | NOMINAL CASE SIZE Ø D x L (mm) | I _R 100 Hz 105 °C (mA) | I _{L1} 1 min (μA) | tan δ 100 Hz | Z 10 kHz (Ω) | ORDERING CODE MAL2152 | | |
| | | | | | | | BULK PACKAGING | | TAPED |
| | | | | | | | FORM CA | FORM CB | FORM TFA |
| 200 | 10 | 10 x 12 | 85 | 130 | 0.12 | 6.3 | 52109E3 | 62109E3 | 32109E3 |
| | 22 | 10 x 16 | 120 | 202 | 0.12 | 3.2 | 52229E3 | 62229E3 | 32229E3 |
| | 33 | 10 x 20 | 150 | 268 | 0.12 | 2.3 | 52339E3 | 62339E3 | 32339E3 |
| | 47 | 12.5 x 20 | 240 | 352 | 0.12 | 0.9 | 52479E3 | 62479E3 | 32479E3 |
| | 68 | 12.5 x 25 | 310 | 478 | 0.12 | 0.6 | 52689E3 | 62689E3 | 32689E3 |
| | 100 | 16 x 20 | 340 | 670 | 0.12 | 0.4 | 52101E3 | 62101E3 | 32101E3 |
| | 220 | 16 x 35 | 630 | 1390 | 0.12 | 0.2 | 52221E3 | 62221E3 | - |
| 250 | 10 | 10 x 16 | 105 | 145 | 0.12 | 6.3 | 53109E3 | 63109E3 | 33109E3 |
| | 22 | 12.5 x 20 | 180 | 235 | 0.12 | 2.3 | 53229E3 | 63229E3 | 33229E3 |
| | 33 | 12.5 x 20 | 180 | 318 | 0.12 | 1.5 | 53339E3 | 63339E3 | 33339E3 |
| | 47 | 12.5 x 25 | 310 | 423 | 0.12 | 0.9 | 53479E3 | 63479E3 | 33479E3 |
| | 47 | 16 x 20 | 310 | 423 | 0.12 | 0.9 | 93475E3 | 93476E3 | 93473E3 |
| | 100 | 16 x 25 | 340 | 820 | 0.12 | 0.4 | 53101E3 | 63101E3 | 33101E3 |
| 400 | 2.2 | 10 x 12 | 44 | 96 | 0.15 | 28.0 | 56228E3 | 66228E3 | 36228E3 |
| | 4.7 | 10 x 12 | 48 | 127 | 0.15 | 24.0 | 96475E3 | 96476E3 | 96473E3 |
| | 4.7 | 10 x 16 | 65 | 126 | 0.15 | 18.0 | 56478E3 | 66478E3 | 36478E3 |
| | 6.8 | 10 x 16 | 65 | 152 | 0.15 | 12.0 | 56688E3 | 66688E3 | 36688E3 |
| | 10 | 10 x 20 | 80 | 190 | 0.15 | 9.0 | 56109E3 | 66109E3 | 36109E3 |
| | 22 | 12.5 x 25 | 150 | 334 | 0.15 | 3.8 | 56229E3 | 66229E3 | 36229E3 |
| | 22 | 16 x 20 | 150 | 334 | 0.15 | 3.8 | 96225E3 | 96226E3 | 96223E3 |
| | 33 | 16 x 20 | 190 | 466 | 0.15 | 2.6 | 56339E3 | 66339E3 | 36339E3 |
| | 47 | 16 x 25 | 240 | 634 | 0.15 | 2.0 | 56479E3 | 66479E3 | 36479E3 |
| | 68 | 16 x 35 | 310 | 886 | 0.15 | 1.7 | 56689E3 | 66689E3 | - |
| 100 | 18 x 35 | 380 | 1270 | 0.15 | 0.9 | 56101E3 | 66101E3 | - | |
| 450 | 1.5 | 10 x 12 | 30 | 90 | 0.20 | 26.0 | 57158E3 | 67158E3 | 37158E3 |
| | 2.2 | 10 x 16 | 50 | 99 | 0.20 | 26.0 | 57228E3 | 67228E3 | 37228E3 |
| | 4.7 | 10 x 20 | 65 | 133 | 0.20 | 20.0 | 57478E3 | 67478E3 | 37478E3 |
| | 6.8 | 12.5 x 20 | 80 | 162 | 0.20 | 16.0 | 57688E3 | 67688E3 | 37688E3 |
| | 10 | 12.5 x 20 | 90 | 205 | 0.20 | 10.0 | 57109E3 | 67109E3 | 37109E3 |
| | 22 | 16 x 25 | 150 | 367 | 0.20 | 4.6 | 57229E3 | 67229E3 | 37229E3 |
| | 22 | 18 x 20 | 150 | 367 | 0.20 | 4.6 | 97225E3 | 97226E3 | - |
| | 33 | 16 x 35 | 200 | 516 | 0.20 | 3.4 | 57339E3 | 67339E3 | - |
| | 33 | 18 x 25 | 200 | 516 | 0.20 | 3.4 | 97335E3 | 97336E3 | - |
| 47 | 18 x 35 | 260 | 705 | 0.20 | 2.0 | 57479E3 | 67479E3 | - | |

| ADDITIONAL ELECTRICAL DATA | | |
|------------------------------------|--|---|
| PARAMETER | CONDITIONS | VALUE |
| Voltage | | |
| Surge voltage | U _R = 200 V to 250 V | U _S ≤ 1.15 x U _R |
| | U _R = 400 V to 450 V | U _S ≤ 1.10 x U _R |
| Reverse voltage | | U _{rev} ≤ 1 V |
| Current | | |
| Leakage current | After 1 min at U _R | I _{L1} ≤ 0.03 C _R x U _R + 70 μA |
| | After 5 min at U _R | I _{L5} ≤ 0.015 C _R x U _R + 30 μA |
| Inductance | | |
| Equivalent series inductance (ESL) | Case Ø D = 10 mm | Typ. 16 nH |
| | Case Ø D ≥ 12.5 mm | Typ. 18 nH |
| Resistance | | |
| Equivalent series resistance (ESR) | Calculated from tan δ _{max.} and C _R (see Table 2) | ESR = tan δ/2 π f C _R |

RIPPLE CURRENT AND USEFUL LIFE

Table 3

| ENDURANCE TEST DURATION AND USEFUL LIFE | | | |
|---|-------------------------------|---------------------------------|--|
| NOMINAL CASE SIZE Ø D x L (mm) | ENDURANCE AT 105 °C (h) | USEFUL LIFE AT 105 °C (h) | USEFUL LIFE AT 40 °C 1.6 x I _R APPLIED (h) |
| 10 x 12 | 2000 | 3000 | 200 000 |
| 10 x 16 | 2000 | 3000 | 200 000 |
| 10 x 20 | 2000 | 3000 | 200 000 |
| 12.5 x 20 | 2000 | 3000 | 200 000 |
| 12.5 x 25 | 2000 | 3000 | 200 000 |
| 16 x 20 | 2000 | 4000 | 260 000 |
| 16 x 25 | 2000 | 4000 | 260 000 |
| 16 x 35 | 2000 | 4000 | 260 000 |
| 18 x 20 | 2000 | 4000 | 260 000 |
| 18 x 25 | 2000 | 4000 | 260 000 |
| 18 x 35 | 2000 | 4000 | 260 000 |

Note

- Multiplier of useful life code: CCC206

I_A = Actual ripple current at 100 Hz
 I_R = Rated ripple current at 100 Hz, 105 °C

⁽¹⁾ Useful life at 105 °C and I_R applied
 Case Ø D = 10 mm and 12.5 mm: 3000 h
 Case Ø D = 16 mm and 18 mm: 4000 h




Fig. 5 - Multiplier of useful life as a function of ambient temperature and ripple current load

Table 4

| MULTIPLIER OF RIPPLE CURRENT (I_R) AS A FUNCTION OF FREQUENCY | | | | | | | |
|---|------------------|------|------|------|------|--------|-----------------|
| U_R (V) | FREQUENCY (Hz) | | | | | | |
| | 50 | 100 | 300 | 1000 | 3000 | 10 000 | $\geq 100\ 000$ |
| | I_R MULTIPLIER | | | | | | |
| 200 | 0.75 | 1.00 | 1.50 | 2.00 | 2.20 | 2.50 | 3.00 |
| 250 | 0.75 | 1.00 | 1.50 | 2.00 | 2.20 | 2.50 | 3.00 |
| 400 | 0.75 | 1.00 | 1.30 | 1.60 | 1.90 | 2.20 | 2.50 |
| 450 | 0.75 | 1.00 | 1.30 | 1.60 | 1.90 | 2.20 | 2.50 |

Table 5

| TEST PROCEDURES AND REQUIREMENTS | | | |
|--|--|--|--|
| TEST | | PROCEDURE (quick reference) | REQUIREMENTS |
| NAME OF TEST | REFERENCE | | |
| Endurance | IEC 60384-4 / EN 130300 subclause 4.13 | $T_{amb} = 105\ ^\circ\text{C}$; U_R applied; 2000 h | $\Delta C/C: \pm 20\ \%$ $\tan \delta \leq 2 \times \text{spec. limit}$ $Z \leq 2 \times \text{spec. limit}$ $I_{L5} \leq \text{spec. limit}$ |
| Useful life | CECC 30301 subclause 1.8.1 | $T_{amb} = 105\ ^\circ\text{C}$; U_R and I_R applied; Case $\varnothing D = 10\ \text{mm}$ and $12.5\ \text{mm}$: 3000 h Case $\varnothing D = 16\ \text{mm}$ and $18\ \text{mm}$: 4000 h | $\Delta C/C: \pm 50\ \%$ $\tan \delta \leq 3 \times \text{spec. limit}$ $Z \leq 3 \times \text{spec. limit}$ $I_{L5} \leq \text{spec. limit}$ no short or open circuit total failure percentage: $\leq 1\ \%$ |
| Shelf life (storage at high temperature) | IEC 60384-4 / EN 130300 subclause 4.17 | $T_{amb} = 105\ ^\circ\text{C}$; no voltage applied; 1000 h After test: U_R to be applied for 30 min, 24 h to 48 h before measurement | $\Delta C/C: \pm 20\ \%$ $\tan \delta \leq 2 \times \text{spec. limit}$ $Z \leq 2 \times \text{spec. limit}$ $I_{L5} \leq 2 \times \text{spec. limit}$ |
| Reverse voltage | IEC 60384-4 / EN 130300 subclause 4.15 | $T_{amb} = 105\ ^\circ\text{C}$; 125 h at $U = -1\ \text{V}$, followed by 125 h at U_R | $\Delta C/C: \pm 15\ \%$ $I_{L5} \leq \text{spec. limit}$ $\tan \delta \leq \text{spec. limit}$ |

Statements about product lifetime are based on calculations and internal testing. They should only be interpreted as estimations. Also due to external factors, the lifetime in the field application may deviate from the calculated lifetime. In general, nothing stated herein shall be construed as a guarantee of durability.



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Vishay products are not designed for use in life-saving or life-sustaining applications or any application in which the failure of the Vishay product could result in personal injury or death unless specifically qualified in writing by Vishay. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View MAL215262479E3 on WIN SOURCE](#)

 [Vishay Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management