



**THE DATASHEET OF  
CC7V-T1A-32.768KHZ-7PF-20PPM-TB-QC**




# CC7V-T1A

## Tuning Fork Crystal 32.768 kHz



### DIMENSIONS



### APPLICATIONS

IoT  
 Metering  
 Industrial  
 Automotive  
 Health Care  
 Wearables, Portables

### DESCRIPTION

The CC7V-T1A is a low frequency SMD Quartz Crystal Unit that incorporates a tuning fork Quartz Crystal Resonator. It operates under vacuum in a hermetically sealed ceramic package with ceramic lid.

### FEATURES

Outstanding hermetic sealing with gold-tin preform.  
 High stability and low aging guaranteed by hermetic sealing.  
 Available for extended operating temperature range.  
 Small size, low profile, lightweight (12.5 mg).  
 High shock and vibration resistant.  
 100% Pb-free, RoHS-compliant.  
 Automotive qualification according to AEC-Q200 available.

### ELECTRICAL CHARACTERISTICS AT 25°C

Standard Frequency	<sup>1)</sup> $F_L$	32.768	kHz
Load capacitance	<sup>2)</sup> $C_L$	6.0 / 7.0 / 9.0 / 12.5	pF
Frequency tolerance	<sup>3)</sup> $\Delta F/F$	±20	ppm
	$\Delta F/F$	±100	ppm
Series resistance typ./max.	$R_S$	50 / 70	kΩ
Motional capacitance typ.	$C_1$	3.7	fF
Static capacitance typ.	$C_0$	1.2	pF
Drive level max.	P	1.0	μW
Insulation resistance min.	$R_i$	500	MΩ
Aging first year max.	$\Delta F/F$	±3	ppm
Turnover temperature	$T_0$	25 ±5	°C
Frequency vs. temperature	$\Delta F/F_0$	$-0.035 \text{ ppm}/^\circ\text{C}^2 (T - T_0)^2 \pm 10\%$	ppm

- 1) Other frequencies on request.  
 2) Other load capacitances on request.  
 3) Tighter frequency tolerances on request.

**STANDARD FREQUENCIES**

<b>Frequency</b>
32.768 kHz
Other frequencies on request

**ENVIRONMENTAL CHARACTERISTICS**

		<b>Conditions</b>	<b>Max. Dev.</b>
Storage temperature range		-55 to +125°C	
TA Operating temperature range		-40 to +85°C	
TB Extended oper. temp. range		-40 to +125°C	
TC Extended oper. temp. range		-55 to +125°C	
Shock resistance	ΔF/F	5000 g, 0.3 ms, ½ sine	±5 ppm
Vibration resistance	ΔF/F	20 g / 10–2000 Hz	±5 ppm

**TERMINATIONS AND PROCESSING**

<b>Type</b>	<b>Termination</b>	<b>Processing</b>
CC7V-T1A	Au flashed pads	IPC/JEDEC J-STD-020C 260°C / 20 - 40 s

**ORDERING INFORMATION**

<p style="text-align: center;"><b>C C 7 V - T 1 A 32.768 kHz 12.5 pF ±20 ppm TA QC</b></p> <p><b>Ceramic package</b> ————</p> <p><b>Ceramic lid</b> ————</p> <p><b>Package size</b> ———— 7 = 3.2 x 1.5 x 0.90 mm</p> <p><b>Tuning fork</b> ————</p> <p><b>SMT Package</b> ————</p> <p><b>Au flashed pads</b> ————</p> <p><b>2 pads</b> ————</p>	<p><b>Frequency <math>F_L</math></b></p> <p><b>Load capacitance <math>C_L</math></b> 6.0 pF 7.0 pF 9.0 pF 12.5 pF Other <math>C_L</math> on request</p> <p><b>Frequency tolerance</b> ———— ±20 ppm ±100 ppm Tighter freq. tolerances on request</p> <p><b>Temperature range</b> ———— <b>TA</b> = -40 to +85°C (Standard) <b>TB</b> = -40 to +125°C <b>TC</b> = -55 to +125°C</p> <p><b>Qualification</b> ———— <b>QC</b> = Commercial Grade (Standard) <b>QA</b> = Automotive Grade AEC-Q200 <b>QM</b> = Medical Grade</p>
---	---

A unique part number will be generated for each product specification, i.e:	
20xxx-MG01	1'000 pcs (in 12 mm tape on 7" reel)
20xxx-MG03	3'000 pcs (in 12 mm tape on 7" reel)
20xxx-PG14	14'000 pcs (in 12 mm tape on 13" reel)

All specifications subject to change without notice.



Micro Crystal AG  
Muehlestrasse 14  
CH-2540 Grenchen  
Switzerland

Phone +41 32 655 82 82  
sales@microcrystal.com  
www.microcrystal.com

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

- ⊖ [View CC7V-T1A-32.768KHZ-7PF-20PPM-TB-QC on WIN SOURCE](#)
- ⊖ [Micro Crystal AG Information](#)

## Optimize Your Supply Chain with WIN SOURCE Solutions

- ✓ Global Sourcing Solution
- ✓ Obsolete Management
- ✓ Cost Control Management
- ✓ Shortage Management
- ✓ Alternative Solution
- ✓ Excess Inventory Management