



THE DATASHEET OF
1411340



Housing - HC-EVO-D15-HHFS-PL-BK - 1411340

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



HEAVYCON EVO sleeve housing, plastic, with bayonet flange for EVO screw connection, D15 series, for single locking latch, height: 65.5 mm, without EVO screw connection

Product Features

- Flexible cable outlet direction, lateral or straight
- Lower costs than metal version
- Labeling option using 9 x 20 mm marking label
- Low weight
- Lower risk of condensation
- Both contact insert PE sheets are connected by means of a metal frame integrated in the sleeve housing
- Metal inlays ensure leading PE contact with angled plugs
- Completely corrosion-resistant
- Halogen-free plastic
- Impact test according to IK 08



Key Commercial Data

| | |
|--------------------------------------|----------|
| Packing unit | 1 pc |
| Weight per Piece (excluding packing) | 60.0 g |
| Custom tariff number | 85389099 |
| Country of origin | Poland |

Technical data

Dimensions

| | |
|--------|---------|
| Height | 65.5 mm |
| Width | 30 mm |
| Length | 63.5 mm |

Ambient conditions

Housing - HC-EVO-D15-HHFS-PL-BK - 1411340

Technical data

Ambient conditions

| | |
|--|-----------------------|
| Degree of protection of housing (IP) | IP66 |
| Degree of protection of housing (NEMA) | 4 (UL50e / NEMA 250) |
| | 4X (UL50e / NEMA 250) |
| | 12 (UL50e / NEMA 250) |
| Ambient temperature (operation) | -40 °C ... 125 °C |

General

| | |
|--|---|
| Note | For contact inserts HC-D15, A10 |
| Size | D15 |
| Housing type | Sleeve housing |
| Color | black |
| Locking type | for single locking latch |
| No. of cable outlets | 1 |
| Cable exit | straight |
| | Lateral |
| Screw connection | none |
| Housing material | Polyamide |
| Flammability rating according to UL 94 | V0 |
| Connection | The sleeve base housing must be supplemented with the EVO screw connection. The EVO screw connection is available in 4 sizes. It enables the creation of a straight or lateral cable outlet. The EVO screw connection is mounted by hand or with the aid of a pipe wrench, for example. |

Standards and Regulations

| | |
|--|----|
| Flammability rating according to UL 94 | V0 |
|--|----|

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 5.1 | 27143424 |
| eCl@ss 6.0 | 27143424 |
| eCl@ss 8.0 | 27440202 |
| eCl@ss 9.0 | 27440202 |

ETIM

| | |
|----------|----------|
| ETIM 4.0 | EC000437 |
| ETIM 5.0 | EC000437 |

Housing - HC-EVO-D15-HHFS-PL-BK - 1411340

Approvals

Approvals

Approvals

EAC / GL

Ex Approvals

Approvals submitted


Approval details

EAC

GL

Drawings


Dimensional drawing



Dimensional drawing

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View 1411340 on WIN SOURCE](#)

 [Phoenix Contact Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management