



**THE DATASHEET OF
MAX86170BENG+T**



Low-Noise AFE for Pulse Oximeter and Heart Rate Monitor

General Description

The MAX86170B is an ultra-low-power optical data acquisition system with both transmit and receive channels. On the transmitter side, the MAX86170B has four LED driver output pins, programmable from three high-current, 8-bit LED drivers. On the receiver side, MAX86170B has a low-noise charge integrating front-end that includes a 20-bit ADC and best-in-class ambient light cancellation (ALC) circuit, producing the highest performing integrated optical data acquisition system on the market today.

Due to its low power consumption, compact size, ease-and flexibility-of-use, the MAX86170B is ideal for a wide variety of optical sensing applications such as pulse oximetry and heart rate detection.

The MAX86170B operates on a 1.8V main supply voltage and a 3.1V to 5.5V LED driver supply voltage. The device supports both I²C- and SPI-compatible interfaces in a fully autonomous way. The device has a large 256-word built-in FIFO. The MAX86170B is available in a compact WLP package 2.78mm x 1.71mm with 6 x 4, 0.4mm ball pitch.

Applications

- Wearable Devices for Fitness, Wellness, and Medical Applications
- Clinical Accuracy
- Suitable for Wrist, Finger, Ear, and Other Locations
- Optimized Performance to Detect:
 - Optical Heart Rate
 - Heart-Rate Variability
 - Oxygen Saturation (SpO₂)
 - Body Hydration
 - Muscle and Tissue Oxygen Saturation (SmO₂ and StO₂)
 - Maximum Oxygen Consumption (VO₂ max)

Benefits and Features

- Complete Single-Channel Optical Data Acquisition System
- Ultra Low-Power Operation for Wearable Devices
 - Low-Power Operation, Optical Readout Channel < 11µA at 25fps
 - Exposure Integration Period Ranging from 14.6µs to 117.1µs
 - Low Shutdown Current < 1µA
- Excellent Top-End Dynamic Range > 91dB in White Card Loop-Back Test (Nyquist Sample-to-Sample Variance)
- Extended Dynamic Range up to 109dB (Averaging and Off-Chip Filtering)
- Supports Frame Rates from 1fps to 2.9kfps
- High Resolution 20-Bit Charge Integrating ADC
- Supports Two PD Inputs for Multiparameter Measurements
- Supports Four LED Driver Output Pins Generated from Three 8-Bit LED Current Drivers
- Low Dark Current Noise of < 50pA RMS (Sample to Sample Variance in 117.1µs Integration Time)
- Excellent Ambient Range and Rejection Capability
 - 200µA Ambient Photodiode Current
 - > 70dB Ambient Rejection at 120Hz
- Miniature 2.78mm x 1.71mm, 6 x 4, 0.4mm Ball Pitch WLP Package
- -40°C to +85°C Operating Temperature Range

Visit [Web Support](#) to complete the nondisclosure agreement (NDA) required to receive additional product information.

Rev. 2

DOCUMENT FEEDBACK



TECHNICAL SUPPORT

Information furnished by Analog Devices is believed to be accurate and reliable. However, no responsibility is assumed by Analog Devices for its use, nor for any infringements of patents or other rights of third parties that may result from its use. Specifications subject to change without notice. No license is granted by implication or otherwise under any patent or patent rights of Analog Devices. Trademarks and registered trademarks are the property of their respective owners.



Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

-  [View MAX86170BENG+T on WIN SOURCE](#)
-  [Analog Devices Inc. Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management