



# PIN RECEPTACLES

FOR .022" - .034" DIAMETER PINS AND .025" SQUARE PINS

<p><b>0291</b> 0291-0-15-XX-16-XX-10-0 Hex press-fit in .067 plated through-hole</p>	<p><b>0293</b> 0293-0-15-XX-16-XX-10-0 Press-fit in .067 mounting hole</p>	<p><b>0287</b> 0287-0-15-XX-16-XX-10-0 Solder mount in .065 min. mounting hole Also available on 8mm wide carrier tape: 3,250 parts per 13" reel See page 194.11 for Tape &amp; Reel details</p>	<p><b>0285</b> 0285-0-15-XX-16-XX-10-0 Solder mount in .065 min. mounting hole</p>
<p><b>0284</b> 0284-0-15-XX-16-XX-10-0 Solder mount in .070 min. mounting hole Also available on 24mm wide carrier tape: 1,200 parts per 13" reel See page 194.11 for Tape &amp; Reel details</p>	<p><b>8114</b> 8114-0-15-XX-16-XX-04-0 Press-fit from underside of pc board into .065 mounting hole</p>	<p><b>0407</b> 0407-0-15-XX-16-XX-04-0 Press-fit in .066 mounting hole</p>	<p><b>0415</b> 0415-0-15-XX-16-XX-10-0 Solder mount in .063 min. mounting hole Also available on 24mm wide carrier tape: 1,500 parts per 13" reel See page 194.11 for Tape &amp; Reel details</p>
<p><b>0303</b> 0303-0-19-XX-16-XX-10-0 Press-fit in .067 mounting hole Wire Crimp Termination. Accepts wire sizes 26 AWG Max. / 30 AWG Min.</p>	<p><b>0306</b> 0306-0-19-XX-16-XX-10-0 Wire Crimp Termination. Accepts wire sizes 20 AWG Max. / 24 AWG Min.</p>	<p><b>0273</b> 0273-0-15-XX-16-XX-10-0 Press-fit in .078 mounting hole</p>	<p><b>7520</b> 7520-0-15-XX-16-XX-10-0 Press-fit in .066 mounting hole</p>

**SPECIFICATIONS:**

**Shell Material:** Brass Alloy 360, 1/2 Hard  
**Contact Material:** Beryllium Copper Alloy 172, HT  
**Dimensions:** Inches  
**Tolerances On:** Lengths: ±.005  
 Diameters: ±.002  
 Angles: ± 2°



**ORDER CODE:** XXXX - X - XX - XX - 16 - XX - XX - 0

**BASIC PART #**

- SPECIFY SHELL FINISH:**
- 01 200 μ" TIN/LEAD OVER NICKEL
  - ◆ 80 200 μ" TIN OVER NICKEL (RoHS)
  - ◆ 15 10 μ" GOLD OVER NICKEL (RoHS)

- SPECIFY CONTACT FINISH:**
- 01 200 μ" TIN/LEAD OVER NICKEL
  - ◆ 80 200 μ" TIN OVER NICKEL (RoHS)
  - ◆ 27 30 μ" GOLD OVER NICKEL (RoHS)

**SELECT CONTACT:**

**#16 CONTACT (DATA ON PAGE 256)**

(For alternate contact choices, see group D on page 248)



## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

- ⊖ [View 0287-0-15-80-16-80-10-0 on WIN SOURCE](#)
- ⊖ [Mill-Max Manufacturing Corp. Information](#)

## Optimize Your Supply Chain with WIN SOURCE Solutions

- ✓ Global Sourcing Solution
- ✓ Obsolete Management
- ✓ Cost Control Management
- ✓ Shortage Management
- ✓ Alternative Solution
- ✓ Excess Inventory Management