


**SERIES**

**1330R  
1330**



**Unshielded Surface Mount Inductors**



**Physical Parameters**

|   | Inches            | Millimeters      |
|---|-------------------|------------------|
| A | 0.300 to 0.325    | 7.62 to 8.26     |
| B | 0.105 to 0.125    | 2.67 to 3.18     |
| C | 0.125 to 0.145    | 3.18 to 3.68     |
| D | 0.020 Min.        | 0.508 Min.       |
| E | 0.040 to 0.060    | 1.02 to 1.52     |
| F | 0.190 (Ref. only) | 4.83 (Ref. only) |
| G | 0.070 (Ref. only) | 1.78 (Ref. only) |

**Weight Max (Grams)** 0.30

**Operating Temperature Range**

Phenolic: -55°C to +125°C  
Iron and Ferrite: -55°C to +105°C

**Current Rating at 90°C Ambient**

Phenolic: 35°C Rise  
Iron and Ferrite: 15°C Rise

**Maximum Power Dissipation at 90°C Ambient**

Phenolic: 0.210 W  
Iron: 0.090 W  
Ferrite: 0.073 W

**Marking** Delevan; dash number; date code (YYWWL).

Note: An R before the date code indicates a RoHS component.

Example: 1330-42K  
DELEVAN  
42  
1818A

**Packaging** Tape & reel (16mm): 7" reel, 500 pieces max.; 13" reel, 2200 pieces max.

**Made In the U.S.A.**

| DASH NUMBER* | INDUCTANCE (µH) ±10% | TEST FREQUENCY (MHz) | SRF MINIMUM (MHz) | DC RESISTANCE MAXIMUM (OHMS) | CURRENT RATING MAXIMUM (mA) |
|--------------|----------------------|----------------------|-------------------|------------------------------|-----------------------------|
|--------------|----------------------|----------------------|-------------------|------------------------------|-----------------------------|

| SERIES 1330 PHENOLIC CORE |      |    |      |       |      |      |
|---------------------------|------|----|------|-------|------|------|
| -94K                      | 0.10 | 40 | 25.0 | 680.0 | 0.08 | 1380 |
| -96K                      | 0.12 | 40 | 25.0 | 640.0 | 0.09 | 1300 |
| -00K                      | 0.15 | 38 | 25.0 | 600.0 | 0.10 | 1230 |
| -02K                      | 0.18 | 35 | 25.0 | 550.0 | 0.12 | 1120 |
| -04K                      | 0.22 | 33 | 25.0 | 510.0 | 0.14 | 1040 |
| -06K                      | 0.27 | 33 | 25.0 | 430.0 | 0.16 | 975  |
| -08K                      | 0.33 | 30 | 25.0 | 410.0 | 0.22 | 830  |
| -10K                      | 0.39 | 30 | 25.0 | 365.0 | 0.30 | 710  |
| -12K                      | 0.47 | 30 | 25.0 | 330.0 | 0.35 | 660  |
| -14K                      | 0.56 | 30 | 25.0 | 300.0 | 0.50 | 550  |
| -16K                      | 0.68 | 28 | 25.0 | 275.0 | 0.60 | 500  |
| -18K                      | 0.82 | 28 | 25.0 | 250.0 | 0.85 | 420  |
| -20K                      | 1.00 | 25 | 25.0 | 230.0 | 1.00 | 390  |

| SERIES 1330 IRON CORE |       |    |     |       |      |     |
|-----------------------|-------|----|-----|-------|------|-----|
| -22K                  | 1.20  | 25 | 7.9 | 150.0 | 0.18 | 620 |
| -24K                  | 1.50  | 28 | 7.9 | 140.0 | 0.22 | 560 |
| -26K                  | 1.80  | 30 | 7.9 | 125.0 | 0.30 | 480 |
| -28K                  | 2.20  | 30 | 7.9 | 115.0 | 0.40 | 415 |
| -30K                  | 2.70  | 37 | 7.9 | 100.0 | 0.55 | 355 |
| -32K                  | 3.30  | 45 | 7.9 | 90.0  | 0.85 | 285 |
| -34K                  | 3.90  | 45 | 7.9 | 80.0  | 1.00 | 263 |
| -36K                  | 4.70  | 45 | 7.9 | 75.0  | 1.20 | 239 |
| -38K                  | 5.60  | 50 | 7.9 | 65.0  | 1.80 | 195 |
| -40K                  | 6.80  | 50 | 7.9 | 60.0  | 2.00 | 185 |
| -42K                  | 8.20  | 55 | 7.9 | 55.0  | 2.70 | 160 |
| -44K                  | 10.00 | 55 | 7.9 | 50.0  | 3.30 | 144 |
| -46K                  | 12.0  | 45 | 2.5 | 40.0  | 2.70 | 160 |
| -48K                  | 15.0  | 45 | 2.5 | 35.0  | 2.80 | 157 |
| -50K                  | 18.0  | 45 | 2.5 | 30.0  | 3.10 | 149 |
| -52K                  | 22.0  | 45 | 2.5 | 25.0  | 3.30 | 144 |
| -54K                  | 27.0  | 45 | 2.5 | 20.0  | 3.50 | 140 |

| SERIES 1330 FERRITE CORE |        |    |      |      |       |     |
|--------------------------|--------|----|------|------|-------|-----|
| -56K                     | 33.0   | 35 | 2.5  | 24.0 | 3.40  | 130 |
| -58K                     | 39.0   | 35 | 2.5  | 22.0 | 3.60  | 125 |
| -60K                     | 47.0   | 35 | 2.5  | 20.0 | 4.50  | 110 |
| -62K                     | 56.0   | 35 | 2.5  | 18.0 | 5.70  | 100 |
| -64K                     | 68.0   | 35 | 2.5  | 15.0 | 6.70  | 92  |
| -66K                     | 82.0   | 35 | 2.5  | 14.0 | 7.30  | 88  |
| -68K                     | 100.0  | 35 | 2.5  | 13.0 | 8.00  | 84  |
| -70K                     | 120.0  | 30 | 0.79 | 12.0 | 13.00 | 66  |
| -72K                     | 150.0  | 30 | 0.79 | 11.0 | 15.00 | 61  |
| -74K                     | 180.0  | 30 | 0.79 | 10.0 | 17.00 | 57  |
| -76K                     | 220.0  | 30 | 0.79 | 9.0  | 21.00 | 52  |
| -78K                     | 270.0  | 30 | 0.79 | 8.0  | 25.00 | 47  |
| -80K                     | 330.0  | 30 | 0.79 | 7.0  | 28.00 | 45  |
| -82K                     | 390.0  | 30 | 0.79 | 6.5  | 35.00 | 40  |
| -84K                     | 470.0  | 30 | 0.79 | 6.0  | 42.00 | 36  |
| -86K                     | 560.0  | 30 | 0.79 | 5.0  | 46.00 | 35  |
| -88K                     | 680.0  | 30 | 0.79 | 4.2  | 60.00 | 30  |
| -90K                     | 820.0  | 30 | 0.79 | 3.8  | 65.00 | 29  |
| -92K                     | 1000.0 | 30 | 0.79 | 3.4  | 72.00 | 28  |

Optional Tolerances: J = 5% H = 3% G = 2% F = 1%  
\*Complete part # must include series # PLUS the dash #

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View 1330-32K on WIN SOURCE](#)

 [API Delevan Inc. Information](#)

## Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management