



THE DATASHEET OF 2.4-A-JJ



PRODUCT SPECIFICATION

Part number: 2.4-A-JJ

No. 1042635

Drawing number: W-1046482

Nominal 1 Standard	IEC 61169-40
2 Voltage rating	AC 160V
3 Frequency range	50GHz
4 Impedance	50Ω
5 Operating Temperature Range	-40°C~+85°C
6 Operating Humidity Range	95%RH(Max.) ※No condensation



	Test Items	Test Method/Value	Remarks
ELECTRICAL	1	Insulation Resistance	1000MΩ(Min.) at DC 500V
	2	Withstand voltage	1 minute at AC 500V
	3	Contact resistance	Inner conductor : 4mΩ(Max.) Outer conductor : 2.5mΩ(Max.)
	4	V.S.W.R	DC~50GHz : 1.25(Max.)
MECHANICAL	5	Compatibility	No defects or abnormalities Mating with connector complying with the standard
	6	Tensile strength of coupling mechanism	450N At axial tensile force
	7	Center contact retaining force	0.25N(Min.) With a standard pin gauge
	8	Coupling torque	0.8~1.1N·m

※The structural shape is shown in the attached drawing (Drawing number:W-1046482)



	REVISIONS	DATE
1		
2		
3		

Checked	Approved	Inspected	Preparation
 23.11.30 村	 23.11.30 山本	 23.11.30 澤	 '23,11,30 渡邊直弘

GKQM-24

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

-  [View 2.4-A-JJ on WIN SOURCE](#)
-  [TYCLON Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management