



THE DATASHEET OF 3.5-A-PP



PRODUCT SPECIFICATIONS

Part number: 3.5-A-PP

No. 1042578

Drawing number: U-1046379





Nominal 1 Standard IEC 61169-23
 2 Voltage rating AC 335V
 3 Rated frequency 26.5GHz
 4 Impedance 50Ω
 5 Operating temperature range -40°C~+85°C



		Test Items	Test Method/Value	Remarks
1 2 3 4	E L E C T R I C A L	Insulation resistance	5000MΩ(Min.) at DC 500V	
		Withstanding voltage	1 minute at AC 1000V	
		Contact resistance	Inner conductor : 3.0mΩ(Max.) Outer conductor : 2.5mΩ(Max.)	
		V.S.W.R	DC~26.5GHz : 1.2(Max.)	
5 6 7 8 9	M E C H A N I C A L	Compatibility	No defects or abnormalities	Connecting with a standard-compliant connector
		Tensile strength of coupling mechanism	180N	At axial tensile force
		Coupling torque	0.8N·m ~ 1.1N·m	
10 11	O T H E R S			

※The structural shape is shown in the attached drawing (Drawing number:U-1046379)



REVISIONS		DATE
1		
2		
3		

Checked	Approved	Inspected	Prepared
			

GKQM-24

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

-  [View 3.5-A-PP on WIN SOURCE](#)
-  [TYCLON Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management