



THE DATASHEET OF BNC-0012



PRODUCT SPECIFICATIONS

Part number: BNC-0012

No. 0392673

Drawing number: U-0396559

Nominal	1 Standard	JIS C 5412
	2 Power handling	250mW
	3 Rated frequency	0.1MHz~110MHz
	4 Impedance	50Ω(unbalance)
	5 Operating temperature and humidity range	0°C~+50°C、 30~90%RH※No condensation
	6 Storage temperature and humidity range	-20°C~+70°C、 30~90%RH ※No condensation



	Test Items	Test Method/Value	Remarks
1 E L E C T R I C A L	Frequency characteristic	0.1MHz~110MHz:0.5dB(Max.)	
	Isolation	0.1MHz~110MHz:25dB(Min.)	
	VSWR	0.1MHz~110MHz:1.2(Max.)	
	Insertion loss	0.1MHz~110MHz:3.5dB(Max.)	
5 M E C H A N I C A L O T H E R S	Compatibility	No defects or abnormalities	Connecting with a standard-compliant connector

※The structural shape is shown in the attached drawing (Drawing number:U-0396559)



	REVISIONS	DATE
1		
2		
3		

Checked	Approved	Inspected	Prepared
 三 24.04.15 村	 山 24.04.15 本	 檜 24.04.15 澤	 井 24.04.15 出

GKQM-24

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

-  [View BNC-0012 on WIN SOURCE](#)
-  [TYCLON Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management