



THE DATASHEET OF BNC-0014



PRODUCT SPECIFICATIONS

Part number: BNC-0014

No. 0392674

Drawing number: U-0396560

Nominal	1 Standard	JIS C 5412
	2 Power handling	250mW
	3 Rated frequency	0.1MHz~110MHz
	4 Impedance	50Ω(unbalance)
	5 Operating temperature and humidity range	0°C~+50°C、 30~90%RH※No condensation
	6 Storage temperature and humidity range	-20°C~+70°C、 30~90%RH ※No condensation



	Test Items	Test Method/Value	Remarks	
1	ELECTRICAL	Frequency characteristic	0.1MHz~110MHz: 1.0dB(Max.)	
2		Isolation	0.1MHz~110MHz: 25dB(Min.)	
3		VSWR	0.1MHz~110MHz: 1.2(Max.)	
4		Insertion loss	0.1MHz~110MHz: 7.0dB(Max.)	
5	MECHANICAL	Compatibility	No defects or abnormalities	Connecting with a standard-compliant connector
	OTHERS			

※The structural shape is shown in the attached drawing (Drawing number:U-0396560)



	REVISIONS	DATE
1		
2		
3		

Checked	Approved	Inspected	Prepared
 24.04.15 村	 24.04.15 山本	 24.04.15 樽澤	 24.04.15 井出

GKQM-24

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

-  [View BNC-0014 on WIN SOURCE](#)
-  [TYCLON Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management