



# THE DATASHEET OF BNC-0092C





# PRODUCT SPECIFICATIONS

Part number: BNC-0092C

No. 0392675

Drawing number: U-0396561

Nominal	1 Standard	JEITA RC-5233
	2 Power handling	250mW
	3 Rated frequency	40MHz~900MHz
	4 Impedance	75Ω(unbalance)
	5 Operating temperature and humidity range	0°C~+50°C、 30~90%RH※No condensation
	6 Storage temperature and humidity range	-20°C~+70°C、 30~90%RH ※No condensation



	Test Items	Test Method/Value	Remarks
1 E L E C T R I C A L	Frequency characteristic	40MHz~900MHz: 1.0dB(Max.)	
	Isolation	40MHz~900MHz: 20dB(Min.)	
	VSWR	40MHz~900MHz: 1.5(Max.)	
	Insertion loss	40MHz~900MHz: 4.0dB(Max.)	
5 M E C H A N I C A L	Compatibility	No defects or abnormalities	Connecting with a standard-compliant connector
O T H E R S			

※The structural shape is shown in the attached drawing (Drawing number:U-0396561)



	REVISIONS	DATE
1		
2		
3		

Checked	Approved	Inspected	Prepared
 三 24.04.15 村	 山 24.04.15 本	 檜 24.04.15 澤	 井 24.04.15 出

GKQM-24

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

-  [View BNC-0092C on WIN SOURCE](#)
-  [TYCLON Information](#)

## Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management