



THE DATASHEET OF BNC-0094



PRODUCT SPECIFICATIONS

Part number: BNC-0094

No. 0392672

Drawing number: U-0396557

Nominal	1 Standard	JIS C 5412
	2 Power handling	250mW
	3 Rated frequency	40MHz~900MHz
	4 Impedance	50Ω(unbalance)
	5 Operating temperature and humidity range	0°C~+50°C, 30~90%RH※No condensation
	6 Storage temperature and humidity range	-20°C~+70°C, 30~90%RH ※No condensation



	Test Items	Test Method/Value	Remarks	
1	E L E C T R I C A L	Frequency characteristic	40MHz~900MHz: 2.0dB(Max.)	
2		Isolation	40MHz~900MHz: 20dB(Min.)	
3		VSWR	40MHz~900MHz: 1.5(Max.)	
4		Insertion loss	40MHz~900MHz: 8.0dB(Max.)	
5	M E C H A N I C A L O T H E R S	Compatibility	No defects or abnormalities	
				Connecting with a standard-compliant connector

※The structural shape is shown in the attached drawing (Drawing number:U-0396557)



	REVISIONS	DATE
1		
2		
3		

Checked	Approved	Inspected	Prepared
24.04.11	24.04.11	24.04.11	24.04.11
村	本	澤	出

GKQM-24

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

-  [View BNC-0094 on WIN SOURCE](#)
-  [TYCLON Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management