



THE DATASHEET OF BNC-0302T



PRODUCT SPECIFICATIONS

Part number: BNC-0302T

No. 0392666

Drawing number: U-0396553

Nominal 1 Standard JIS C 5412(BNC50Ω)、JEITA RC-5233(BNC75Ω)

2 Power handling 0.5W

3 Rated frequency 3.5GHz

4 Impedance 75Ω←→50Ω

5 Operating temperature range -10°C~+40°C

6 Operating humidity range 90%(Max.) ※No condensation



		Test Items	Test Method/Value	Remarks	
1	E L E C T R I C A L	V.S.W.R.	DC~2GHz : 1.2(Max.) 2GHz~3.5GHz : 1.25(Max.)		
2		Insertion loss	DC~2GHz : 5.7±0.5dB 2GHz~3.5GHz : 5.7±0.7dB		
3	M E C H A N I C A L	Compatibility	No defects or abnormalities	Connecting with a standard-compliant connector	
	O T H E R S				

※The structural shape is shown in the attached drawing (Drawing number:U-0396553)



	REVISIONS	DATE
1		
2		
3		

Checked	Approved	Inspected	Prepared
三	山	檜	井
24.04.09	24.04.09	24.04.09	24.04.09
村	本	澤	出

GKQM-24

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

-  [View BNC-0302T on WIN SOURCE](#)
-  [TYCLON Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management