



**THE DATASHEET OF
MCX-J-316**



PRODUCT SPECIFICATIONS

Part No. MCX-J-316
 DWG No. Y-1024728
 Nominal 1 Frequency range 6 GHz
 2 Impedance 50Ω

No. 1021781
 To-Conne Co., Ltd. (TYC)

Checked	Inspected	Prepared
山 16.03.08 本	檜 16.03.08 澤	渡邊 16.03.08 直弘



	Test Items	Procedures/Test method	Requirements	
1	DESIGN Materials Finishes	Specified on relevant product drawing (DWG No. Y-1024728)	No defects or abnormalities	
2				
3				
4	ELECTRICAL	Insulation Resistance	DC 500V	1000MΩ (Min.)
5		Withstanding voltage	DC 1000V (1 minute.)	No defects or abnormalities
6		Contact resistance	DC 0.2V、 1A	Inner 5mΩ (Max.) Outer 2.5mΩ (Max.)
7		V. S. W. R	0~3.0GHz 0~6.0GHz	1.3 (Max.) 1.5 (Max.)
8	MECHANICAL	Compatibility	Connecting with a standard-compliant connector	No defects or abnormalities
9		Force to engage/disengage	Force to engage 63N (Max.) Force to disengage 8N~20N	No defects or abnormalities
10		Cable tensile strength	At axial tensile force 44.48N (Min.)	No defects or abnormalities
11	Cable group	RG-316/U、 RG-174/U		

GKQM-19-1

	Remarks	Date
1		
2		
3		

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

-  [View MCX-J-316 on WIN SOURCE](#)
-  [TYCLON Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management