



# THE DATASHEET OF MCX-LP-316





# PRODUCT SPECIFICATIONS

Part No. MCX-LP-316  
 DWG No. Y-1014564  
 Nominal 1 Frequency range 6 GHz  
 2 Impedance 50Ω

No. 1011709  
 To-Conne Co., Ltd. (TYC)

Checked	Inspected	Prepared
山 15.10.19 本	檜 15.10.19 澤	栗 15.10.19 原

	Test Items	Procedures/Test method	Requirements
1	DESIGN	Design & construction	No defects or abnormalities
2		Materials	
3		Finishes	
4	ELECTRICAL	Insulation Resistance	5000MΩ (Min.)
5		Withstanding voltage	DC 1000V (1 minute.)
6		Contact resistance	DC 0.2V、 1A
7		V. S. W. R	0~6.0GHz
8	MECHANICAL	Compatibility	Connecting with a standard-compliant connector
9		Force to engage/disengage	Force to engage 63N (Max.) Force to disengage 8N~20N
10		Center contact capivation	Axial fixing force with body (Speed 60mm/min)
11		Cable tensile strength	At axial tensile force 44.48N (Min.)

GKQM-19-1

	Remarks	Date
1		
2		
3		

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

- ⊖ [View MCX-LP-316](#) on WIN SOURCE
- ⊖ [TYCLON](#) Information

## Optimize Your Supply Chain with WIN SOURCE Solutions

- ✓ Global Sourcing Solution
- ✓ Obsolete Management
- ✓ Cost Control Management
- ✓ Shortage Management
- ✓ Alternative Solution
- ✓ Excess Inventory Management