



THE DATASHEET OF MMCX-J-316



PRODUCT SPECIFICATIONS

Part No. MMCX-J-316
 DWG No. Y-1024727
 Nominal 1 Frequency range 6 GHz
 2 Impedance 50 Ω

No. 1021777

To-Conne Co., Ltd. (TYO)

Checked	Inspected	Prepared
山 16.03.08 本	檜 16.03.08 澤	栗 16.03.08 原



	Test Items	Procedures/Test method	Requirements
1	DESIGN Design & construction Materials Finishes	Specified on relevant product drawing (DWG No. Y-1024727)	No defects or abnormalities
2			
3			
4	ELECTRICAL Insulation Resistance	DC 500V	1000MΩ (Min.)
5		Withstanding voltage DC 500V (1 minute.)	No defects or abnormalities
6		Contact resistance DC 0.2V、 1A	Inner 5mΩ (Max.) Outer 2.5mΩ (Max.)
7		V. S. W. R 0~3.0GHz	1.35 (Max.)
8	Compatibility	Connecting with a standard-compliant connector	No defects or abnormalities
9	MECHANICAL Force to engage/disengage	Force to engage 6.3N (Min.) 36N (Max.) Force to disengage 6.3N (Min.) 36N (Max.)	No defects or abnormalities
10		Cable tensile strength	
11	Cable group	RG-316/U	

GKQM-19-1

	Remarks	Date
1		
2		
3		

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

-  [View MMCX-J-316](#) on WIN SOURCE
-  [TYCLON](#) Information

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management