



**THE DATASHEET OF  
N-0092**





# PRODUCT SPECIFICATIONS

Part number: N-0092

No. 0592585

Drawing number: W-0596403





Nominal 1 Standard JIS C 5411  
 2 Power handling 250mW  
 3 Rated frequency 40MHz~900MHz  
 4 Impedance 50Ω(unbalance)  
 5 Operating temperature 0°C~+50°C、  
 and humidity range 30~90%RH※No condensation  
 6 Storage temperature -20°C~+70°C、  
 and humidity range 30~90%RH ※No condensation



		Test Items	Test Method/Value	Remarks
1 E L E C T R I C A L		Frequency characteristic	40MHz~900MHz: 1.0dB(Max.)	
		Isolation	40MHz~900MHz: 20dB(Min.)	
		VSWR	40MHz~900MHz: 1.5(Max.)	
		Insertion loss	40MHz~900MHz: 4.0dB(Max.)	
5 M E C H A N I C A L		Compatibility	No defects or abnormalities	Connecting with a standard-compliant connector
10 O T H E R S				

※The structural shape is shown in the attached drawing (Drawing number:W-0596403)



	REVISIONS	DATE
1		
2		
3		

Checked	Approved	Inspected	Prepared
 三 24.04.24 村	 山 24.04.24 本	 檜 24.04.24 澤	 上 24.04.24 領

GKQM-24

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

-  [View N-0092 on WIN SOURCE](#)
-  [TYCLON Information](#)

## Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management