



**THE DATASHEET OF  
N-9182**





# PRODUCT SPECIFICATIONS

Part number: N-9182

No. 0592678

Drawing number: U-0596564

Nominal 1 Standard	JIS C 5411
2 Power handling	250mW
3 Rated frequency	900MHz~1800MHz
4 Impedance	50Ω(unbalance)
5 Operating temprure range	-10°C~+50°C



		Test Items	Test Method/Value	Remarks
1	E L E C T R I C A L	Isolation	900MHz~1800MHz: 20dB(Min.)	
2		VSWR	900MHz~1800MHz: 1.3(Max.)	
3		Insertion loss	900MHz~1800MHz: 3.5dB(Max.)	
4	M E C H A N I C A L	Compatibility	No defects or abnormalities	Connecting with a standard-compliant connector
	O T H E R S			

※The structural shape is shown in the attached drawing (Drawing number:U-0596564)



	REVISIONS	DATE
1		
2		
3		

Checked	Approved	Inspected	Prepared
三 24.04.16 村	山 24.04.16 本	檜 24.04.16 澤	井 24.04.16 出

GKQM-24

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

-  [View N-9182 on WIN SOURCE](#)
-  [TYCLON Information](#)

## Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management