



**THE DATASHEET OF
NPJ50AT6G50W-30DB**



PRODUCT SPECIFICATIONS

Part No. NPJ50AT6G50W-30dB

No. 0592415

DWG No. W-0596075

Nominal 1 Standard JIS C 5411
 2 Power handling 50W
 3 Frequency range 6GHz
 4 Impedance 50Ω
 5 [OPR]Temp-Range -45°C~+85°C





		Test Items	Procedures/Test method	Requirements
1	DESIGN	Design & construction	Specified on relevant product drawing (DWG No. W-0596075)	No defects or abnormalities
2		Materials		
3		Finishes		
4	ELECTRICAL	Attenuation	DC~6GHz	30±1.4dB
5		V. S. W. R	DC~3GHz 3~6GHz	1.2 (Max.) 1.3 (Max.)
6	MECHANICAL	Compatibility	Connecting with a standard-compliant connector	No defects or abnormalities
7		Tensile strength of coupling mechanism	At axial tensile force 300N	No defects or abnormalities
8		Connection nut tightening torque	0.9~1.7N·m	
9	ENVIRONMENTAL	Waterproof	IPX7	No water ingress inside the connector

	Remarks	Date
1		
2		
3		

Checked	Approved	Inspected	Prepared
 三 22.08.30 村	 山 22.08.30 本	 檜 22.08.30 澤	 渡邊 '22,08,30 直弘

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

-  [View NPJ50AT6G50W-30dB on WIN SOURCE](#)
-  [TYCLON Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management